



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itaotec

Servidor Itaotec LX201 (Intel Xeon 5130 processor, 2.00GHz)

SPECint_rate2000 = 83.4

SPECint_rate_base2000 = 83.4

SPEC license #: 9001 | Tested by: Itaotec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	116	56.0	4	116	56.0
175.vpr	4	108	60.0	4	108	60.0
176.gcc	4	60.9	83.8	4	60.9	83.8
181.mcf	4	114	73.6	4	114	73.6
186.crafty	4	54.6	84.9	4	54.6	84.9
197.parser	4	118	70.7	4	118	70.7
252.eon	4	50.4	120	4	50.4	120
253.perlbnk	4	79.9	105	4	79.9	105
254.gap	4	65.3	78.1	4	65.3	78.1
255.vortex	4	62.1	142	4	62.1	142
256.bzip2	4	112	62.3	4	112	62.3
300.twolf	4	132	105	4	132	105

Hardware

CPU: Intel Xeon 5130 processor (2.00 GHz, 4MB L2, 1333 MHz system bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4096KB(I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 4x1024MB + 4x512MB FB-DIMM DDR2 SDRAM ECC CL5 667MHz
Disk Subsystem: 1 x 200GB Serial ATA 7200 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio .NET 7.0.9466 (for libraries),
MicroQuill SmartHeap for SMP Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for C programs: -fast -QxP +FDO sh1SMPMt.lib
for C++ programs: -fast -Qcxx_features +FDO

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>