



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB8(1.60GHz, Intel Xeon E5310 processor)

SPECint2000 = 1698

SPECint_base2000 = 1695

SPEC license #01176 Tested by: Supermicro Test date: Nov-2006 Hardware Avail: Nov-2006 Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	141	993	141	994				
175.vpr	1400	112	1251	109	1288				
176.gcc	1100	60.0	1832	60.0	1832				
181.mcf	1800	63.2	2849	63.2	2849				
186.crafty	1000	67.8	1475	67.8	1474				
197.parser	1800	144	1247	144	1247				
252.eon	1300	62.6	2075	63.0	2065				
253.perlbmk	1800	91.3	1972	91.7	1964				
254.gap	1100	64.8	1697	64.8	1697				
255.vortex	1900	66.0	2880	66.0	2880				
256.bzip2	1500	116	1291	116	1292				
300.twolf	3000	164	1832	164	1831				

Hardware

CPU: Intel Xeon E5310 processor (1.60 GHz,1066MHz bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
CPU(s) orderable: 1 chip
Parallel: N/A
Primary Cache: 32KBI + 32KBD on chip per core
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 X 2GB DDR2 ECC CL5 667MHz FBDIMM
Disk Subsystem: 1 X Seagate Barracuda 120GB 7200 RPM
Other Hardware: N/A

Software

Operating System: Windows Server 2003 Enterprise Edition 32-bits w/ SP1
Compiler: Intel C++ Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_CC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB8(1.60GHz, Intel Xeon E5310 processor)

SPECint2000 = 1698

SPECint_base2000 = 1695

SPEC license #01176 | Tested by: Supermicro | Test date: Nov-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO
300.twolf: -fast -O3 +FDO shlw32m.lib

Tested systems can be used with SC816S-R700 case,
To ensure system stability, a 500W (minimum) ATX power supply [4-pin (+12V), 8-pin (+12V) and 24-pin are required]
Product description located as of <http://www.supermicro.com/products/motherboard/Xeon1333/5000P/X7DB8.cfm>

The system bus runs at 1333 MHz

shlw32m-80.lib is the V8.0 SmartHeap library renamed to co-exist with older versions