



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor E5320, 1.86 GHz

SPECint_rate2000 = 77.8

SPECint_rate_base2000 = 77.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Nov-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	125	51.9	4	125	51.9
175.vpr	4	114	57.0	4	114	57.0
176.gcc	4	57.6	88.6	4	57.6	88.6
181.mcf	4	126	66.5	4	126	66.5
186.crafty	4	58.8	79.0	4	58.8	79.0
197.parser	4	129	64.7	4	129	64.7
252.eon	4	54.1	112	4	54.1	112
253.perlbnk	4	82.6	101	4	82.6	101
254.gap	4	77.5	65.8	4	77.5	65.8
255.vortex	4	67.2	131	4	67.2	131
256.bzip2	4	121	57.6	4	121	57.6
300.twolf	4	141	98.9	4	141	98.9

Hardware

CPU: Intel Xeon processor E5320 (1.86 GHz, 2x4MB L2, 1066 MHz system bus)
CPU MHz: 1866
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem: Seagate ST373454SS (SAS, 15.4krpm, 73GB)
Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060323Z (for 32-bit applications),
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries),
SmartHeap Library Version 8.0
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32m.lib
for C++ programs: -fast -Qcxx_features +FDO shlw32m.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 1066 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor E5320, 1.86 GHz

SPECint_rate2000 = 77.8

SPECint_rate_base2000 = 77.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Nov-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

BIOS Configuration:

Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>