



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5148, 2.33 GHz

SPECfp_rate2000 = 73.4

SPECfp_rate_base2000 = 73.4

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Oct-2006 | Software Avail: Jan-2006

250 200 150 100 50					Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
					168.wupwise	4	72.9	102	4	72.9	102
					171.swim	4	273	52.6	4	273	52.6
					172.mgrid	4	176	47.6	4	176	47.6
					173.applu	4	192	50.9	4	192	50.9
					177.mesa	4	59.9	109	4	59.9	109
					178.galgel	4	70.0	192	4	70.0	192
					179.art	4	58.1	208	4	58.1	208
					183.equake	4	119	50.6	4	119	50.6
					187.facerec	4	93.4	94.4	4	93.4	94.4
					188.amp	4	142	71.8	4	142	71.8
					189.lucas	4	174	53.4	4	174	53.4
					191.fma3d	4	182	53.5	4	182	53.5
					200.sixtrack	4	126	40.5	4	126	40.5
					301.apsi	4	204	59.0	4	204	59.0

Hardware

CPU: Intel Xeon processor 5148 (2.33 GHz, 4MB L2, 1333 MHz system bus)
 CPU MHz: 2333
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4MB(I+D) on chip, per chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)
 Disk Subsystem: Seagate ST936701SS (SAS, 10 krpm, 36GB)
 Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
 Kernel 2.6.5-7.244-smp on an x86_64
 Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
 Build 20060120 (for 64-bit applications)
 File System: ext3
 System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
 PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5148, 2.33 GHz

SPECfp_rate2000 = 73.4

SPECfp_rate_base2000 = 73.4

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Oct-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>