



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965SS motherboard(1.8 GHz, Intel(R) Core(TM) 2 Duo processor E4300)

SPECint2000 = --

SPECint_base2000 = 1821

SPEC license #: 13 Tested by: Intel Corporation Test date: Oct-2006 Hardware Avail: Jan-2007 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	127	1106						
175.vpr	1400	106	1318						
176.gcc	1100	54.0	2036						
181.mcf	1800	71.3	2524						
186.crafty	1000	61.0	1638						
197.parser	1800	133	1354						
252.eon	1300	55.9	2325						
253.perlbmk	1800	83.6	2154						
254.gap	1100	57.2	1923						
255.vortex	1900	59.4	3199						
256.bzip2	1500	118	1275						
300.twolf	3000	148	2034						

Hardware

CPU: Intel(R) Core(TM) 2 Duo processor E4300(1.8 GHz, 800 MHz bus)
CPU MHz: 1800
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32KBI + 32KBD per core, on chip
Secondary Cache: 2 MB(I+D) per chip, on chip (shared)
L3 Cache: None
Other Cache: None
Memory: 2 GB (2 1GB Micron MT16HTF12864AY-80ED4 DDR2 800, CL5)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: SoundBlaster Live! PCI card

Software

Operating System: Windows XP Professional SP2
Compiler: Intel C++ Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_CC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M-80.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M-80.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M-80.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965SS motherboard(1.8 GHz, Intel(R) Core(TM) 2 Duo processor E4300)

SPECint2000 = --

SPECint_base2000 = 1821

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Oct-2006 | Hardware Avail: Jan-2007 | Software Avail: May-2006

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO

300.twolf: -fast -O3 +FDO shlw32M-80.lib

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 1/2007:

<http://www.intel.com/products/motherboard/DG965SS/index.htm>

The system bus runs at 800 MHz