



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL480c (2.66 GHz, Intel Xeon processor X5355)

SPECint_rate2000 = 199
SPECint_rate_base2000 = 198

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jan-2007 Hardware Avail: Jan-2007 Software Avail: Nov-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	89.4	145	8	89.5	145
175.vpr	8	91.3	142	8	90.0	144
176.gcc	8	57.8	177	8	57.8	177
181.mcf	8	122	137	8	119	140
186.crafty	8	41.3	225	8	41.3	224
197.parser	8	95.0	176	8	94.8	176
252.eon	8	37.7	320	8	37.7	320
253.perlbnk	8	60.3	277	8	59.3	282
254.gap	8	70.3	145	8	69.9	146
255.vortex	8	51.8	340	8	51.9	340
256.bzip2	8	94.1	148	8	94.1	148
300.twolf	8	97.2	286	8	97.2	286

Hardware

CPU: Intel Xeon processor X5355 (2.66 GHz, 2x4 MB L2 shared, 1333 MHz bus)
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 8 MB I+D on chip per chip (4 MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 16 GB (8x2 GB PC2-5300F CL5)
Disk Subsystem: 1x72 GB 10 K SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise X64 Edition (x86_64) SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20061103Z)
Microsoft Visual Studio .NET 2003 (v7.1.3088, for libraries)
MicroQuill Smartheap Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast +FDO ONESTEP=yes
175.vpr: -fast +FDO ONESTEP=yes
176.gcc: basepeak=1
181.mcf: -fast +FDO
186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib
197.parser: -fast +FDO ONESTEP=yes
252.eon: -fast +FDO
253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib
254.gap: -fast +FDO ONESTEP=yes
255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib
256.bzip2: basepeak=1
```



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL480c (2.66 GHz, Intel Xeon processor X5355)

SPECint_rate2000 = 199
SPECint_rate_base2000 = 198

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jan-2007 | Hardware Avail: Jan-2007 | Software Avail: Nov-2006

Notes/Tuning Information (Continued)

```
300.twolf:      -fast          +FDO          shlw32M.lib
BIOS Configuration Notes
  Power Regulator set to Static High Performance Mode
  Adjacent Sector Prefetch disabled
Other Configuration Notes
  The start /b /wait /affinity command is used to bind CPU(s) to processes.
```