



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation

IBM BladeCenter HS21 XM (1.86 GHz Xeon E5320, 8MB L2 Cache)

SPECint2000 = --

SPECint_base2000 = 1908

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jan-2007 | Hardware Avail: Feb-2007 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	121	1154						
175.vpr	1400	100	1397						
176.gcc	1100	58.0	1897						
181.mcf	1800	59.5	3026						
186.crafty	1000	57.7	1732						
197.parser	1800	125	1442						
252.eon	1300	53.6	2426						
253.perlbmk	1800	79.6	2262						
254.gap	1100	59.5	1848						
255.vortex	1900	58.9	3224						
256.bzip2	1500	105	1435						
300.twolf	3000	139	2153						

Hardware

CPU: Intel Xeon processor E5320 (1.86 GHz, 1066 MHz bus)
CPU MHz: 1866
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 2048 MB ECC PC2-5300F
Disk Subsystem: 73GB SAS 10K RPM
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler: Intel C++ Compiler 9.1 for 32-bit applications
Build 20060323Z
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```