



# CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant BL480c (2.66 GHz, Intel Xeon processor X5355)

SPECfp2000 = **2780**  
SPECfp\_base2000 = **2539**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Feb-2007 Hardware Avail: Jan-2007 Software Avail: Nov-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	44.9	3563	44.9	3563
171.swim	3100	114	2712	110	2817
172.mgrid	1800	101	1775	79.6	2262
173.applu	2100	114	1838	82.1	2558
177.mesa	1400	50.3	2783	46.6	3005
178.galgel	2900	45.8	6336	45.8	6336
179.art	2600	24.7	10541	24.3	10694
183.quake	1300	60.5	2147	49.5	2626
187.facerec	1900	68.1	2788	50.3	3779
188.amp	2200	111	1986	111	1986
189.lucas	2000	97.4	2053	97.0	2061
191.fma3d	2100	103	2037	103	2037
200.sixtrack	1100	108	1021	108	1021
301.apsi	2600	167	1558	158	1645

### Hardware

CPU: Intel Xeon processor X5355 (2.66 GHz, 2x4 MB L2 shared, 1333 MHz bus)  
CPU MHz: 2666  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 4 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 8 MB I+D on chip per chip (4 MB shared per 2 cores)  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 16 GB (8x2 GB PC2-5300F CL5)  
Disk Subsystem: 1x72 GB 10K SAS  
Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64)  
Kernel 2.6.16.21-0.8-default  
Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20061101)  
Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20061101)  
PathScale EKOPath(TM) Compiler Suite, Release 2.5  
File System: ext2  
System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
  -DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch_ahead=5
          -OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
          -LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
          -OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



# CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant BL480c (2.66 GHz, Intel Xeon processor X5355)

SPECfp2000 = 2780  
SPECfp\_base2000 = 2539

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Feb-2007 | Hardware Avail: Jan-2007 | Software Avail: Nov-2006

## Notes/Tuning Information (Continued)

```
177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art:    icc -fast -auto_ilp32 +FDO
183.equake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
            -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t +FDO
188.ammmp: basepeak=1
189.lucas:  ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
200.sixtrack: basepeak=1
301.apsi:   pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t
```

### BIOS Configuration Notes

Power Regulator set to Static High  
Adjacent Sector Prefetch disabled

### Other Configuration Notes

Taskset utility used to bind process to CPU(s)  
Single user kernel used