



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECfp®2006 = 19.5

ProLiant DL380 G5
(2.66 GHz, Intel Xeon processor 5150)

SPECfp_base2006 = 17.1

CPU2006 license: 3


Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jun-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon 5150
 CPU Characteristics: 2.66 GHz, 2x4 MB L2 shared, 1333 MHz system bus
 CPU MHz: 2666
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1 or 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64) SP1
 kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1
 Build 20070824
 Auto Parallel: Yes
 File System: ext2
 System State: Multi-user run level 3
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL380 G5
(2.66 GHz, Intel Xeon processor 5150)

SPECfp2006 = **19.5**

SPECfp_base2006 = **17.1**

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Aug-2007
Hardware Availability: Jun-2006
Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 8 GB (8x1 GB PC2-5300F CL5)
Disk Subsystem: 1x72 GB 10 K SAS
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: binutils-2.17.50

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	421	32.3	422	32.2	<u>422</u>	<u>32.2</u>	<u>412</u>	<u>33.0</u>	412	33.0	413	32.9
416.gamess	1063	18.4	<u>1063</u>	<u>18.4</u>	1061	18.4	1019	19.2	<u>1019</u>	<u>19.2</u>	1022	19.2
433.milc	<u>847</u>	<u>10.8</u>	848	10.8	847	10.8	875	10.5	<u>876</u>	<u>10.5</u>	876	10.5
434.zeusmp	649	14.0	<u>648</u>	<u>14.0</u>	648	14.0	650	14.0	<u>651</u>	<u>14.0</u>	651	14.0
435.gromacs	425	16.8	426	16.8	<u>425</u>	<u>16.8</u>	<u>429</u>	<u>16.6</u>	430	16.6	429	16.6
436.cactusADM	369	32.4	<u>369</u>	<u>32.4</u>	369	32.4	219	54.6	<u>221</u>	<u>54.1</u>	221	54.0
437.leslie3d	<u>590</u>	<u>15.9</u>	590	15.9	590	15.9	<u>590</u>	<u>15.9</u>	590	15.9	590	15.9
444.namd	568	14.1	567	14.1	<u>568</u>	<u>14.1</u>	563	14.2	564	14.2	<u>563</u>	<u>14.2</u>
447.dealII	<u>452</u>	<u>25.3</u>	451	25.3	452	25.3	428	26.8	428	26.7	<u>428</u>	<u>26.7</u>
450.soplex	661	12.6	664	12.6	<u>663</u>	<u>12.6</u>	614	13.6	<u>614</u>	<u>13.6</u>	616	13.5
453.povray	247	21.5	246	21.6	<u>246</u>	<u>21.6</u>	213	25.0	<u>213</u>	<u>24.9</u>	214	24.9
454.calculix	589	14.0	590	14.0	<u>590</u>	<u>14.0</u>	405	20.4	<u>405</u>	<u>20.4</u>	408	20.2
459.GemsFDTD	621	17.1	<u>619</u>	<u>17.2</u>	618	17.2	607	17.5	<u>608</u>	<u>17.5</u>	608	17.5
465.tonto	531	18.5	538	18.3	<u>538</u>	<u>18.3</u>	510	19.3	508	19.4	<u>510</u>	<u>19.3</u>
470.lbm	2106	6.52	<u>2115</u>	<u>6.50</u>	2115	6.50	787	17.5	<u>786</u>	<u>17.5</u>	786	17.5
481.wrf	561	19.9	562	19.9	<u>562</u>	<u>19.9</u>	582	19.2	<u>581</u>	<u>19.2</u>	581	19.2
482.sphinx3	922	21.1	931	20.9	<u>923</u>	<u>21.1</u>	928	21.0	910	21.4	<u>918</u>	<u>21.2</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 200M

Platform Notes

BIOS configuration:
Power Regulator set to Static High Performance Mode



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL380 G5
(2.66 GHz, Intel Xeon processor 5150)

SPECfp2006 = 19.5

SPECfp_base2006 = 17.1

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Aug-2007

Hardware Availability: Jun-2006

Software Availability: Nov-2007

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast -parallel

C++ benchmarks:

-fast -parallel

Fortran benchmarks:

-fast -parallel

Benchmarks using both Fortran and C:

-fast -parallel



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL380 G5
(2.66 GHz, Intel Xeon processor 5150)

SPECfp2006 = 19.5

SPECfp_base2006 = 17.1

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Aug-2007
Hardware Availability: Jun-2006
Software Availability: Nov-2007

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/bin/icpc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/include
```

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL380 G5
(2.66 GHz, Intel Xeon processor 5150)

SPECfp2006 = 19.5

SPECfp_base2006 = 17.1

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Aug-2007

Hardware Availability: Jun-2006

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealIII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch -parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -parallel -prefetch -auto-ilp32

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-flags.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-flags.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL380 G5
(2.66 GHz, Intel Xeon processor 5150)

SPECfp2006 = 19.5

SPECfp_base2006 = 17.1

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Aug-2007
Hardware Availability: Jun-2006
Software Availability: Nov-2007

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:54:01 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 October 2007.