



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp[®]_rate2006 = 59.9

PowerEdge 2950 (Intel Xeon E5345, 2.33GHz)

SPECfp_rate_base2006 = 56.6

CPU2006 license: 55


Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5345
 CPU Characteristics: 1333MHz system bus
 CPU MHz: 2333
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070725
 Auto Parallel: No
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 59.9

PowerEdge 2950 (Intel Xeon E5345, 2.33GHz)

SPECfp_rate_base2006 = 56.6

CPU2006 license: 55

Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB 667 MHz ECC CL5 FB-DIMM)
Disk Subsystem: 1 x 73 GB SAS 15k RPM
Other Hardware: None

Other Software: SmartHeap library V8.1

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3299	33.0	<u>3299</u>	<u>33.0</u>	3299	33.0	8	3269	33.3	<u>3270</u>	<u>33.2</u>	3273	33.2
416.gamess	8	1192	131	<u>1194</u>	<u>131</u>	1194	131	8	<u>1174</u>	<u>133</u>	1174	133	1177	133
433.milc	8	<u>2473</u>	<u>29.7</u>	2473	29.7	2469	29.7	8	<u>2469</u>	<u>29.7</u>	2467	29.8	2472	29.7
434.zeusmp	8	<u>1206</u>	<u>60.3</u>	1206	60.4	1219	59.7	8	<u>1209</u>	<u>60.2</u>	1213	60.0	1205	60.4
435.gromacs	8	526	109	527	108	<u>526</u>	<u>109</u>	8	512	112	<u>511</u>	<u>112</u>	509	112
436.cactusADM	8	1460	65.5	1454	65.7	<u>1458</u>	<u>65.6</u>	8	1327	72.0	<u>1329</u>	<u>71.9</u>	1337	71.5
437.leslie3d	8	3143	23.9	3149	23.9	<u>3145</u>	<u>23.9</u>	8	3086	24.4	<u>3072</u>	<u>24.5</u>	3068	24.5
444.namd	8	655	98.0	655	98.0	<u>655</u>	<u>98.0</u>	8	653	98.2	<u>651</u>	<u>98.5</u>	651	98.6
447.dealII	8	848	108	<u>841</u>	<u>109</u>	826	111	8	<u>811</u>	<u>113</u>	791	116	821	112
450.soplex	8	2071	32.2	<u>2072</u>	<u>32.2</u>	2073	32.2	8	<u>1878</u>	<u>35.5</u>	1873	35.6	1879	35.5
453.povray	8	<u>285</u>	<u>149</u>	288	148	284	150	8	<u>240</u>	<u>177</u>	239	178	240	177
454.calculix	8	744	88.7	<u>735</u>	<u>89.8</u>	735	89.8	8	536	123	<u>538</u>	<u>123</u>	538	123
459.GemsFDTD	8	3578	23.7	<u>3574</u>	<u>23.8</u>	3565	23.8	8	3546	23.9	<u>3545</u>	<u>23.9</u>	3544	23.9
465.tonto	8	991	79.4	994	79.2	<u>991</u>	<u>79.4</u>	8	966	81.5	<u>970</u>	<u>81.2</u>	971	81.1
470.lbm	8	<u>4511</u>	<u>24.4</u>	4511	24.4	4513	24.4	8	<u>4271</u>	<u>25.7</u>	4271	25.7	4270	25.7
481.wrf	8	1947	45.9	<u>1946</u>	<u>45.9</u>	1942	46.0	8	<u>1946</u>	<u>45.9</u>	1952	45.8	1942	46.0
482.sphinx3	8	3176	49.1	3180	49.0	<u>3178</u>	<u>49.1</u>	8	2962	52.6	2957	52.7	<u>2961</u>	<u>52.7</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs

Platform Notes

BIOS Settings:

Adjacent Cache Line Prefetch = Disabled (default Enabled)

Hardware Prefetcher = Disabled (default Enabled)



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 59.9

PowerEdge 2950 (Intel Xeon E5345, 2.33GHz)

SPECfp_rate_base2006 = 56.6

CPU2006 license: 55

Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Nov-2007

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 59.9

PowerEdge 2950 (Intel Xeon E5345, 2.33GHz)

SPECfp_rate_base2006 = 56.6

CPU2006 license: 55

Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Nov-2007

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icpc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/ifort
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 59.9

PowerEdge 2950 (Intel Xeon E5345, 2.33GHz)

SPECfp_rate_base2006 = 56.6

CPU2006 license: 55

Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 59.9

PowerEdge 2950 (Intel Xeon E5345, 2.33GHz)

SPECfp_rate_base2006 = 56.6

CPU2006 license: 55

Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:56:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 16 October 2007.