



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

(Test Sponsor: Intel Corporation)

Supermicro X7DB8+ (Intel Xeon processor E5335, 2.00 GHz)

SPECint®2006 = 18.1

SPECint_base2006 = 15.6

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Aug-2007

Hardware Availability: Jul-2007

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5335
 CPU Characteristics: Quad Core, 2.00 GHz
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8 * 2GB Samsung DDR2 5300F, 2 rank, CL5-5-5, ECC)
 Disk Subsystem: Seagate, SCSI, 73GB, 10Krpm, 1 disk only
 Other Hardware: None

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10 SP1 RC1, Kernel linux-cbmg 2.6.16.43-0.5-smp for x86_64
 Compiler: Intel C++ Compiler for Linux32 and Linux64 Version 10.1 Build 20070725
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap library V8.1 Binutils 2.17.50.0.15



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

(Test Sponsor: Intel Corporation)

Supermicro X7DB8+ (Intel Xeon processor E5335, 2.00 GHz)

SPECint2006 = 18.1

SPECint_base2006 = 15.6

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Aug-2007

Hardware Availability: Jul-2007

Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	749	13.0	<u>745</u>	<u>13.1</u>	743	13.2	599	16.3	<u>602</u>	<u>16.2</u>	602	16.2
401.bzip2	938	10.3	933	10.3	<u>935</u>	<u>10.3</u>	867	11.1	865	11.2	<u>865</u>	<u>11.2</u>
403.gcc	699	11.5	<u>668</u>	<u>12.0</u>	665	12.1	539	14.9	540	14.9	<u>539</u>	<u>14.9</u>
429.mcf	528	17.3	<u>528</u>	<u>17.3</u>	527	17.3	499	18.3	497	18.4	<u>498</u>	<u>18.3</u>
445.gobmk	806	13.0	<u>806</u>	<u>13.0</u>	806	13.0	711	14.8	<u>711</u>	<u>14.8</u>	711	14.8
456.hmmer	890	10.5	<u>890</u>	<u>10.5</u>	889	10.5	<u>512</u>	<u>18.2</u>	513	18.2	512	18.2
458.sjeng	1000	12.1	<u>1000</u>	<u>12.1</u>	998	12.1	<u>897</u>	<u>13.5</u>	900	13.4	893	13.5
462.libquantum	203	102	186	111	<u>198</u>	<u>104</u>	166	125	<u>166</u>	<u>125</u>	167	124
464.h264ref	<u>1080</u>	<u>20.5</u>	1102	20.1	1076	20.6	1010	21.9	<u>1011</u>	<u>21.9</u>	1011	21.9
471.omnetpp	525	11.9	<u>525</u>	<u>11.9</u>	526	11.9	<u>485</u>	<u>12.9</u>	485	12.9	485	12.9
473.astar	<u>702</u>	<u>10.0</u>	730	9.61	699	10.0	<u>631</u>	<u>11.1</u>	632	11.1	630	11.1
483.xalanbmk	<u>393</u>	<u>17.6</u>	393	17.6	393	17.6	<u>393</u>	<u>17.6</u>	393	17.6	393	17.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Bios settings:

Hardware Prefetcher: Enabled

Adjacent Sector Prefetch: Enabled

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer, for peak, are compiled in 64-bit mode

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

462.libquantum: -DSPEC_CPU_LINUX

483.xalanbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

(Test Sponsor: Intel Corporation)

Supermicro X7DB8+ (Intel Xeon processor E5335, 2.00 GHz)

SPECint2006 = 18.1

SPECint_base2006 = 15.6

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Aug-2007

Hardware Availability: Jul-2007

Software Availability: Nov-2007

Base Optimization Flags

C benchmarks:

-fast -vec-guard-write -parallel -par-runtime-control

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/include

456.hmmer: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

(Test Sponsor: Intel Corporation)

Supermicro X7DB8+ (Intel Xeon processor E5335, 2.00 GHz)

SPECint2006 = 18.1

SPECint_base2006 = 15.6

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Aug-2007

Hardware Availability: Jul-2007

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive
-auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll14 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

(Test Sponsor: Intel Corporation)

Supermicro X7DB8+ (Intel Xeon processor E5335, 2.00 GHz)

SPECint2006 = 18.1

SPECint_base2006 = 15.6

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Aug-2007

Hardware Availability: Jul-2007

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.28.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.28.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:56:31 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 16 October 2007.