SPEC® CINT2006 Result

Hewlett-Packard Company

HP Integrity rx2660 (1.66GHz/18MB Dual-Core Intel Itanium)

SPECint®2006 = 17.0

SPECint_base2006 = 15.7

CPU2006 license: 03
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Sep-2007
Hardware Availability: Nov-2007
Software Availability: Sep-2007



Hardware

CPU Name:	Dual-Core Intel Itanium 9140M
CPU Characteristics:	1.66GHz/18MB, 667MHz FSB
CPU MHz:	1666
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1-2 chips
Primary Cache:	16 KB I + 16 KB D on chip per core
Secondary Cache:	1 MB I + 256 KB D on chip per core
L3 Cache:	9 MB I+D on chip per core
Other Cache:	None
Memory:	16 GB (8x2GB DIMMs)
Disk Subsystem:	73GB 10K RPM SAS
Other Hardware:	None

Software

Operating System:	HPUX11i-MCOE B.11.31 (LR)
Compiler:	HP C/aC++ Developer's Bundle C.11.31.03 HP Fortran90 Compiler B.11.31.03
Auto Parallel:	No
File System:	vxfs
System State:	Multi-user
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill Smartheap 8.1

SPEC CINT2006 Result

Hewlett-Packard Company

HP Integrity rx2660 (1.66GHz/18MB Dual-Core Intel Itanium)

SPECint2006 = 17.0

SPECint_base2006 = 15.7

CPU2006 license: 03
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Sep-2007
Hardware Availability: Nov-2007
Software Availability: Sep-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	1000	9.77	1001	9.76	**1000**	**9.77**	835	11.7	**834**	**11.7**	834	11.7
401.bzip2	871	11.1	**871**	**11.1**	871	11.1	**848**	**11.4**	848	11.4	847	11.4
403.gcc	687	11.7	688	11.7	**688**	**11.7**	625	12.9	625	12.9	**625**	**12.9**
429.mcf	492	18.5	**495**	**18.4**	497	18.4	471	19.4	469	19.4	**470**	**19.4**
445.gobmk	867	12.1	868	12.1	**868**	**12.1**	**699**	**15.0**	700	15.0	699	15.0
456.hmmer	331	28.2	332	28.1	**331**	**28.2**	**326**	**28.6**	326	28.6	326	28.6
458.sjeng	**1140**	**10.6**	1140	10.6	1140	10.6	975	12.4	976	12.4	**975**	**12.4**
462.libquantum	333	62.3	334	62.0	**333**	**62.3**	339	61.2	**337**	**61.4**	337	61.4
464.h264ref	979	22.6	**978**	**22.6**	977	22.6	979	22.6	**978**	**22.6**	977	22.6
471.omnetpp	754	8.29	**754**	**8.29**	753	8.30	691	9.05	691	9.05	**691**	**9.05**
473.astar	454	15.5	453	15.5	**453**	**15.5**	450	15.6	**450**	**15.6**	450	15.6
483.xalancbmk	454	15.2	**453**	**15.2**	453	15.2	415	16.6	415	16.6	**415**	**16.6**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
The system had the September 2007 HP-UX 11i v3 Mission Critical
Operating Environment (MCOE) and compilers installed, along with
the following patches:

PHSS_36349  linker + fdp cumulative patch
PHSS_36351  Math Library Cumulative Patch
PHSS_36352  Integrity Unwind Library
PHSS_36350  aC++ Runtime (A.06.15)
PHSS_36354  assembler patch

The following kernel tunables were set, in addition to the defaults
set by the Mission Critical OE:

maxdsiz=3221225472
maxssiz=401604608
maxrsessiz=41943040
```

Platform Notes

```
The "cpuconfig" EFI command was used prior to booting
  to deconfigure processors.

Although two cores were enabled during testing,
  the SPEC CPU2006 benchmarks used only one core.

The setboot command was used to disable hyperthreading.
```

Base Compiler Invocation

C benchmarks:
```
/opt/ansic/bin/cc -Ae
```

C++ benchmarks:
```
/opt/aCC/bin/aCC -Aa
```

Base Portability Flags

400.perlbench: -DSPEC_CPU_HPUX_IA64
403.gcc: -DSPEC_CPU_HPUX
462.libquantum: -DSPEC_CPU_HPUX
483.xalancbmk: -DSPEC_CPU_HPUX_IA64

Base Optimization Flags

C benchmarks:
```
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M
-Wl,+pi,64M -Wl,-N
```

C++ benchmarks:
```
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M
-Wl,+pi,64M -Wl,-N
/opt/smartheap/SmartHeap_8.1/lib/libsmartheapC.a /opt/smartheap/SmartHeap_8.1/lib/libsmartheap.a
```

Peak Compiler Invocation

C benchmarks:
```
/opt/ansic/bin/cc -Ae
```

C++ benchmarks:
```
/opt/aCC/bin/aCC -Aa
```

Peak Portability Flags

400.perlbench: -DSPEC_CPU_HPUX_IA64
403.gcc: -DSPEC_CPU_HPUX
462.libquantum: -DSPEC_CPU_HPUX
483.xalancbmk: -DSPEC_CPU_HPUX_IA64

Peak Optimization Flags

C benchmarks:

400.perlbench: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2)
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared
-Wl,+pd,64M -Wl,+pi,64M -Wl,-N

401.bzip2: Same as 400.perlbench

403.gcc: Same as 400.perlbench

429.mcf: Same as 400.perlbench

445.gobmk: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2)
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared
-Wl,+pd,64M -Wl,+pi,64M +Odataprefetch=direct

456.hmmer: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2)
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared
-Wl,+pd,64M -Wl,+pi,64M

458.sjeng: Same as 445.gobmk

462.libquantum: Same as 456.hmmer

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2)
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared
-Wl,+pd,64M -Wl,+pi,64M
/opt/smartheap/SmartHeap_8.1/lib/libsmartheapC.a /opt/smartheap/SmartHeap_8.1/lib/libsmar

473.astar: +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared
-Wl,+pd,64M -Wl,+pi,64M +Onoparmsoverlap
/opt/smartheap/SmartHeap_8.1/lib/libsmartheapC.a /opt/smartheap/SmartHeap_8.1/lib/libsmar

483.xalancbmk: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2)
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared
-Wl,+pd,64M -Wl,+pi,64M +Onoparmsoverlap
/opt/smartheap/SmartHeap_8.1/lib/libsmartheapC.a /opt/smartheap/SmartHeap_8.1/lib/libsmar

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.07.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.07.xml

Hewlett-Packard Company

HP Integrity rx2660 (1.66GHz/18MB Dual-Core Intel Itanium)

SPECint2006 = 17.0

SPECint_base2006 = 15.7

CPU2006 license: 03
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Sep-2007
Hardware Availability: Nov-2007
Software Availability: Sep-2007

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.
Report generated on Tue Jul 22 14:19:56 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 9 November 2007.