SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (Intel Xeon E5310)

SPECfp®_rate2006 = 44.4

SPECfp_rate_base2006 = 42.4

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Oct-2007
Hardware Availability: Nov-2006
Software Availability: Nov-2007



Hardware

CPU Name:	Intel Xeon E5310
CPU Characteristics:	1066MHz system bus
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1, 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System:	SuSE Linux Enterprise Server 10 EM64T (kernel 2.6.16.21-0.8-smp)
Compiler:	Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070725
Auto Parallel:	Yes
File System:	ReiserFS
System State:	Multi-user, level 3
Base Pointers:	64-bit

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (Intel Xeon E5310)

SPECfp_rate2006 = 44.4

SPECfp_rate_base2006 = 42.4

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Oct-2007
Hardware Availability: Nov-2006
Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
Disk Subsystem: 1 x 73GB 10000PRM SAS HDD
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: MicroQuill SmartHeap Library 8.1

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	4284	25.4	**4283**	**25.4**	4282	25.4	8	4250	25.6	4253	25.6	**4251**	**25.6**
416.gamess	8	1740	90.0	1744	89.8	**1740**	**90.0**	8	1716	91.3	**1715**	**91.3**	1715	91.3
433.milc	8	3068	23.9	**3070**	**23.9**	3071	23.9	8	**3071**	**23.9**	3071	23.9	3070	23.9
434.zeusmp	8	**1590**	**45.8**	1592	45.7	1579	46.1	8	**1587**	**45.9**	1586	45.9	1589	45.8
435.gromacs	8	762	75.0	**761**	**75.0**	761	75.1	8	738	77.4	**738**	**77.4**	738	77.4
436.cactusADM	8	**1897**	**50.4**	1895	50.5	1901	50.3	1	190	63.0	**190**	**62.9**	193	62.0
437.leslie3d	8	4004	18.8	4031	18.7	**4016**	**18.7**	8	3955	19.0	**3944**	**19.1**	3941	19.1
444.namd	8	952	67.4	953	67.3	**953**	**67.3**	8	**951**	**67.5**	952	67.4	951	67.5
447.dealII	8	1093	83.7	1107	82.6	**1093**	**83.7**	8	**1033**	**88.6**	1076	85.1	1026	89.2
450.soplex	8	**2648**	**25.2**	2650	25.2	2641	25.3	8	2406	27.7	2405	27.7	**2405**	**27.7**
453.povray	8	**418**	**102**	418	102	420	101	8	352	121	353	120	**353**	**121**
454.calculix	8	1049	62.9	**1049**	**62.9**	1051	62.8	8	**761**	**86.8**	765	86.3	760	86.9
459.GemsFDTD	8	4549	18.7	**4559**	**18.6**	4567	18.6	8	4531	18.7	**4526**	**18.8**	4522	18.8
465.tonto	8	**1347**	**58.5**	1344	58.6	1347	58.4	8	1313	59.9	**1312**	**60.0**	1312	60.0
470.lbm	8	5750	19.1	**5750**	**19.1**	5750	19.1	2	**1845**	**14.9**	1845	14.9	1845	14.9
481.wrf	8	**2487**	**35.9**	2494	35.8	2485	36.0	8	2494	35.8	2488	35.9	**2490**	**35.9**
482.sphinx3	8	4087	38.2	**4086**	**38.2**	4078	38.2	8	3769	41.4	**3778**	**41.3**	3782	41.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
This results was measured on the Acer Altos R520.
The Altos R720 and Altos R520 are electronically equivalent.

BIOS Settings
  Hardware Prefetcher set to OFF

  Adjacent Cache Line Prefetch set to OFF

  Optimization for high-frequency FSB applications set to OFF

All results used taskset to bind processes to cores.
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

Peak Compiler Invocation

C benchmarks (except as noted below):
```
/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

433.milc: `icc`

C++ benchmarks (except as noted below):
```
icpc
```

450.soplex: `/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icpc -L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib -I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include`

Fortran benchmarks (except as noted below):
```
ifort
```

437.leslie3d: `/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/ifort -L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib -I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include`

Benchmarks using both Fortran and C:
```
icc ifort
```

Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`

Peak Optimization Flags

C benchmarks:

433.milc: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -fno-alias -auto-ilp32`

Continued on next page

Peak Optimization Flags (Continued)

470.lbm: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -scalar-rep- -prefetch -opt-malloc-options=3`

482.sphinx3: `-fast -unroll2`

C++ benchmarks:

444.namd: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -fno-alias -auto-ilp32`

447.dealII: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -ansi-alias -scalar-rep-`

450.soplex: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -opt-malloc-options=3`

453.povray: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4 -ansi-alias`

Fortran benchmarks:

410.bwaves: `-fast -prefetch`

416.gamess: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -Ob0 -ansi-alias -scalar-rep-`

434.zeusmp: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast`

437.leslie3d: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -prefetch -opt-malloc-options=3`

459.GemsFDTD: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -Ob0 -prefetch`

465.tonto: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4 -auto`

Benchmarks using both Fortran and C:

435.gromacs: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -prefetch -auto-ilp32`

436.cactusADM: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -prefetch -parallel -auto-ilp32`

454.calculix: `-fast -unroll-aggressive -auto-ilp32`

481.wrf: `-fast -auto-ilp32`

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:10:24 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 14 November 2007.