



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp®_rate2006 = Not Run

IBM System x3650 (Intel Xeon E5405)

SPECfp_rate_base2006 = 58.2

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Nov-2007

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5405
CPU Characteristics: 1333MHz system bus
CPU MHz: 1995
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64), kernel 2.6.16.21-0.8-smp
Compiler: Intel C++ and Fortran Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008, l_fc_p_10.1.008
Auto Parallel: No
File System: ReiserFS
System State: Multi-user, run level 3
Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = Not Run

IBM System x3650 (Intel Xeon E5405)

SPECfp_rate_base2006 = 58.2

CPU2006 license: 11

Test date: Nov-2007

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8 x 2 GB DDR2-5300F ECC)
 Disk Subsystem: 1 x 36 GB SAS, 15000 RPM
 Other Hardware: None

Peak Pointers: Not Applicable
 Other Software: Binutils 2.17.50.0.15

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	<u>3236</u>	<u>33.6</u>	3237	33.6	3233	33.6							
416.gamess	8	1332	118	<u>1334</u>	<u>117</u>	1335	117							
433.milc	8	<u>2366</u>	<u>31.0</u>	2365	31.1	2367	31.0							
434.zeusmp	8	1175	62.0	1154	63.1	<u>1169</u>	<u>62.3</u>							
435.gromacs	8	<u>576</u>	<u>99.2</u>	576	99.2	575	99.3							
436.cactusADM	8	<u>1427</u>	<u>67.0</u>	1430	66.8	1422	67.2							
437.leslie3d	8	2874	26.2	<u>2860</u>	<u>26.3</u>	2857	26.3							
444.namd	8	<u>762</u>	<u>84.2</u>	766	83.8	762	84.2							
447.dealII	8	856	107	862	106	<u>857</u>	<u>107</u>							
450.soplex	8	<u>1839</u>	<u>36.3</u>	1840	36.3	1838	36.3							
453.povray	8	319	133	<u>319</u>	<u>134</u>	316	135							
454.calculix	8	<u>794</u>	<u>83.1</u>	798	82.8	794	83.1							
459.GemsFDTD	8	3077	27.6	3075	27.6	<u>3077</u>	<u>27.6</u>							
465.tonto	8	863	91.2	865	91.0	<u>864</u>	<u>91.1</u>							
470.lbm	8	4177	26.3	<u>4175</u>	<u>26.3</u>	4175	26.3							
481.wrf	8	1837	48.6	<u>1840</u>	<u>48.6</u>	1842	48.5							
482.sphinx3	8	2402	64.9	2422	64.4	<u>2412</u>	<u>64.6</u>							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

All benchmarks compiled in 64-bit mode
 Hardware Sector Prefetch Disabled and Adjacent Sector Prefetch Disabled
 OMP_NUM_THREADS set to number of cores
 KMP_AFFINITY set to physical,0
 KMP_STACKSIZE set to 64M
 Powersaved dameon was disabled in OS
 taskset utility used to bind CPU(s) to processes

Base Compiler Invocation

C benchmarks:
 icc

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = Not Run

IBM System x3650 (Intel Xeon E5405)

SPECfp_rate_base2006 = 58.2

CPU2006 license: 11

Test date: Nov-2007

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

Base Compiler Invocation (Continued)

C++ benchmarks:

`icpc`

Fortran benchmarks:

`ifort`

Benchmarks using both Fortran and C:

`icc ifort`

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.games: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

`-fast`

C++ benchmarks:

`-fast`

Fortran benchmarks:

`-fast`

Benchmarks using both Fortran and C:

`-fast`



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = Not Run

IBM System x3650 (Intel Xeon E5405)

SPECfp_rate_base2006 = 58.2

CPU2006 license: 11

Test date: Nov-2007

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.11.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.11.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 15:08:27 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 26 December 2007.