



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5460,3.16GHz)

SPECfp®2006 = 23.3

SPECfp\_base2006 = 19.6

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Mar-2008

Hardware Availability: Feb-2008

Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon X5460  
 CPU Characteristics: 3.16 GHz, 2x6 MB L2 shared, 1333 MHz bus  
 CPU MHz: 3167  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smpp  
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070913 Package ID: l\_cc\_p\_10.1.008, l\_fc\_p\_10.1.008  
 Auto Parallel: Yes  
 File System: ext2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5460,3.16GHz)

SPECfp2006 = 23.3

SPECfp\_base2006 = 19.6

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Mar-2008  
Hardware Availability: Feb-2008  
Software Availability: Nov-2007

L3 Cache: None  
Other Cache: None  
Memory: 12 GB (12x1 GB PC2-5300F, 2 rank, CL5-5-5, ECC)  
Disk Subsystem: 1x73.2 GB SAS, 15000RPM  
Other Hardware: None

System State: Run level 3 (multi-user)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: binutils-2.17.tar.gz, Version 2.17

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	432	31.5	<b>429</b>	<b>31.6</b>	429	31.7	426	31.9	424	32.1	<b>425</b>	<b>32.0</b>
416.gamess	874	22.4	878	22.3	<b>876</b>	<b>22.3</b>	829	23.6	<b>829</b>	<b>23.6</b>	829	23.6
433.milc	<b>863</b>	<b>10.6</b>	862	10.6	864	10.6	862	10.6	<b>861</b>	<b>10.7</b>	859	10.7
434.zeusmp	557	16.3	<b>557</b>	<b>16.3</b>	556	16.4	<b>577</b>	<b>15.8</b>	577	15.8	577	15.8
435.gromacs	350	20.4	350	20.4	<b>350</b>	<b>20.4</b>	348	20.5	350	20.4	<b>350</b>	<b>20.4</b>
436.cactusADM	298	40.1	<b>298</b>	<b>40.0</b>	299	40.0	120	99.8	<b>120</b>	<b>99.6</b>	121	99.0
437.leslie3d	<b>487</b>	<b>19.3</b>	484	19.4	492	19.1	<b>487</b>	<b>19.3</b>	484	19.4	492	19.1
444.namd	480	16.7	<b>479</b>	<b>16.8</b>	478	16.8	475	16.9	<b>475</b>	<b>16.9</b>	476	16.8
447.dealII	405	28.2	405	28.2	<b>405</b>	<b>28.2</b>	<b>381</b>	<b>30.0</b>	381	30.1	381	30.0
450.soplex	671	12.4	<b>671</b>	<b>12.4</b>	670	12.4	597	14.0	<b>596</b>	<b>14.0</b>	596	14.0
453.povray	203	26.2	201	26.5	<b>202</b>	<b>26.4</b>	171	31.2	169	31.5	<b>169</b>	<b>31.5</b>
454.calculix	493	16.7	494	16.7	<b>494</b>	<b>16.7</b>	<b>335</b>	<b>24.7</b>	335	24.7	340	24.2
459.GemsFDTD	<b>585</b>	<b>18.1</b>	586	18.1	585	18.1	578	18.3	577	18.4	<b>577</b>	<b>18.4</b>
465.tonto	441	22.3	<b>438</b>	<b>22.5</b>	438	22.5	418	23.6	<b>418</b>	<b>23.5</b>	419	23.5
470.lbm	1882	7.30	1873	7.34	<b>1882</b>	<b>7.30</b>	590	23.3	592	23.2	<b>592</b>	<b>23.2</b>
481.wrf	<b>501</b>	<b>22.3</b>	500	22.3	501	22.3	<b>508</b>	<b>22.0</b>	508	22.0	509	22.0
482.sphinx3	726	26.9	704	27.7	<b>713</b>	<b>27.3</b>	684	28.5	672	29.0	<b>679</b>	<b>28.7</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores

## Platform Notes

Bios settings:  
Intel SpeedStep Technology: Disabled

## General Notes

All benchmarks compiled in 64-bit mode except 450.soplex,  
470.lbm and 482.sphinx3, for peak, are compiled in 32-bit mode

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5460,3.16GHz)

SPECfp2006 = 23.3

SPECfp\_base2006 = 19.6

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Mar-2008

Hardware Availability: Feb-2008

Software Availability: Nov-2007

## General Notes (Continued)

The NEC Express5800/120Lj(Intel Xeon X5460) and the Bull NovaScale T860 E1(Intel Xeon X5460,3.16GHz) models are electronically equivalent. The results have been measured on a NEC Express5800/120Lj(Intel Xeon X5460) model.

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-fast -parallel

C++ benchmarks:

-fast -parallel

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5460,3.16GHz)

SPECfp2006 = 23.3

SPECfp\_base2006 = 19.6

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Mar-2008  
Hardware Availability: Feb-2008  
Software Availability: Nov-2007

## Base Optimization Flags (Continued)

Fortran benchmarks:  
-fast -parallel

Benchmarks using both Fortran and C:  
-fast -parallel

## Peak Compiler Invocation

C benchmarks (except as noted below):  
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include  
  
433.milc: icc

C++ benchmarks (except as noted below):  
icpc  
  
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5460,3.16GHz)

SPECfp2006 = 23.3

SPECfp\_base2006 = 19.6

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** NEC Corporation

**Test date:** Mar-2008  
**Hardware Availability:** Feb-2008  
**Software Availability:** Nov-2007

## Peak Optimization Flags

### C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: -fast -prefetch -parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5460,3.16GHz)

SPECfp2006 = 23.3

SPECfp\_base2006 = 19.6

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Mar-2008

Hardware Availability: Feb-2008

Software Availability: Nov-2007

## Peak Optimization Flags (Continued)

481.wrf: -fast -parallel -prefetch -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090713.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090713.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 18:13:10 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 8 April 2008.