



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp®2006 = 16.5

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECfp_base2006 = 13.6

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Mar-2008

Hardware Availability: Oct-2007

Software Availability: Oct-2007



Hardware

CPU Name: POWER6
 CPU Characteristics: 3500
 CPU MHz: Integrated
 FPU: 1 core, 1 chip, 2 cores/chip
 CPU(s) enabled: 4,8,12,16 cores
 CPU(s) orderable: 64 KB I + 64 KB D on chip per core
 Primary Cache: 4 MB I+D on chip per core
 Secondary Cache:

Continued on next page

Software

Operating System: IBM AIX 5L V5.3 updated with the 5300-07 Technology Level
 Compiler: XL C/C++ Enterprise Edition V9 for AIX Updated with the Oct2007 PTF.
 XL Fortran Enterprise Edition V11.1 for AIX Updated with the Oct2007 PTF.
 Auto Parallel: No
 File System: AIX/JFS2
 System State: Multi-user

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 16.5

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECfp_base2006 = 13.6

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Mar-2008

Hardware Availability: Oct-2007

Software Availability: Oct-2007

L3 Cache: 32 MB I+D off chip per chip
Other Cache: None
Memory: 128 GB (64x2 GB) DDR2 667 MHz
Disk Subsystem: 2x73 GB SAS 15K RPM
Other Hardware: None

Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: --

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	479	28.4	479	28.4	479	28.4	296	45.9	296	45.9	296	45.9
416.gamess	1877	10.4	1877	10.4	1877	10.4	1761	11.1	1761	11.1	1761	11.1
433.milc	638	14.4	638	14.4	638	14.4	575	16.0	575	16.0	575	16.0
434.zeusmp	977	9.31	977	9.32	977	9.32	476	19.1	476	19.1	475	19.2
435.gromacs	913	7.82	913	7.82	913	7.82	763	9.36	763	9.36	762	9.36
436.cactusADM	862	13.9	862	13.9	862	13.9	622	19.2	623	19.2	623	19.2
437.leslie3d	405	23.2	405	23.2	405	23.2	380	24.7	380	24.7	380	24.7
444.namd	623	12.9	623	12.9	623	12.9	580	13.8	580	13.8	580	13.8
447.dealII	711	16.1	711	16.1	711	16.1	711	16.1	711	16.1	711	16.1
450.soplex	579	14.4	579	14.4	579	14.4	554	15.0	555	15.0	555	15.0
453.povray	581	9.16	581	9.16	581	9.15	455	11.7	455	11.7	456	11.7
454.calculix	716	11.5	716	11.5	716	11.5	638	12.9	638	12.9	638	12.9
459.GemsFDTD	939	11.3	939	11.3	939	11.3	774	13.7	774	13.7	774	13.7
465.tonto	1491	6.60	1491	6.60	1491	6.60	854	11.5	854	11.5	854	11.5
470.lbm	368	37.3	368	37.3	368	37.3	360	38.1	360	38.1	360	38.1
481.wrf	1203	9.29	1203	9.29	1203	9.29	1196	9.34	1196	9.34	1194	9.35
482.sphinx3	820	23.8	820	23.8	820	23.8	733	26.6	732	26.6	732	26.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

See flags file of details on following settings.

all ulimits set to unlimited.

Environment variables set before executing benchmarks:

MALLOCOPTIONS=pool

MEMORY_AFFINITY=MCM

XLFRTIOPTS=intrinthds=1

System set to "Enhanced" mode when defining partition on HMC.

Remote console disabled in /etc/inittab.

fdpr binary optimization tool used for:

Speed run on 1 core partition defined on HMC.

128 16M large pages defined with vmo command

410.bwaves 433.milc 435.gromacs 436.cactusADM

453.povray 470.lbm 482.sphinx3



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 16.5

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECfp_base2006 = 13.6

CPU2006 license: 20

Test date: Mar-2008

Test sponsor: Bull SAS

Hardware Availability: Oct-2007

Tested by: Bull SAS

Software Availability: Oct-2007

Base Compiler Invocation

C benchmarks:

```
/usr/vac/bin/xlc -qlanglvl=extc99
```

C++ benchmarks:

```
/usr/vacpp/bin/xlC
```

Fortran benchmarks:

```
/usr/bin/xlf95
```

Benchmarks using both Fortran and C:

```
/usr/vac/bin/xlc -qlanglvl=extc99 /usr/bin/xlf95
```

Base Portability Flags

```
410.bwaves: -qfixed
416.gamess: -qfixed
434.zeusmp: -qfixed
435.gromacs: -qfixed -qextname
436.cactusADM: -qfixed -qextname
437.leslie3d: -qfixed
454.calculix: -qfixed -qextname
481.wrf: -DSPEC_CPU_AIX -DNOUNDERSCORE
482.sphinx3: -qchars=signed
```

Base Optimization Flags

C benchmarks:

```
-bmaxdata:0x40000000 -O5 -qlargepage -D_ILS_MACROS -blpdata
```

C++ benchmarks:

```
-bmaxdata:0x50000000 -O5 -qlargepage -D_ILS_MACROS -qrtti=all
-D__IBM_FAST_VECTOR -blpdata
```

Fortran benchmarks:

```
-bmaxdata:0x60000000 -O5 -qlargepage -qsmallstack=dynlenonheap
-qalias=nostd -blpdata
```

Benchmarks using both Fortran and C:

```
-bmaxdata:0x60000000 -O5 -qlargepage -D_ILS_MACROS
-qsmallstack=dynlenonheap -qalias=nostd -blpdata
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 16.5

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECfp_base2006 = 13.6

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Mar-2008
Hardware Availability: Oct-2007
Software Availability: Oct-2007

Base Other Flags

C benchmarks:
-qipa=noobject -qipa=threads -qsuppress=1500-036

C++ benchmarks:
-qipa=noobject -qipa=threads -qsuppress=1500-036

Fortran benchmarks:
-qipa=noobject -qsuppress=1500-010 -qsuppress=cmpmsg -qipa=threads
-qsuppress=1500-036

Benchmarks using both Fortran and C:
-qipa=noobject -qsuppress=1500-010 -qsuppress=cmpmsg -qipa=threads
-qsuppress=1500-036

Peak Compiler Invocation

C benchmarks:
/usr/vac/bin/xlc -qlanglvl=extc99

C++ benchmarks:
/usr/vacpp/bin/xlC

Fortran benchmarks:
/usr/bin/xlf95

Benchmarks using both Fortran and C:
/usr/vac/bin/xlc -qlanglvl=extc99 /usr/bin/xlf95

Peak Portability Flags

410.bwaves: -qfixed
416.gamess: -qfixed
434.zeusmp: -qfixed
435.gromacs: -qfixed -qextname
436.cactusADM: -qfixed -qextname
437.leslie3d: -qfixed
454.calculix: -qfixed -qextname
481.wrf: -DSPEC_CPU_AIX -DNOUNDERSCORE
482.sphinx3: -qchars=signed

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 16.5

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECfp_base2006 = 13.6

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Mar-2008

Hardware Availability: Oct-2007

Software Availability: Oct-2007

Peak Optimization Flags (Continued)

433.milc: -bmaxdata:0x40000000 -O5 -qlargepage -D_ILS_MACROS
-qalign=natural -qfdpr -blpdata

470.lbm: -O5 -qlargepage -D_ILS_MACROS -qfdpr -q64 -blpdata

482.sphinx3: -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qlargepage -qenablevmx
-qvecnv1 -D_ILS_MACROS -qfdpr -blpdata

C++ benchmarks:

444.namd: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -D_ILS_MACROS

447.dealIII: -bmaxdata:0x50000000 -O5 -qlargepage -D_ILS_MACROS
-qrtti=all -D__IBM_FAST_VECTOR -blpdata

450.soplex: -bmaxdata:0x40000000 -qpdf1(pass 1) -qpdf2(pass 2) -O4
-qlargepage -qenablevmx -qvecnv1 -qstrict -D_ILS_MACROS
-blpdata

453.povray: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qlargepage -qenablevmx
-qvecnv1 -D_ILS_MACROS -qalign=natural -qfdpr -blpdata

Fortran benchmarks:

410.bwaves: -bmaxdata:0x50000000 -O5 -qlargepage -qenablevmx -qvecnv1
-qfdpr -qsmallstack=dynlenonheap -blpdata

416.gamess: -bmaxdata:0x40000000 -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qalias=nostd

434.zeusmp: -bmaxdata:0x40000000 -qpdf1(pass 1) -qpdf2(pass 2) -O3
-qarch=auto -qtune=auto -qlargepage -qenablevmx -qvecnv1
-qxlf90=nosignedzero -blpdata

437.leslie3d: -O4 -qlargepage -q64 -blpdata

459.GemsFDTD: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qlargepage -qenablevmx
-qvecnv1 -q64 -blpdata

465.tonto: -bmaxdata:0x20000000 -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qlargepage -blpdata

Benchmarks using both Fortran and C:

435.gromacs: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qlargepage -qenablevmx
-qvecnv1 -qfdpr -D_ILS_MACROS -blpdata

436.cactusADM: -bmaxdata:0x60000000 -qpdf1(pass 1) -qpdf2(pass 2) -O2
-qarch=auto -qtune=auto -qlargepage -qenablevmx -qvecnv1
-qfdpr -qnostrict -D_ILS_MACROS -blpdata

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 16.5

Bull Escala PL1660 (3.5 GHz, 1 core)

SPECfp_base2006 = 13.6

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Mar-2008

Hardware Availability: Oct-2007

Software Availability: Oct-2007

Peak Optimization Flags (Continued)

454.calculix: -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qlargepage
-D_ILS_MACROS -blpdata

481.wrf: -bmaxdata:0x30000000 -O5 -qlargepage -qalias=nostd
-D_ILS_MACROS -blpdata

Peak Other Flags

C benchmarks:

-qipa=noobject -qipa=threads -qsuppress=1500-036

C++ benchmarks:

-qipa=noobject -qipa=threads -qsuppress=1500-036

Fortran benchmarks:

-qipa=noobject -qsuppress=1500-010 -qsuppress=cmpmsg -qipa=threads
-qsuppress=1500-036

Benchmarks using both Fortran and C:

-qipa=noobject -qsuppress=1500-010 -qsuppress=cmpmsg -qipa=threads
-qsuppress=1500-036

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.06.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.06.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 18:22:38 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 April 2008.