



SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp®_rate2006 = 76.8

CELSIUS V840, AMD Opteron 2346 HE (1.8 GHz)

SPECfp_rate_base2006 = 69.1

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jun-2008

Hardware Availability: May-2008

Software Availability: May-2008



Hardware

CPU Name: AMD Opteron 2346 HE
 CPU Characteristics:
 CPU MHz: 1800
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: PGI Workstation Complete Version 7.2-1 PathScale Compiler Suite, Release 3.2 Beta
 Auto Parallel: No
 File System: ext3
 System State: Multi-User SuSE Run Level 3
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = **76.8**

CELSIUS V840, AMD Opteron 2346 HE (1.8 GHz)

SPECfp_rate_base2006 = **69.1**

CPU2006 license: 22

Test date: Jun-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2008

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008

L3 Cache: 2 MB I+D on chip per chip
Other Cache: None
Memory: 16 GB (8x2GB PC2-5300P, CL5, dual rank ECC)
Disk Subsystem: 1 x 400 GB SATA II, 7200 rpm
Other Hardware: None

Other Software: binutils 2.18.50

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	1804	60.3	1597	68.1	1601	67.9	8	1458	74.6	1452	74.9	1452	74.9
416.gamess	8	1769	88.6	1765	88.7	1767	88.7	8	1622	96.6	1620	96.7	1623	96.5
433.milc	8	1290	56.9	1288	57.0	1289	57.0	8	1265	58.1	1264	58.1	1265	58.1
434.zeusmp	8	968	75.2	963	75.6	959	75.9	8	968	75.2	963	75.6	959	75.9
435.gromacs	8	796	71.8	794	71.9	795	71.9	8	653	87.4	653	87.5	653	87.5
436.cactusADM	8	1171	81.6	1195	80.0	1197	79.9	8	1069	89.5	1075	89.0	1079	88.6
437.leslie3d	8	1550	48.5	1554	48.4	1552	48.4	8	1450	51.9	1449	51.9	1447	52.0
444.namd	8	951	67.4	951	67.5	951	67.5	8	841	76.3	840	76.4	839	76.5
447.dealII	8	989	92.5	986	92.8	973	94.1	8	705	130	703	130	700	131
450.soplex	8	1350	49.4	1336	49.9	1337	49.9	8	1363	49.0	1333	50.0	1328	50.3
453.povray	8	471	90.4	467	91.1	470	90.5	8	399	107	400	106	399	107
454.calculix	8	712	92.8	712	92.7	711	92.8	8	608	109	607	109	606	109
459.GemsFDTD	8	1931	44.0	1923	44.1	1925	44.1	8	1714	49.5	1710	49.6	1711	49.6
465.tonto	8	1006	78.3	1010	78.0	1007	78.1	8	853	92.3	853	92.2	847	92.9
470.lbm	8	2296	47.9	2379	46.2	2380	46.2	8	2289	48.0	2290	48.0	2291	48.0
481.wrf	8	1141	78.3	1142	78.3	1143	78.2	8	1080	82.7	1084	82.4	1084	82.4
482.sphinx3	8	1959	79.6	1956	79.7	1960	79.6	8	1873	83.3	1872	83.3	1872	83.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

powersave -f is applied to set CPU to maximum frequency prior to run
stacksize is set to unlimited prior to run
ulimit -l 2457600
PGI_HUGE_PAGES set to 150
(Total number of huge pages available is 1200)

General Notes

The command numactl has been used to bind processes to CPUs

For information about Fujitsu Siemens Computers please see:
<http://www.fujitsu-siemens.com>



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 76.8

CELSIUS V840, AMD Opteron 2346 HE (1.8 GHz)

SPECfp_rate_base2006 = 69.1

CPU2006 license: 22

Test date: Jun-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2008

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008

Base Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp

Fortran benchmarks:

pgf95

Benchmarks using both Fortran and C:

pgcc pgf95

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -Mnomain
 436.cactusADM: -DSPEC_CPU_LP64 -Mnomain
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -Mnomain
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fastsse -Msmartalloc=huge:150 -Mfprelaxed -Mipa=jobs:4 -Mipa=fast
-Mipa=inline -tp barcelona-64 -Bstatic_pgi

C++ benchmarks:

-fastsse -Msmartalloc=huge:150 -Mfprelaxed --zc_eh -Mipa=jobs:4
-Mipa=fast -Mipa=inline -tp barcelona-64 -Bstatic_pgi

Fortran benchmarks:

-fastsse -Mfprelaxed -Msmartalloc=huge:150 -Mipa=jobs:4 -Mipa=fast
-Mipa=inline -tp barcelona-64 -Bstatic_pgi

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 76.8

CELSIUS V840, AMD Opteron 2346 HE (1.8 GHz)

SPECfp_rate_base2006 = 69.1

CPU2006 license: 22

Test date: Jun-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2008

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-fastsse -Msmartalloc=huge:150 -Mfprelaxed -Mipa=jobs:4 -Mipa=fast
-Mipa=inline -tp barcelona-64 -Bstatic_pgi

Peak Compiler Invocation

C benchmarks (except as noted below):

pgcc

470.lbm: pathcc

C++ benchmarks (except as noted below):

pathCC

444.namd: pgcpp

Fortran benchmarks (except as noted below):

pathf95

410.bwaves: pgf95

434.zeusmp: pgf95

437.leslie3d: pgf95

Benchmarks using both Fortran and C (except as noted below):

pgcc pgf95

436.cactusADM: pathcc pathf95

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -Mnomain
436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -Mnomain
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 76.8

CELSIUS V840, AMD Opteron 2346 HE (1.8 GHz)

SPECfp_rate_base2006 = 69.1

CPU2006 license: 22

Test date: Jun-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2008

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008

Peak Portability Flags (Continued)

481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Peak Optimization Flags

C benchmarks:

433.milc: -fastsse -Msmartalloc=huge:150 -Msafeptr -Mfprelaxed
-Mipa=jobs:4 -Mipa=inline -Mipa=arg -Mipa=const -Mipa=ptr
-Mipa=shape -tp barcelona-64 -Bstatic_pgi

470.lbm: -march=barcelona -Ofast -CG:sse_cse_regs=0
-CG:locs_shallow_depth=1 -m3dnw

482.sphinx3: -Mphi=indirect(pass 1) -Mpfo=indirect(pass 2)
-Mipa=jobs:4(pass 2) -Mipa=fast(pass 2) -Mipa=inline(pass 2)
-fastsse -Mfprelaxed -Msmartalloc -tp barcelona-64
-Bstatic_pgi

C++ benchmarks:

444.namd: -Mphi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2)
-Mipa=fast(pass 2) -Mipa=inline(pass 2) -fastsse
-Munroll=n:4 -Munroll=m:8 -Msmartalloc=huge:150 -Mnodepch
-Mfprelaxed --zc_eh -tp barcelona-64 -Bstatic_pgi

447.dealIII: -march=barcelona -Ofast -static -INLINE:aggressive=on
-fno-exceptions -m32

450.soplex: -march=barcelona -fb_create fbdata(pass 1)
-fb_opt fbdata(pass 2) -O3 -TENV:frame_pointer=off
-LNO:prefetch=1 -OPT:malloc_alg=1 -CG:load_exe=0 -m32

453.povray: -march=barcelona -fb_create fbdata(pass 1)
-fb_opt fbdata(pass 2) -Ofast

Fortran benchmarks:

410.bwaves: -Mphi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2)
-Mipa=fast(pass 2) -Mipa=inline(pass 2) -fastsse
-Msmartalloc -Mprefetch=distance:12 -Mprefetch=nta -Mpre
-Mfprelaxed -tp barcelona-64 -Bstatic_pgi

416.gamess: -march=barcelona -fb_create fbdata(pass 1)
-fb_opt fbdata(pass 2) -O2 -OPT:Ofast -OPT:ro=3
-OPT:unroll_size=256

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp_rate2006 = 76.8

CELSIUS V840, AMD Opteron 2346 HE (1.8 GHz)

SPECfp_rate_base2006 = 69.1

CPU2006 license: 22

Test date: Jun-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2008

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008

Peak Optimization Flags (Continued)

434.zeusmp: basepeak = yes

437.leslie3d: -Mphi=indirect(pass 1) -Mpfo=indirect(pass 2)
-Mipa=jobs:4(pass 2) -Mipa=fast(pass 2) -Mipa=inline(pass 2)
-fastsse -Mvect=fuse -Msmartalloc=huge:150
-Mprefetch=distance:8 -Mprefetch=t0 -Mfprelaxed
-tp barcelona-64 -Bstatic_pgi

459.GemsFDTD: -march=barcelona -Ofast -LNO:fission=2 -LNO:simd=2
-LNO:prefetch_ahead=1 -CG:load_exe=0

465.tonto: -march=barcelona -Ofast -OPT:alias=no_f90_pointer_alias
-LNO:blocking=off -CG:load_exe=1 -IPA:plimit=525

Benchmarks using both Fortran and C:

435.gromacs: -fastsse -Msmartalloc=huge:150 -Mfprelaxed -Mfpapprox=rsqrt
-Mipa=jobs:4 -Mipa=fast -Mipa=inline -tp barcelona-64
-Bstatic_pgi

436.cactusADM: -march=barcelona -fb_create fbdata(pass 1)
-fb_opt fbdata(pass 2) -Ofast -LNO:blocking=off

454.calculix: -Mphi=indirect(pass 1) -Mpfo=indirect(pass 2)
-Mipa=jobs:4(pass 2) -Mipa=fast(pass 2) -Mipa=inline(pass 2)
-fastsse -Msmartalloc=huge:150 -Mprefetch=t0 -Mpre
-Mfprelaxed -tp barcelona-64 -Bstatic_pgi

481.wrf: -fastsse -Mvect=noaltcode -Msmartalloc
-Mprefetch=distance:8 -Mfprelaxed -tp barcelona-64
-Bstatic_pgi

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/fsc-mix-pgi-path.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/fsc-mix-pgi-path.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Sep 13 11:30:53 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 July 2008.