



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/i120Ra-e1
(Intel Xeon L5410)

SPECfp[®]_rate2006 = 38.5

SPECfp_rate_base2006 = 36.0

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2008

Hardware Availability: May-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon L5410
 CPU Characteristics: 2.33 GHz, 2x6 MB L2 shared, 1333 MHz bus
 CPU MHz: 2333
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler for Linux version 10.1 Build 20070913 Package ID: l_cc_p_10.1.008, l_fc_p_10.1.008
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run level 3 (multi-user)

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/i120Ra-e1
(Intel Xeon L5410)

SPECfp_rate2006 = 38.5

SPECfp_rate_base2006 = 36.0

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Jun-2008
Hardware Availability: May-2008
Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (4x4 GB PC2-5300P, 2 rank, CL5-5-5, ECC)
Disk Subsystem: 1x80.0 GB SATAII, 7200RPM
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: binutils 2.17

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2381	22.8	<u>2381</u>	<u>22.8</u>	2380	22.8	4	2362	23.0	<u>2361</u>	<u>23.0</u>	2361	23.0
416.gamess	4	<u>1142</u>	<u>68.6</u>	1142	68.6	1142	68.6	4	1128	69.4	1125	69.6	<u>1126</u>	<u>69.5</u>
433.milc	4	1814	20.2	1807	20.3	<u>1813</u>	<u>20.2</u>	4	<u>1802</u>	<u>20.4</u>	1805	20.3	1800	20.4
434.zeusmp	4	<u>947</u>	<u>38.4</u>	947	38.4	950	38.3	4	<u>966</u>	<u>37.7</u>	954	38.2	966	37.7
435.gromacs	4	<u>495</u>	<u>57.7</u>	494	57.8	496	57.6	4	<u>481</u>	<u>59.4</u>	480	59.5	483	59.1
436.cactusADM	4	<u>1190</u>	<u>40.2</u>	1193	40.1	1186	40.3	1	236	50.7	234	51.2	<u>234</u>	<u>51.0</u>
437.leslie3d	4	2140	17.6	2148	17.5	<u>2142</u>	<u>17.6</u>	4	<u>2091</u>	<u>18.0</u>	2085	18.0	2092	18.0
444.namd	4	652	49.2	651	49.3	<u>651</u>	<u>49.2</u>	4	647	49.5	647	49.6	<u>647</u>	<u>49.5</u>
447.dealII	4	729	62.8	724	63.2	<u>726</u>	<u>63.0</u>	4	696	65.8	692	66.1	<u>694</u>	<u>65.9</u>
450.soplex	4	1414	23.6	1413	23.6	<u>1414</u>	<u>23.6</u>	4	1275	26.2	<u>1277</u>	<u>26.1</u>	1277	26.1
453.povray	4	270	78.9	<u>272</u>	<u>78.2</u>	274	77.7	4	231	92.1	<u>231</u>	<u>92.3</u>	231	92.3
454.calculix	4	<u>682</u>	<u>48.4</u>	685	48.2	681	48.4	4	481	68.6	484	68.2	<u>484</u>	<u>68.2</u>
459.GemsFDTD	4	2314	18.3	<u>2313</u>	<u>18.4</u>	2311	18.4	4	<u>2330</u>	<u>18.2</u>	2328	18.2	2331	18.2
465.tonto	4	725	54.3	728	54.1	<u>725</u>	<u>54.3</u>	4	<u>711</u>	<u>55.3</u>	707	55.7	714	55.2
470.lbm	4	3339	16.5	<u>3336</u>	<u>16.5</u>	3336	16.5	4	3115	17.6	<u>3114</u>	<u>17.6</u>	3114	17.6
481.wrf	4	<u>1400</u>	<u>31.9</u>	1401	31.9	1397	32.0	4	<u>1403</u>	<u>31.8</u>	1394	32.0	1404	31.8
482.sphinx3	4	<u>1931</u>	<u>40.4</u>	1924	40.5	1948	40.0	4	1780	43.8	1816	42.9	<u>1781</u>	<u>43.8</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
except for 436.cactusADM at peak.
OMP_NUM_THREADS set to number of cores

Platform Notes

Bios settings:
Hardware Prefetcher: Disabled
Adjacent Cache Line Prefetch: Disabled
Intel SpeedStep Technology: Disabled



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/i120Ra-e1
(Intel Xeon L5410)

SPECfp_rate2006 = 38.5

SPECfp_rate_base2006 = 36.0

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Jun-2008
Hardware Availability: May-2008
Software Availability: Nov-2007

General Notes

All benchmarks compiled in 64-bit mode except 437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3, for peak, are compiled in 32-bit mode

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/i120Ra-e1
(Intel Xeon L5410)

SPECfp_rate2006 = 38.5

SPECfp_rate_base2006 = 36.0

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Jun-2008
Hardware Availability: May-2008
Software Availability: Nov-2007

Base Optimization Flags (Continued)

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib  
-I/opt/intel/fc/10.1.008/include
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
433.milc: -DSPEC_CPU_LP64  
434.zeusmp: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/i120Ra-e1
(Intel Xeon L5410)

SPECfp_rate2006 = 38.5

SPECfp_rate_base2006 = 36.0

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Jun-2008
Hardware Availability: May-2008
Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/i120Ra-e1
(Intel Xeon L5410)

SPECfp_rate2006 = 38.5

SPECfp_rate_base2006 = 36.0

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2008

Hardware Availability: May-2008

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 19:52:26 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 July 2008.