



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp[®]_rate2006 = 37.9

PowerEdge M600 (Intel Xeon E5205, 1.86 GHz)

SPECfp_rate_base2006 = 34.9

CPU2006 license: 55


Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Feb-2008

Tested by: Dell Inc.

Software Availability: May-2008



Hardware

CPU Name: Intel Xeon E5205
 CPU Characteristics: 1866
 CPU MHz: 1866
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 6 MB I+D on chip per chip

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16-60.0.21-smp
 Compiler: Intel C++ and Fortran Compiler 10.1 for Linux Build 20080312 Package ID: l_cc_p_10.1.015, l_fc_p_10.1.015
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 37.9

PowerEdge M600 (Intel Xeon E5205, 1.86 GHz)

SPECfp_rate_base2006 = 34.9

CPU2006 license: 55

Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Feb-2008

Tested by: Dell Inc.

Software Availability: May-2008

L3 Cache: None
Other Cache: None
Memory: 16 GB (8 x 2 GB 667 MHz ECC CL5 FB-DIMM)
Disk Subsystem: 1 x 80 GB 5400 RPM SATA
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.18.50.0.7.20080502

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1886	28.8	<u>1883</u>	<u>28.9</u>	1882	28.9	4	<u>1848</u>	<u>29.4</u>	1846	29.4	1848	29.4
416.gamess	4	1428	54.8	<u>1429</u>	<u>54.8</u>	1432	54.7	4	<u>1410</u>	<u>55.6</u>	1410	55.6	1412	55.5
433.milc	4	1913	19.2	1909	19.2	<u>1911</u>	<u>19.2</u>	4	1890	19.4	<u>1896</u>	<u>19.4</u>	1897	19.4
434.zeusmp	4	<u>947</u>	<u>38.4</u>	951	38.3	945	38.5	4	943	38.6	939	38.8	<u>940</u>	<u>38.7</u>
435.gromacs	4	<u>600</u>	<u>47.6</u>	598	47.7	602	47.4	4	594	48.1	596	47.9	<u>594</u>	<u>48.1</u>
436.cactusADM	4	1198	39.9	<u>1199</u>	<u>39.9</u>	1206	39.6	1	266	45.0	263	45.4	<u>265</u>	<u>45.1</u>
437.leslie3d	4	1720	21.9	<u>1726</u>	<u>21.8</u>	1732	21.7	4	1691	22.2	1692	22.2	<u>1692</u>	<u>22.2</u>
444.namd	4	<u>813</u>	<u>39.5</u>	816	39.3	813	39.5	4	807	39.8	820	39.1	<u>808</u>	<u>39.7</u>
447.dealII	4	<u>746</u>	<u>61.3</u>	745	61.4	763	60.0	4	<u>715</u>	<u>64.0</u>	714	64.1	717	63.8
450.soplex	4	1322	25.2	1333	25.0	<u>1332</u>	<u>25.0</u>	4	1208	27.6	1203	27.7	<u>1207</u>	<u>27.6</u>
453.povray	4	341	62.3	<u>340</u>	<u>62.5</u>	340	62.6	4	287	74.0	288	73.9	<u>288</u>	<u>73.9</u>
454.calculix	4	825	40.0	<u>823</u>	<u>40.1</u>	821	40.2	4	572	57.7	<u>570</u>	<u>57.9</u>	567	58.2
459.GemsFDTD	4	2123	20.0	<u>2112</u>	<u>20.1</u>	2093	20.3	4	2052	20.7	<u>2048</u>	<u>20.7</u>	2044	20.8
465.tonto	4	794	49.6	797	49.4	<u>797</u>	<u>49.4</u>	4	774	50.8	<u>775</u>	<u>50.8</u>	781	50.4
470.lbm	4	<u>3597</u>	<u>15.3</u>	3598	15.3	3597	15.3	4	2396	22.9	2395	22.9	<u>2395</u>	<u>22.9</u>
481.wrf	4	<u>1134</u>	<u>39.4</u>	1132	39.5	1136	39.3	4	1132	39.5	<u>1134</u>	<u>39.4</u>	1145	39.0
482.sphinx3	4	<u>2052</u>	<u>38.0</u>	2052	38.0	2059	37.9	4	1906	40.9	1886	41.3	<u>1888</u>	<u>41.3</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

Operating System Notes

'ulimit -s unlimited' was used to set the stack size to unlimited prior to run

Platform Notes

BIOS Settings:
Adjacent Cache Line Prefetch = Disabled (default Enabled)
Hardware Prefetcher = Disabled (default Enabled)



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 37.9

PowerEdge M600 (Intel Xeon E5205, 1.86 GHz)

SPECfp_rate_base2006 = 34.9

CPU2006 license: 55

Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Feb-2008

Tested by: Dell Inc.

Software Availability: May-2008

General Notes

All benchmarks compiled in 64-bit mode except 437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode
taskset was used to bind processes to cores except
for 436.cactusADM peak
OMP_NUM_THREADS set to number of processors
KMP_AFFINITY set to "physical,0"
KMP_STACKSIZE set to 64M

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 37.9

PowerEdge M600 (Intel Xeon E5205, 1.86 GHz)

SPECfp_rate_base2006 = 34.9

CPU2006 license: 55

Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Feb-2008

Tested by: Dell Inc.

Software Availability: May-2008

Base Optimization Flags (Continued)

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

Peak Compiler Invocation

C benchmarks (except as noted below):

/opt/intel/cc/10.1.015/bin/icc -L/opt/intel/cc/10.1.015/lib
-I/opt/intel/cc/10.1.015/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.1.015/bin/icpc -L/opt/intel/cc/10.1.015/lib
-I/opt/intel/cc/10.1.015/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/fc/10.1.015/bin/ifort -L/opt/intel/fc/10.1.015/lib
-I/opt/intel/fc/10.1.015/include

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 37.9

PowerEdge M600 (Intel Xeon E5205, 1.86 GHz)

SPECfp_rate_base2006 = 34.9

CPU2006 license: 55

Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Feb-2008

Tested by: Dell Inc.

Software Availability: May-2008

Peak Portability Flags (Continued)

465.tonto: -DSPEC_CPU_LP64

481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 37.9

PowerEdge M600 (Intel Xeon E5205, 1.86 GHz)

SPECfp_rate_base2006 = 34.9

CPU2006 license: 55

Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Feb-2008

Tested by: Dell Inc.

Software Availability: May-2008

Peak Optimization Flags (Continued)

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-fp-linux64-revD.20090713.html>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.07.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-fp-linux64-revD.20090713.xml>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.07.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 19:12:38 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 September 2008.