



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7440, 2.40 GHz)

SPECfp<sup>®</sup>\_rate2006 = 126

SPECfp\_rate\_base2006 = 118

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Jan-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008



### Hardware

CPU Name: Intel Xeon E7440  
 CPU Characteristics: 1066 MHz system bus  
 CPU MHz: 2400  
 FPU: Integrated  
 CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip  
 CPU(s) orderable: 1,2,3,4 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 6 MB I+D on chip per chip, 3 MB shared / 2 cores

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP2, Kernel 2.6.16.60-0.21-smp  
 Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080730 Package ID: l\_cproc\_b\_11.0.042, l\_fproc\_b\_11.0.042  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7440, 2.40 GHz)

SPECfp\_rate2006 = 126

SPECfp\_rate\_base2006 = 118

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Jan-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008

L3 Cache: 16 MB I+D on chip per chip  
Other Cache: None  
Memory: 32 GB (16 x 2GB DDR2-667 FBDIMM)  
Disk Subsystem: 1x146 GB SAS, 10000 RPM  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	3851	56.5	3841	56.6	<b>3848</b>	<b>56.5</b>	16	3852	56.4	3834	56.7	<b>3848</b>	<b>56.5</b>
416.gamess	16	<b>1097</b>	<b>286</b>	1096	286	1099	285	16	1080	290	1076	291	<b>1079</b>	<b>290</b>
433.milc	16	2288	64.2	<b>2285</b>	<b>64.3</b>	2282	64.4	16	2282	64.4	<b>2278</b>	<b>64.5</b>	2277	64.5
434.zeusmp	16	1296	112	<b>1297</b>	<b>112</b>	1298	112	16	1293	113	<b>1302</b>	<b>112</b>	1305	112
435.gromacs	16	<b>492</b>	<b>232</b>	492	232	493	232	16	488	234	488	234	<b>488</b>	<b>234</b>
436.cactusADM	16	1287	149	1280	149	<b>1282</b>	<b>149</b>	1	81.0	148	<b>81.0</b>	<b>148</b>	81.2	147
437.leslie3d	16	2730	55.1	2747	54.8	<b>2738</b>	<b>54.9</b>	16	2682	56.1	2694	55.8	<b>2691</b>	<b>55.9</b>
444.namd	16	<b>621</b>	<b>207</b>	621	207	627	205	16	625	205	633	203	<b>632</b>	<b>203</b>
447.dealII	16	938	195	932	196	<b>932</b>	<b>196</b>	16	914	200	<b>906</b>	<b>202</b>	903	203
450.soplex	16	<b>2107</b>	<b>63.3</b>	2108	63.3	2104	63.4	16	1917	69.6	1916	69.6	<b>1917</b>	<b>69.6</b>
453.povray	16	275	310	270	316	<b>271</b>	<b>314</b>	16	<b>230</b>	<b>371</b>	230	371	230	371
454.calculix	16	<b>547</b>	<b>241</b>	558	237	546	242	16	558	236	<b>546</b>	<b>242</b>	544	243
459.GemsFDTD	16	3704	45.8	<b>3700</b>	<b>45.9</b>	3694	46.0	16	3742	45.4	<b>3707</b>	<b>45.8</b>	3706	45.8
465.tonto	16	886	178	<b>889</b>	<b>177</b>	890	177	16	836	188	<b>837</b>	<b>188</b>	837	188
470.lbm	16	5838	37.7	5822	37.8	<b>5836</b>	<b>37.7</b>	8	1561	70.4	1558	70.6	<b>1559</b>	<b>70.5</b>
481.wrf	16	2008	89.0	<b>2003</b>	<b>89.2</b>	1972	90.6	16	2008	89.0	<b>2003</b>	<b>89.2</b>	1972	90.6
482.sphinx3	16	<b>2210</b>	<b>141</b>	2214	141	2198	142	8	977	160	<b>984</b>	<b>158</b>	992	157

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
taskset was used to bind processes to cores except  
for 436.cactusADM peak  
For peak modules using 1/2 the number of available cores, copies  
were each assigned to a single L2 cache using mysubmit.pl script.  
See the flags description file for mysubmit.pl details.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to physical,0  
KMP\_STACKSIZE set to 64M



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7440, 2.40 GHz)

SPECfp\_rate2006 = 126

SPECfp\_rate\_base2006 = 118

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Bull SAS

Test date: Jan-2009  
Hardware Availability: Nov-2008  
Software Availability: Nov-2008

### Platform Notes

BIOS Settings:  
Adjacent Cache Line Prefetch = Disabled  
Hardware Prefetcher = Disabled  
High Bandwidth option = Enabled

### General Notes

The NEC Express5800/R140a-4(Intel Xeon E7440) and the Bull NovaScale R480 E1(Intel Xeon E7440, 2.40 GHz) models are electronically equivalent. The results have been measured on a Bull NovaScale R480 E1(Intel Xeon E7440, 2.40 GHz) model.

### Base Compiler Invocation

C benchmarks:  
icc  
  
C++ benchmarks:  
icpc  
  
Fortran benchmarks:  
ifort  
  
Benchmarks using both Fortran and C:  
icc ifort

### Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7440, 2.40 GHz)

SPECfp\_rate2006 = 126

SPECfp\_rate\_base2006 = 118

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Bull SAS

Test date: Jan-2009  
Hardware Availability: Nov-2008  
Software Availability: Nov-2008

## Base Optimization Flags

C benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

C++ benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

Fortran benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

Benchmarks using both Fortran and C:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc

482.sphinx3: /opt/intel/Compiler/11.0/042/bin/ia32/icc  
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib  
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include

C++ benchmarks (except as noted below):  
icpc

450.soplex: /opt/intel/Compiler/11.0/042/bin/ia32/icpc  
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib  
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include

Fortran benchmarks (except as noted below):  
ifort

437.leslie3d: /opt/intel/Compiler/11.0/042/bin/ia32/ifort  
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib  
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7440, 2.40 GHz)

SPECfp\_rate2006 = 126

SPECfp\_rate\_base2006 = 118

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Bull SAS

Test date: Jan-2009  
Hardware Availability: Nov-2008  
Software Availability: Nov-2008

## Peak Portability Flags (Continued)

```
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

### C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -fno-alias

470.lbm: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
-auto-ilp32

482.sphinx3: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2
```

### C++ benchmarks:

```
444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -fno-alias -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll4 -ansi-alias
```

### Fortran benchmarks:

```
410.bwaves: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -Ob0 -ansi-alias
-scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7440, 2.40 GHz)

SPECfp\_rate2006 = 126

SPECfp\_rate\_base2006 = 118

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Jan-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008

## Peak Optimization Flags (Continued)

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -opt-malloc-options=3 -opt-prefetch

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll2 -Ob0 -opt-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll2 -opt-prefetch -parallel  
-auto-ilp32

454.calculix: -xSSE4.1 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.01.html>

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.04.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.01.xml>

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.04.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 22:40:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 4 February 2009.