



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7430, 2.13 GHz)

SPECfp<sup>®</sup>\_rate2006 = 113

SPECfp\_rate\_base2006 = 107

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008



### Hardware

CPU Name: Intel Xeon E7430  
 CPU Characteristics: 1066 MHz system bus  
 CPU MHz: 2133  
 FPU: Integrated  
 CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip  
 CPU(s) orderable: 1,2,3,4 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 6 MB I+D on chip per chip, 3 MB shared / 2 cores

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP2, Kernel 2.6.16.60-0.21-smp  
 Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080730 Package ID: l\_cproc\_b\_11.0.042, l\_fproc\_b\_11.0.042  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7430, 2.13 GHz)

SPECfp\_rate2006 = 113

SPECfp\_rate\_base2006 = 107

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008

L3 Cache: 12 MB I+D on chip per chip  
Other Cache: None  
Memory: 32 GB (16 x 2GB DDR2-667 FBDIMM)  
Disk Subsystem: 1x146 GB SAS, 10000 RPM  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	3875	56.1	<b>3874</b>	<b>56.1</b>	3873	56.1	16	3874	56.1	3841	56.6	<b>3874</b>	<b>56.1</b>
416.gamess	16	<b>1234</b>	<b>254</b>	1234	254	1238	253	16	1214	258	1212	258	<b>1212</b>	<b>258</b>
433.milc	16	2304	63.7	2295	64.0	<b>2296</b>	<b>64.0</b>	16	2295	64.0	2291	64.1	<b>2292</b>	<b>64.1</b>
434.zeusmp	16	1371	106	1367	107	<b>1369</b>	<b>106</b>	16	<b>1364</b>	<b>107</b>	1372	106	1353	108
435.gromacs	16	557	205	<b>557</b>	<b>205</b>	558	205	16	553	207	553	207	<b>553</b>	<b>207</b>
436.cactusADM	16	1389	138	<b>1387</b>	<b>138</b>	1384	138	1	87.0	137	<b>87.2</b>	<b>137</b>	87.2	137
437.leslie3d	16	2902	51.8	<b>2883</b>	<b>52.2</b>	2878	52.3	16	<b>2823</b>	<b>53.3</b>	2821	53.3	2825	53.2
444.namd	16	<b>699</b>	<b>183</b>	699	184	700	183	16	713	180	710	181	<b>712</b>	<b>180</b>
447.dealII	16	1006	182	1014	181	<b>1008</b>	<b>182</b>	16	981	187	<b>981</b>	<b>187</b>	988	185
450.soplex	16	2279	58.5	<b>2280</b>	<b>58.5</b>	2281	58.5	16	2095	63.7	<b>2094</b>	<b>63.7</b>	2093	63.7
453.povray	16	306	278	308	276	<b>308</b>	<b>277</b>	16	257	332	256	333	<b>256</b>	<b>332</b>
454.calculix	16	616	214	<b>616</b>	<b>214</b>	613	215	16	609	217	<b>614</b>	<b>215</b>	621	212
459.GemsFDTD	16	3778	44.9	3758	45.2	<b>3762</b>	<b>45.1</b>	16	3804	44.6	<b>3776</b>	<b>45.0</b>	3770	45.0
465.tonto	16	1058	149	1057	149	<b>1058</b>	<b>149</b>	16	1006	157	1002	157	<b>1005</b>	<b>157</b>
470.lbm	16	6199	35.5	6187	35.5	<b>6189</b>	<b>35.5</b>	8	2125	51.7	<b>2117</b>	<b>51.9</b>	2116	51.9
481.wrf	16	<b>2065</b>	<b>86.6</b>	2087	85.6	2055	87.0	16	<b>2065</b>	<b>86.6</b>	2087	85.6	2055	87.0
482.sphinx3	16	<b>3124</b>	<b>99.8</b>	3113	100	3125	99.8	8	1347	116	<b>1341</b>	<b>116</b>	1303	120

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
taskset was used to bind processes to cores except for 436.cactusADM peak  
For peak modules using 1/2 the number of available cores, copies were each assigned to a single L2 cache using mysubmit.pl script.  
See the flags description file for mysubmit.pl details.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to physical,0  
KMP\_STACKSIZE set to 64M



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7430, 2.13 GHz)

SPECfp\_rate2006 = 113

SPECfp\_rate\_base2006 = 107

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** Bull SAS

**Test date:** Feb-2009  
**Hardware Availability:** Nov-2008  
**Software Availability:** Nov-2008

### Platform Notes

BIOS Settings:  
Adjacent Cache Line Prefetch = Disabled  
Hardware Prefetcher = Disabled  
High Bandwidth option = Enabled

### General Notes

The NEC Express5800/R140a-4(Intel Xeon E7430) and the Bull NovaScale R480 E1(Intel Xeon E7430, 2.13 GHz) models are electronically equivalent. The results have been measured on a Bull NovaScale R480 E1(Intel Xeon E7430, 2.13 GHz) model.

### Base Compiler Invocation

C benchmarks:  
icc  
  
C++ benchmarks:  
icpc  
  
Fortran benchmarks:  
ifort  
  
Benchmarks using both Fortran and C:  
icc ifort

### Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7430, 2.13 GHz)

SPECfp\_rate2006 = 113

SPECfp\_rate\_base2006 = 107

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Bull SAS

Test date: Feb-2009  
Hardware Availability: Nov-2008  
Software Availability: Nov-2008

## Base Optimization Flags

C benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

C++ benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

Fortran benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

Benchmarks using both Fortran and C:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc

482.sphinx3: /opt/intel/Compiler/11.0/042/bin/ia32/icc  
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib  
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include

C++ benchmarks (except as noted below):  
icpc

450.soplex: /opt/intel/Compiler/11.0/042/bin/ia32/icpc  
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib  
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include

Fortran benchmarks (except as noted below):  
ifort

437.leslie3d: /opt/intel/Compiler/11.0/042/bin/ia32/ifort  
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib  
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7430, 2.13 GHz)

SPECfp\_rate2006 = 113

SPECfp\_rate\_base2006 = 107

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Bull SAS

Test date: Feb-2009  
Hardware Availability: Nov-2008  
Software Availability: Nov-2008

## Peak Portability Flags (Continued)

```
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

### C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -fno-alias

470.lbm: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
-auto-ilp32

482.sphinx3: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2
```

### C++ benchmarks:

```
444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -fno-alias -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll4 -ansi-alias
```

### Fortran benchmarks:

```
410.bwaves: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -Ob0 -ansi-alias
-scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R480 E1  
(Intel Xeon E7430, 2.13 GHz)

SPECfp\_rate2006 = 113

SPECfp\_rate\_base2006 = 107

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2009

Hardware Availability: Nov-2008

Software Availability: Nov-2008

## Peak Optimization Flags (Continued)

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -opt-malloc-options=3 -opt-prefetch

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll2 -Ob0 -opt-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -unroll2 -opt-prefetch -parallel  
-auto-ilp32

454.calculix: -xSSE4.1 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090710.00.html>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090710.00.xml>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Tue Jul 22 23:31:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 31 March 2009.