



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp®2006 = 33.9

Fujitsu SPARC Enterprise M8000

SPECfp_base2006 = 28.2

CPU2006 license: 19


Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jul-2009

Hardware Availability: Nov-2009

Software Availability: Jun-2009



Hardware

CPU Name: SPARC64 VII
 CPU Characteristics:
 CPU MHz: 2880
 FPU: Integrated
 CPU(s) enabled: 64 cores, 16 chips, 4 cores/chip, 2 threads/core
 CPU(s) orderable: 1 to 4 CMUs; each CMU contains 2 or 4 CPU chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 6 MB I+D on chip per chip

Continued on next page

Software

Operating System: Solaris 10 5/09 with patches 119963-13, 120753-06, 118683-03
 Compiler: Sun Studio 12 Update 1
 Auto Parallel: Yes
 File System: ufs
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 33.9

Fujitsu SPARC Enterprise M8000

SPECfp_base2006 = 28.2

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jul-2009

Hardware Availability: Nov-2009

Software Availability: Jun-2009

L3 Cache: None
Other Cache: None
Memory: 384 GB (64 x 2 GB + 64 x 4 GB), 8-way interleaved
Disk Subsystem: 1 x Seagate Savvio 10K.2 (146 GB 10,000 RPM SAS)
Other Hardware: None

Other Software: Apache C++ Standard Library V4.2.1

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	34.0	400	<u>34.5</u>	<u>394</u>	34.8	391	<u>26.3</u>	<u>516</u>	26.2	518	26.3	516
416.gamess	1649	11.9	1649	11.9	<u>1649</u>	<u>11.9</u>	<u>1481</u>	<u>13.2</u>	1481	13.2	1480	13.2
433.milc	1059	8.67	<u>1056</u>	<u>8.70</u>	1055	8.70	700	13.1	699	13.1	<u>699</u>	<u>13.1</u>
434.zeusmp	253	35.9	<u>253</u>	<u>36.0</u>	253	36.0	<u>253</u>	<u>36.0</u>	253	36.0	253	35.9
435.gromacs	1350	5.29	1348	5.30	<u>1348</u>	<u>5.30</u>	534	13.4	534	13.4	<u>534</u>	<u>13.4</u>
436.cactusADM	48.5	246	<u>48.4</u>	<u>247</u>	47.5	252	<u>48.3</u>	<u>248</u>	49.4	242	47.8	250
437.leslie3d	131	71.9	129	72.9	<u>129</u>	<u>72.9</u>	131	71.9	129	72.9	<u>129</u>	<u>72.9</u>
444.namd	638	12.6	<u>638</u>	<u>12.6</u>	638	12.6	<u>627</u>	<u>12.8</u>	627	12.8	627	12.8
447.dealII	732	15.6	731	15.6	<u>732</u>	<u>15.6</u>	527	21.7	<u>526</u>	<u>21.7</u>	526	21.7
450.soplex	<u>932</u>	<u>8.95</u>	931	8.96	932	8.95	630	13.2	630	13.2	<u>630</u>	<u>13.2</u>
453.povray	411	12.9	411	13.0	<u>411</u>	<u>12.9</u>	337	15.8	<u>337</u>	<u>15.8</u>	337	15.8
454.calculix	594	13.9	<u>594</u>	<u>13.9</u>	594	13.9	<u>540</u>	<u>15.3</u>	540	15.3	540	15.3
459.GemsFDTD	140	75.8	<u>140</u>	<u>76.0</u>	140	76.0	<u>135</u>	<u>78.4</u>	136	77.7	135	78.8
465.tonto	838	11.7	840	11.7	<u>838</u>	<u>11.7</u>	<u>633</u>	<u>15.5</u>	633	15.5	633	15.5
470.lbm	<u>36.7</u>	<u>374</u>	36.7	374	36.6	375	36.1	380	35.3	390	<u>35.4</u>	<u>388</u>
481.wrf	728	15.3	<u>728</u>	<u>15.3</u>	728	15.3	<u>697</u>	<u>16.0</u>	697	16.0	698	16.0
482.sphinx3	1003	19.4	1009	19.3	<u>1004</u>	<u>19.4</u>	<u>990</u>	<u>19.7</u>	991	19.7	987	19.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

Sun Studio compiler patches are available at
http://developers.sun.com/sunstudio/downloads/patches/ss12u1_patches.jsp

The Apache C++ Standard Library V4.2.1 was installed from
<http://stdcxx.apache.org/download.html> using:
alias gmake=specmake
gmake BUILDTYPE=8d CONFIG=sunpro.config

Submit Notes

The config file option 'submit' was used. Processes were assigned to specific processors using 'pbind' commands. The list of processors to use was provided in the 'BIND' variable, to generate the pbind commands.
(For details, please see the config file.)



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 33.9

Fujitsu SPARC Enterprise M8000

SPECfp_base2006 = 28.2

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jul-2009

Hardware Availability: Nov-2009

Software Availability: Jun-2009

Operating System Notes

Shell Environments:

ulimit -s 131072 was used to limit the space consumed by the stack.(making more space available for the heap)

The maximum number of threads a program can create was set with:
OMP_NUM_THREADS=64

Program threads were bound to processors with:

```
SUNW_MP_PROCBIND=" 1  2  4  6  8 10 12 14 16 18 20 22 24 26 28 30 32 34
                  36 38 40 42 44 46 48 50 52 54 56 58 60 62 64 66 68 70
                  72 74 76 78 80 82 84 86 88 90 92 94 96 98 100 102 104
                  106 108 110 112 114 116 118 120 122 124 126"
```

Behavior of parallel threads was set with:

SUNW_MP_THR_IDLE=SPIN

SPIN specifies that an idle thread should spin while waiting at barrier or waiting for new parallel regions to work on.

System Tunables:

(/etc/system parameters)

tune_t_fsflushr=10

Controls how many seconds elapse between runs of the page flush daemon, fsflush.

autoup=300

Causes pages older than the listed number of seconds to be written by fsflush.

bufhwm=3000

Memory byte limit for caching I/O buffers.

segmap_percent=3

Set maximum percent memory for file system cache.

lpg_alloc_prefer=1

Set lgroup page allocation to strongly prefer local pages.

Other System Settings:

The webconsole service was turned off using svcadm disable webconsole.

Platform Notes

Memory is 8-way interleaved by filling each CMU's slots with the same capacity DIMMs.

This result is measured on a Fujitsu SPARC Enterprise M8000 Server. Note that the Fujitsu SPARC Enterprise M8000 and Sun SPARC Enterprise M8000 are electrically equivalent.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 33.9

Fujitsu SPARC Enterprise M8000

SPECfp_base2006 = 28.2

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Jul-2009
Hardware Availability: Nov-2009
Software Availability: Jun-2009

General Notes

447.dealIII (peak): "apache_stdctx_4_2_1" src.alt was used.

Base Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Fortran benchmarks:
f90

Benchmarks using both Fortran and C:
cc f90

Base Optimization Flags

C benchmarks:
-fast -fma=fused -xpagesize=4M -xipo=2 -xprefetch=latx:2 -xautopar
-xreduction -xprefetch_level=3
-xprefetch_auto_type=indirect_array_access

C++ benchmarks:
-fast -fma=fused -xpagesize=4M -xipo=2 -xprefetch=latx:2 -xautopar
-xreduction -xprefetch_level=2 -xalias_level=compatible
-library=stlport4

Fortran benchmarks:
-fast -fma=fused -xpagesize=4M -xipo=2 -xprefetch=latx:2 -xautopar
-xreduction -xprefetch_level=2

Benchmarks using both Fortran and C:
-fast(cc) -fast(f90) -fma=fused -xpagesize=4M -xipo=2
-xprefetch=latx:2 -xautopar -xreduction -xprefetch_level=3
-xprefetch_auto_type=indirect_array_access -xprefetch_level=2

Base Other Flags

C benchmarks:
-xjobs=16 -V -#

C++ benchmarks:
-xjobs=16 -verbose=diags,version

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 33.9

Fujitsu SPARC Enterprise M8000

SPECfp_base2006 = 28.2

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Jul-2009
Hardware Availability: Nov-2009
Software Availability: Jun-2009

Base Other Flags (Continued)

Fortran benchmarks:
-xjobs=16 -V -v

Benchmarks using both Fortran and C:
-xjobs=16 -V -# -v

Peak Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Fortran benchmarks:
f90

Benchmarks using both Fortran and C:
cc f90

Peak Optimization Flags

C benchmarks:

```
433.milc: -fast -fma=fused -xpagesize=4M -xipo=2 -xprefetch_level=2
          -fsimple=1 -xprefetch_auto_type=indirect_array_access
          -W2,-Ainline:rs=400 -xalias_level=std -xprefetch=latx:2.0
```

```
470.lbm: -xprofile=collect:./feedback(pass 1)
          -xprofile=use:./feedback(pass 2) -fast -fma=fused
          -xpagesize=4M -xipo=2 -xprefetch=latx:2 -xalias_level=std
          -xprefetch_level=3 -xprefetch_auto_type=indirect_array_access
          -xarch=v8plusb -xprefetch_level=2 -xautopar -xreduction
```

```
482.sphinx3: -xprofile=collect:./feedback(pass 1)
              -xprofile=use:./feedback(pass 2) -fast -xipo=2 -fma=fused
              -xalias_level=std -xautopar -xreduction
```

C++ benchmarks:

```
444.namd: -fast -fma=fused -xpagesize=4M -xalias_level=any
          -library=stlport4
```

```
447.dealII: -xprofile=collect:./feedback(pass 1)
             -xprofile=use:./feedback(pass 2) -fast -fma=fused
             -xpagesize=4M -xipo=2 -xprefetch_level=2 -xrestrict
             -xalias_level=compatible -library=no%Cstd
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 33.9

Fujitsu SPARC Enterprise M8000

SPECfp_base2006 = 28.2

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jul-2009

Hardware Availability: Nov-2009

Software Availability: Jun-2009

Peak Optimization Flags (Continued)

447.dealIII (continued):

```
-I/export/cpu2006/stdcxx-4.2.1/include
-I/export/cpu2006/stdcxx-4.2.1/build/include
-L/export/cpu2006/stdcxx-4.2.1/build/lib
-R/export/cpu2006/stdcxx-4.2.1/build/lib -lstd8d
```

```
450.soplex: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xipo=2 -xdepend -xprefetch_level=2
-xprefetch_auto_type=indirect_array_access
-Qoption cg -Qlp-ol=1 -Qoption cg -Qlp-it=3
-Qoption cg -Qlp-imb=1 -Qoption iropt -Apf:pdl=3
-xalias_level=simple -xrestrict -library=stlport4
```

```
453.povray: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xipo=2 -xrestrict -xalias_level=compatible
-library=stlport4
```

Fortran benchmarks:

```
410.bwaves: -fast -fma=fused -xpagesize=512K -xipo=2 -xprefetch=latx:2
-xprefetch_level=2 -xautopar -xreduction
```

```
416.gamess: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xipo=2 -xprefetch_level=3
```

```
434.zeusmp: -fast -fma=fused -xpagesize=4M -xipo=2 -xprefetch=latx:2
-xautopar -xreduction
```

```
437.leslie3d: basepeak = yes
```

```
459.GemsFDTD: -fast -fma=fused -xpagesize=4M -xipo=2 -xprefetch=latx:2
-fsimple=1 -xprefetch_level=2 -xautopar -xreduction
```

```
465.tonto: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xipo=2 -xprefetch=no -xarch=generic -lfast
```

Benchmarks using both Fortran and C:

```
435.gromacs: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
-fma=fused -xipo=2 -xalias_level=std
```

```
436.cactusADM: -fast(cc) -fast(f90) -fma=fused -xpagesize=4M -xipo=2
-xprefetch=latx:2 -xalias_level=std -xprefetch_level=3
-xprefetch_auto_type=indirect_array_access -xautopar
-xreduction
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 33.9

Fujitsu SPARC Enterprise M8000

SPECfp_base2006 = 28.2

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jul-2009

Hardware Availability: Nov-2009

Software Availability: Jun-2009

Peak Optimization Flags (Continued)

454.calculix: -fast(cc) -fast(f90) -fma=fused -xpagesize=4M -xipo=2
-xprefetch_level=3 -xprefetch=latx:3.0 -xalias_level=std

481.wrf: -fast(cc) -fast(f90) -fma=fused -xpagesize=4M -xipo=2
-xprefetch_level=3 -xunroll=8

Peak Other Flags

C benchmarks:
-xjobs=16 -V -#

C++ benchmarks:
-xjobs=16 -verbose=diags,version

Fortran benchmarks:
-xjobs=16 -V -v

Benchmarks using both Fortran and C:
-xjobs=16 -V -# -v

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-12u1-and-gccfss4.2.r4.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-12u1-and-gccfss4.2.r4.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 04:15:22 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 28 October 2009.