



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp®_rate2006 = 60.6

Servidor Itautec MX223+ (Intel Xeon E5504)

SPECfp_rate_base2006 = 58.8

CPU2006 license: 9001


Test date: Oct-2009

Test sponsor: Itautec

Hardware Availability: Sep-2009

Tested by: Itautec

Software Availability: Feb-2009



SPECfp_rate_base2006 = 58.8

SPECfp_rate2006 = 60.6

Hardware

CPU Name: Intel Xeon E5504
CPU Characteristics:
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
CPU(s) orderable: 1, 2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64)
SP2 with patch Linux kernel 20090119,
Kernel 2.6.16.60-0.34-smp
Compiler: Intel C++ and Fortran Compiler 11.0 for Linux
Build 20090131 Package ID: l_cproc_p_11.0.081
l_cprof_p_11.0.081
Auto Parallel: No
File System: ReiserFS
System State: Run level 3 (multi-user)

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp_rate2006 = 60.6

Servidor Itautec MX223+ (Intel Xeon E5504)

SPECfp_rate_base2006 = 58.8

CPU2006 license: 9001

Test date: Oct-2009

Test sponsor: Itautec

Hardware Availability: Sep-2009

Tested by: Itautec

Software Availability: Feb-2009

L3 Cache: 4 MB I+D on chip per chip
 Other Cache: None
 Memory: 9 GB (9 x 1GB DDR3-1066, CL 7, ECC, running at 800 MHz)
 Disk Subsystem: 1 x 160 GB SATA-2, 7200RPM
 Other Hardware: None

Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other Software: Binutils 2.18.50.0.7.20080502

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	796	68.3	799	68.1	799	68.0	4	797	68.2	797	68.2	797	68.2
416.gamess	4	1217	64.3	1216	64.4	1217	64.4	4	1217	64.4	1216	64.4	1215	64.5
433.milc	4	507	72.5	508	72.3	508	72.3	4	506	72.5	507	72.4	507	72.4
434.zeusmp	4	574	63.5	571	63.8	572	63.6	4	574	63.5	571	63.8	572	63.6
435.gromacs	4	511	55.9	512	55.8	512	55.8	4	506	56.5	506	56.5	506	56.4
436.cactusADM	4	697	68.6	699	68.4	698	68.5	4	681	70.2	678	70.5	680	70.3
437.leslie3d	4	889	42.3	911	41.3	906	41.5	4	889	42.3	911	41.3	906	41.5
444.namd	4	687	46.7	687	46.7	687	46.7	4	682	47.1	684	46.9	682	47.0
447.dealII	4	570	80.3	583	78.5	568	80.6	4	563	81.3	557	82.1	562	81.4
450.soplex	4	725	46.0	753	44.3	752	44.4	4	685	48.7	711	46.9	710	47.0
453.povray	4	291	73.2	290	73.4	291	73.2	4	234	90.9	234	90.8	235	90.4
454.calculix	4	465	71.0	465	71.0	465	71.0	4	465	71.0	465	71.0	465	71.0
459.GemsFDTD	4	1051	40.4	1044	40.7	1044	40.6	4	1012	41.9	1007	42.1	1009	42.1
465.tonto	4	676	58.2	675	58.3	674	58.4	4	648	60.8	640	61.5	641	61.4
470.lbm	4	1272	43.2	1278	43.0	1278	43.0	4	1233	44.6	1236	44.5	1237	44.4
481.wrf	4	590	75.7	587	76.1	590	75.8	4	590	75.7	587	76.1	590	75.8
482.sphinx3	4	1375	56.7	1368	57.0	1364	57.2	4	1331	58.6	1322	59.0	1314	59.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
 numactl was used to bind copies to the cores

General Notes

This result was measured on the Servidor Itautec MX223+.
 The Servidor Itautec MX223+ and the Servidor Itautec MX203+ are electronically equivalent.
 'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaute

Servidor Itaute MX223+ (Intel Xeon E5504)

SPECfp_rate2006 = 60.6

CPU2006 license: 9001

Test date: Oct-2009

Test sponsor: Itaute

Hardware Availability: Sep-2009

Tested by: Itaute

Software Availability: Feb-2009

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static

Fortran benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:
-xSSE4.2 -ipo -O3 -no-prec-div -static



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaute

SPECfp_rate2006 = 60.6

Servidor Itaute MX223+ (Intel Xeon E5504)

SPECfp_rate_base2006 = 58.8

CPU2006 license: 9001

Test date: Oct-2009

Test sponsor: Itaute

Hardware Availability: Sep-2009

Tested by: Itaute

Software Availability: Feb-2009

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc

450.soplex: icpc -m32

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-fno-alias

470.lbm: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
-auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX223+ (Intel Xeon E5504)

SPECfp_rate2006 = 60.6

SPECfp_rate_base2006 = 58.8

CPU2006 license: 9001

Test sponsor: Itautec

Tested by: Itautec

Test date: Oct-2009

Hardware Availability: Sep-2009

Software Availability: Feb-2009

Peak Optimization Flags (Continued)

482.sphinx3: -xsse4.2 -ipo -O3 -no-prec-div -static -unroll12

C++ benchmarks:

444.namd: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
 -fno-alias -auto-ilp32

447.dealII: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
 -unroll12 -ansi-alias -scalar-rep-

450.soplex: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
 -opt-malloc-options=3

453.povray: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
 -unroll14 -ansi-alias

Fortran benchmarks:

410.bwaves: -xsse4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
 -unroll12 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
 -unroll12 -Ob0 -opt-prefetch

465.tonto: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
 -unroll14 -auto

Benchmarks using both Fortran and C:

435.gromacs: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
 -opt-prefetch -auto-ilp32

436.cactusADM: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
 -unroll12 -opt-prefetch -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX223+ (Intel Xeon E5504)

SPECfp_rate2006 = 60.6

CPU2006 license: 9001

Test date: Oct-2009

Test sponsor: Itautec

Hardware Availability: Sep-2009

Tested by: Itautec

Software Availability: Feb-2009

Peak Optimization Flags (Continued)

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Itautec-Intel-ic11.0-fp-linux64-revI.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Itautec-Intel-ic11.0-fp-linux64-revI.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 04:54:57 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 10 November 2009.