



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp®2006 = 37.8

NovaScale T820 F2 (Intel Xeon X3470, 2.93 GHz)

SPECfp\_base2006 = 36.5

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Dell Inc.

Test date: Nov-2009

Hardware Availability: Dec-2009

Software Availability: Jul-2009



### Hardware

CPU Name: Intel Xeon X3470  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.60 GHz  
 CPU MHz: 2933  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server release 5.3, Kernel 2.6.18-128.el5  
 Compiler: Intel Fortran Compiler and Intel C++ Compiler Professional Edition 11.1 For Linux Build 20090511 Package ID: l\_cproc\_p\_11.1.040, l\_cprof\_p\_11.1.040  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp2006 = **37.8**

NovaScale T820 F2 (Intel Xeon X3470, 2.93 GHz)

SPECfp\_base2006 = **36.5**

CPU2006 license: 20

Test date: Nov-2009

Test sponsor: Bull SAS

Hardware Availability: Dec-2009

Tested by: Dell Inc.

Software Availability: Jul-2009

L3 Cache: 8 MB I+D on chip per chip  
Other Cache: None  
Memory: 8 GB (4 x 2 GB DDR3-1333 DR RDIMM)  
Disk Subsystem: 1 x 160 GB 7200 RPM SATA  
Other Hardware: None

Base Pointers: 64-bit  
Peak Pointers: 64-bit  
Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	176	77.1	177	76.8	<u>177</u>	<u>76.9</u>	176	77.1	177	76.6	<u>177</u>	<u>76.7</u>
416.gamess	790	24.8	791	24.7	<u>791</u>	<u>24.8</u>	<u>763</u>	<u>25.7</u>	763	25.7	762	25.7
433.milc	202	45.4	201	45.6	<u>202</u>	<u>45.5</u>	212	43.4	211	43.5	<u>211</u>	<u>43.5</u>
434.zeusmp	248	36.6	248	36.7	<u>248</u>	<u>36.7</u>	248	36.7	248	36.6	<u>248</u>	<u>36.7</u>
435.gromacs	320	22.3	305	23.4	<u>320</u>	<u>22.3</u>	315	22.6	314	22.7	<u>315</u>	<u>22.7</u>
436.cactusADM	114	105	114	104	<u>114</u>	<u>105</u>	<u>106</u>	<u>113</u>	106	113	105	114
437.leslie3d	<u>297</u>	<u>31.6</u>	297	31.7	298	31.6	<u>297</u>	<u>31.6</u>	297	31.7	298	31.6
444.namd	395	20.3	395	20.3	<u>395</u>	<u>20.3</u>	395	20.3	395	20.3	<u>395</u>	<u>20.3</u>
447.dealII	310	37.0	<u>310</u>	<u>37.0</u>	310	37.0	303	37.8	304	37.6	<u>303</u>	<u>37.8</u>
450.soplex	<u>306</u>	<u>27.3</u>	306	27.3	321	26.0	<u>306</u>	<u>27.3</u>	306	27.3	321	26.0
453.povray	<u>183</u>	<u>29.0</u>	183	29.1	183	29.0	<u>145</u>	<u>36.6</u>	145	36.7	146	36.5
454.calculix	<u>284</u>	<u>29.0</u>	284	29.1	285	29.0	281	29.4	<u>281</u>	<u>29.4</u>	282	29.2
459.GemsFDTD	275	38.5	275	38.6	<u>275</u>	<u>38.6</u>	264	40.2	265	40.1	<u>264</u>	<u>40.1</u>
465.tonto	404	24.4	404	24.3	<u>404</u>	<u>24.3</u>	330	29.8	<u>330</u>	<u>29.8</u>	334	29.5
470.lbm	251	54.8	267	51.5	<u>255</u>	<u>53.9</u>	251	54.8	267	51.5	<u>255</u>	<u>53.9</u>
481.wrf	273	41.0	272	41.1	<u>272</u>	<u>41.1</u>	<u>272</u>	<u>41.1</u>	272	41.1	271	41.1
482.sphinx3	467	41.7	444	43.9	<u>448</u>	<u>43.5</u>	467	41.7	444	43.9	<u>448</u>	<u>43.5</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

BIOS Settings:

Power Management = Maximum Performance (Default = Active Power Controller)



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp2006 = 37.8

NovaScale T820 F2 (Intel Xeon X3470, 2.93 GHz)

SPECfp\_base2006 = 36.5

CPU2006 license: 20

Test date: Nov-2009

Test sponsor: Bull SAS

Hardware Availability: Dec-2009

Tested by: Dell Inc.

Software Availability: Jul-2009

## General Notes

OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to granularity=fine,scatter  
KMP\_STACKSIZE set to 200M  
The Dell PowerEdge T310 (Intel Xeon X3470 2.93 GHz) and the Bull NovaScale T820 F2 (Intel Xeon X3470 2.93 GHz) models are electronically equivalent. The results have been measured on a Dell PowerEdge T310 (Intel Xeon X3470 2.93 GHz) model.

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 37.8**

NovaScale T820 F2 (Intel Xeon X3470, 2.93 GHz)

**SPECfp\_base2006 = 36.5**

**CPU2006 license:** 20

**Test date:** Nov-2009

**Test sponsor:** Bull SAS

**Hardware Availability:** Dec-2009

**Tested by:** Dell Inc.

**Software Availability:** Jul-2009

## Base Optimization Flags (Continued)

C++ benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch`

Fortran benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel`

Benchmarks using both Fortran and C:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel`

## Peak Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

`433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias`

`470.lbm: basepeak = yes`

`482.sphinx3: basepeak = yes`

C++ benchmarks:

`444.namd: basepeak = yes`

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 37.8**

NovaScale T820 F2 (Intel Xeon X3470, 2.93 GHz)

**SPECfp\_base2006 = 36.5**

**CPU2006 license:** 20

**Test date:** Nov-2009

**Test sponsor:** Bull SAS

**Hardware Availability:** Dec-2009

**Tested by:** Dell Inc.

**Software Availability:** Jul-2009

## Peak Optimization Flags (Continued)

447.dealIII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias -scalar-rep- -opt-prefetch

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
-parallel

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: Same as 410.bwaves

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -opt-prefetch -parallel

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32

436.cactusADM: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -opt-prefetch -parallel -auto-ilp32

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
-parallel -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-fp-linux64-revA.html>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 37.8**

NovaScale T820 F2 (Intel Xeon X3470, 2.93 GHz)

**SPECfp\_base2006 = 36.5**

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** Dell Inc.

**Test date:** Nov-2009  
**Hardware Availability:** Dec-2009  
**Software Availability:** Jul-2009

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-fp-linux64-revA.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 03:43:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 22 December 2009.