



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Motherboard X8SIE-F (Intel Xeon X3430, 2.40 GHz)

**SPECfp®2006 = 31.4**

**SPECfp\_base2006 = 28.0**

CPU2006 license: 001176


Test sponsor: Supermicro

Tested by: Supermicro

Test date: Feb-2010

Hardware Availability: Sep-2009

Software Availability: Oct-2009



Hardware	
CPU Name:	Intel Xeon X3430
CPU Characteristics:	Intel Turbo Boost Technology up to 2.80 GHz
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core

Software	
Operating System:	SUSE Linux Enterprise Server 11 (x86_64)
Compiler:	Kernel 2.6.27.19-5-default
Auto Parallel:	Intel C++ and Fortran Professional Compiler for IA32 and Intel 64, Version 11.1
File System:	Build 20091012 Package ID: l_cproc_p_11.1.059, l_cprof_p_11.1.059
System State:	Yes
	ReiserFS
	Run level 3 (multi-user)

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

**SPECfp2006 = 31.4**

Motherboard X8SIE-F (Intel Xeon X3430, 2.40 GHz)

**SPECfp\_base2006 = 28.0**

**CPU2006 license:** 001176

**Test date:** Feb-2010

**Test sponsor:** Supermicro

**Hardware Availability:** Sep-2009

**Tested by:** Supermicro

**Software Availability:** Oct-2009

L3 Cache: 8 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 16 GB (4 x 4 GB DDR3-1333 RDIMM, ECC, CL9)  
 Disk Subsystem: 1 x 160 GB SATA II, 7200 RPM  
 Other Hardware: None

Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	244	55.7	<b>243</b>	<b>55.9</b>	241	56.4	<b>243</b>	<b>56.0</b>	240	56.6	<b>240</b>	<b>56.6</b>
416.gamess	893	21.9	<b>897</b>	<b>21.8</b>	897	21.8	<b>895</b>	<b>21.9</b>	918	21.3	895	21.9
433.milc	216	42.4	<b>216</b>	<b>42.6</b>	216	42.6	<b>210</b>	<b>43.8</b>	<b>212</b>	<b>43.4</b>	213	43.2
434.zeusmp	374	24.3	373	24.4	<b>374</b>	<b>24.4</b>	374	24.3	373	24.4	<b>374</b>	<b>24.4</b>
435.gromacs	378	18.9	377	18.9	<b>378</b>	<b>18.9</b>	369	19.3	<b>369</b>	<b>19.3</b>	383	18.6
436.cactusADM	477	25.0	481	24.8	<b>481</b>	<b>24.9</b>	225	53.2	<b>225</b>	<b>53.0</b>	225	53.0
437.leslie3d	347	27.1	338	27.8	<b>342</b>	<b>27.5</b>	347	27.1	338	27.8	<b>342</b>	<b>27.5</b>
444.namd	<b>501</b>	<b>16.0</b>	501	16.0	492	16.3	<b>495</b>	<b>16.2</b>	495	16.2	495	16.2
447.dealII	<b>369</b>	<b>31.0</b>	373	30.6	367	31.2	<b>350</b>	<b>32.7</b>	346	33.1	350	32.7
450.soplex	341	24.4	<b>341</b>	<b>24.5</b>	340	24.6	<b>336</b>	<b>24.8</b>	339	24.6	<b>337</b>	<b>24.7</b>
453.povray	249	21.3	<b>227</b>	<b>23.5</b>	226	23.5	<b>177</b>	<b>30.1</b>	170	31.3	<b>171</b>	<b>31.2</b>
454.calculix	326	25.3	<b>325</b>	<b>25.4</b>	324	25.4	<b>332</b>	<b>24.8</b>	<b>326</b>	<b>25.3</b>	326	25.3
459.GemsFDTD	<b>349</b>	<b>30.4</b>	349	30.4	355	29.9	<b>280</b>	<b>37.9</b>	280	37.9	281	37.7
465.tonto	444	22.2	<b>449</b>	<b>21.9</b>	449	21.9	364	27.0	364	27.0	<b>364</b>	<b>27.0</b>
470.lbm	<b>307</b>	<b>44.8</b>	303	45.3	312	44.0	<b>270</b>	<b>50.8</b>	271	50.8	<b>271</b>	<b>50.8</b>
481.wrf	312	35.8	326	34.3	<b>313</b>	<b>35.7</b>	272	41.1	275	40.6	<b>275</b>	<b>40.6</b>
482.sphinx3	605	32.2	<b>605</b>	<b>32.2</b>	602	32.4	<b>554</b>	<b>35.2</b>	560	34.8	<b>557</b>	<b>35.0</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Platform Notes

Fan speed set to Full Speed in BIOS Setup.  
 As tested, the system used a Supermicro  
 PWS-665-PQ power supply, SNK-P0046P heatsink,  
 and FAN-0077L cooling fan.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Motherboard X8SIE-F (Intel Xeon X3430, 2.40 GHz)

**SPECfp2006 = 31.4**

CPU2006 license: 001176

Test date: Feb-2010

Test sponsor: Supermicro

Hardware Availability: Sep-2009

Tested by: Supermicro

Software Availability: Oct-2009

## General Notes

OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to granularity=fine,scatter  
KMP\_STACKSIZE set to 200M

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Supermicro**

Motherboard X8SIE-F (Intel Xeon X3430, 2.40 GHz)

**SPECfp2006 = 31.4**

**SPECfp\_base2006 = 28.0**

**CPU2006 license:** 001176

**Test sponsor:** Supermicro

**Tested by:** Supermicro

**Test date:** Feb-2010

**Hardware Availability:** Sep-2009

**Software Availability:** Oct-2009

## Base Optimization Flags (Continued)

Fortran benchmarks:

```
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
```

Benchmarks using both Fortran and C:

```
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
```

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
icc -m64
```

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

```
icpc -m64
```

450.soplex: icpc -m32

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
    433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
    447.dealII: -DSPEC_CPU_LP64
    453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
    465.tonto: -DSPEC_CPU_LP64
    470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

Motherboard X8SIE-F (Intel Xeon X3430, 2.40 GHz)

**SPECfp2006 = 31.4**

CPU2006 license: 001176

Test date: Feb-2010

Test sponsor: Supermicro

Hardware Availability: Sep-2009

Tested by: Supermicro

Software Availability: Oct-2009

## Peak Optimization Flags

C benchmarks:

```
433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
           -ansi-alias
```

```
470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
           -ansi-alias -parallel -auto-ilp32
```

```
482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2
```

C++ benchmarks:

```
444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
           -fno-alias -auto-ilp32
```

```
447.dealII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
           -unroll2 -ansi-alias -scalar-rep -auto-ilp32
```

```
450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
           -opt-malloc-options=3
```

```
453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
           -unroll4 -ansi-alias
```

Fortran benchmarks:

```
410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
```

```
416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
           -unroll2 -Ob0 -ansi-alias -scalar-rep-
```

```
434.zeusmp: basepeak = yes
```

```
437.leslie3d: basepeak = yes
```

```
459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
               -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
               -unroll2 -Ob0 -opt-prefetch -parallel
```

```
465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
           -inline-calloc -opt-malloc-options=3 -auto -unroll4
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Motherboard X8SIE-F (Intel Xeon X3430, 2.40 GHz)

**SPECfp2006 = 31.4**

**CPU2006 license:** 001176

**Test date:** Feb-2010

**Test sponsor:** Supermicro

**Hardware Availability:** Sep-2009

**Tested by:** Supermicro

**Software Availability:** Oct-2009

## Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

```
435.gromacs: -xSSE4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
               -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
               -opt-prefetch -auto-ilp32
```

```
436.cactusADM: -xSSE4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
                 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
                 -unroll12 -opt-prefetch -parallel -auto-ilp32
```

```
454.calculix: -xSSE4 .2 -ipo -O3 -no-prec-div -static -auto-ilp32
```

```
481.wrf: Same as 454.calculix
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-fp-linux64-revE.20100202.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-fp-linux64-revE.20100202.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 07:26:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 27 April 2010.