



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp®2006 = 44.5

NovaScale R460 F2 (Intel Xeon X5660, 2.80 GHz)

SPECfp\_base2006 = 41.4

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Dell Inc.

Test date: May-2010

Hardware Availability: Mar-2010

Software Availability: Dec-2009



### Hardware

CPU Name: Intel Xeon X5660  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.20 GHz  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64), Kernel 2.6.27.19-5-smp  
 Compiler: Intel C++ and Fortran Professional Compiler for IA32 and Intel 64, Version 11.1 Build 20091130 Package ID: l\_cproc\_p\_11.1.064, l\_cprof\_p\_11.1.064  
 Auto Parallel: Yes  
 File System: ext3  
 System State: Run level 3 (multi-user)

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp2006 = 44.5

NovaScale R460 F2 (Intel Xeon X5660, 2.80 GHz)

SPECfp\_base2006 = 41.4

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Dell Inc.

Test date: May-2010

Hardware Availability: Mar-2010

Software Availability: Dec-2009

L3 Cache: 12 MB I+D on chip per chip  
Other Cache: None  
Memory: 48 GB (12 x 4 GB DDR3-1333 DR RDIMM, CL9, ECC)  
Disk Subsystem: 1 x 146 GB 15000 RPM SAS  
Other Hardware: None

Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	75.9	179	76.7	177	<b><u>76.3</u></b>	<b><u>178</u></b>	75.3	181	76.3	178	<b><u>75.9</u></b>	<b><u>179</u></b>
416.gamess	858	22.8	854	22.9	<b><u>857</u></b>	<b><u>22.9</u></b>	763	25.6	<b><u>764</u></b>	<b><u>25.6</u></b>	764	25.6
433.milc	<b><u>189</u></b>	<b><u>48.6</u></b>	188	48.9	189	48.6	187	49.1	187	49.2	<b><u>187</u></b>	<b><u>49.1</u></b>
434.zeusmp	251	36.2	<b><u>251</u></b>	<b><u>36.3</u></b>	251	36.3	251	36.2	<b><u>251</u></b>	<b><u>36.3</u></b>	251	36.3
435.gromacs	319	22.4	320	22.3	<b><u>320</u></b>	<b><u>22.3</u></b>	314	22.7	316	22.6	<b><u>316</u></b>	<b><u>22.6</u></b>
436.cactusADM	48.6	246	<b><u>48.4</u></b>	<b><u>247</u></b>	48.0	249	47.4	252	46.6	257	<b><u>47.4</u></b>	<b><u>252</u></b>
437.leslie3d	264	35.6	266	35.3	<b><u>265</u></b>	<b><u>35.5</u></b>	264	35.6	266	35.3	<b><u>265</u></b>	<b><u>35.5</u></b>
444.namd	425	18.9	425	18.9	<b><u>425</u></b>	<b><u>18.9</u></b>	425	18.9	425	18.9	<b><u>425</u></b>	<b><u>18.9</u></b>
447.dealII	311	36.8	<b><u>311</u></b>	<b><u>36.8</u></b>	311	36.8	305	37.5	304	37.6	<b><u>305</u></b>	<b><u>37.5</u></b>
450.soplex	266	31.3	266	31.3	<b><u>266</u></b>	<b><u>31.3</u></b>	<b><u>265</u></b>	<b><u>31.5</u></b>	265	31.5	263	31.7
453.povray	<b><u>186</u></b>	<b><u>28.6</u></b>	187	28.4	185	28.7	<b><u>146</u></b>	<b><u>36.5</u></b>	145	36.7	146	36.4
454.calculix	298	27.7	296	27.8	<b><u>297</u></b>	<b><u>27.7</u></b>	286	28.8	285	29.0	<b><u>286</u></b>	<b><u>28.8</u></b>
459.GemsFDTD	226	47.0	225	47.1	<b><u>226</u></b>	<b><u>47.0</u></b>	155	68.6	<b><u>155</u></b>	<b><u>68.6</u></b>	154	68.8
465.tonto	410	24.0	<b><u>411</u></b>	<b><u>24.0</u></b>	412	23.9	310	31.7	<b><u>310</u></b>	<b><u>31.8</u></b>	310	31.8
470.lbm	<b><u>225</u></b>	<b><u>61.2</u></b>	225	61.2	225	61.1	221	62.1	<b><u>222</u></b>	<b><u>62.0</u></b>	222	62.0
481.wrf	267	41.8	<b><u>266</u></b>	<b><u>41.9</u></b>	266	42.0	<b><u>239</u></b>	<b><u>46.8</u></b>	239	46.8	238	46.9
482.sphinx3	<b><u>450</u></b>	<b><u>43.3</u></b>	451	43.2	449	43.4	<b><u>450</u></b>	<b><u>43.3</u></b>	451	43.2	449	43.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

BIOS Settings:

Power Management = Maximum Performance (Default = Active Power Controller)

Data Reuse = Disabled (Default = Enabled)

## General Notes

OMP\_NUM\_THREADS set to number of cores

KMP\_AFFINITY set to granularity=fine,scatter

KMP\_STACKSIZE set to 200M

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 2



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp2006 = 44.5

NovaScale R460 F2 (Intel Xeon X5660, 2.80 GHz)

SPECfp\_base2006 = 41.4

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Dell Inc.

Test date: May-2010  
Hardware Availability: Mar-2010  
Software Availability: Dec-2009

### General Notes (Continued)

Binaries were compiled on SLES 10 with Binutils 2.18.50.0.7.20080502  
The Dell PowerEdge R710 and  
the Bull NovaScale R460 F2 models are electronically equivalent.  
The results have been measured on a Dell PowerEdge R710 model.

### Base Compiler Invocation

C benchmarks:  
icc -m64

C++ benchmarks:  
icpc -m64

Fortran benchmarks:  
ifort -m64

Benchmarks using both Fortran and C:  
icc -m64 ifort -m64

### Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

### Base Optimization Flags

C benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

C++ benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 44.5**

NovaScale R460 F2 (Intel Xeon X5660, 2.80 GHz)

**SPECfp\_base2006 = 41.4**

**CPU2006 license:** 20

**Test date:** May-2010

**Test sponsor:** Bull SAS

**Hardware Availability:** Mar-2010

**Tested by:** Dell Inc.

**Software Availability:** Dec-2009

## Base Optimization Flags (Continued)

Fortran benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch`

Benchmarks using both Fortran and C:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch`

## Peak Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-ansi-alias`

470.lbm: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-parallel -ansi-alias -auto-ilp32`

482.sphinx3: `basepeak = yes`

C++ benchmarks:

444.namd: `basepeak = yes`

447.dealIII: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias -scalar-rep- -auto-ilp32`

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 44.5**

NovaScale R460 F2 (Intel Xeon X5660, 2.80 GHz)

**SPECfp\_base2006 = 41.4**

**CPU2006 license:** 20

**Test date:** May-2010

**Test sponsor:** Bull SAS

**Hardware Availability:** Mar-2010

**Tested by:** Dell Inc.

**Software Availability:** Dec-2009

## Peak Optimization Flags (Continued)

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3 -auto-ilp32

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
-parallel

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -opt-prefetch -parallel

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-inline-calloc -opt-malloc-options=3 -auto -unroll4

### Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32

436.cactusADM: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -opt-prefetch -parallel -auto-ilp32

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: Same as 454.calculix

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100330.html>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp2006 = 44.5

NovaScale R460 F2 (Intel Xeon X5660, 2.80 GHz)

SPECfp\_base2006 = 41.4

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Dell Inc.

**Test date:** May-2010

**Hardware Availability:** Mar-2010

**Software Availability:** Dec-2009

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100330.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 08:30:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 22 June 2010.