SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X6270 M2 (Intel Xeon X5680 3.33GHz)

SPECfp®2006 = 60.5

SPECfp_base2006 = 56.5

CPU2006 license: 6
Test sponsor: Oracle Corporation
Tested by: Oracle Corporation

Test date: May-2010
Hardware Availability: Jun-2010
Software Availability: Jun-2010



Hardware

CPU Name:	Intel Xeon X5680
CPU Characteristics:	Intel Turbo Boost Technology up to 3.60 GHz
CPU MHz:	3333
FPU:	Integrated
CPU(s) enabled:	12 cores, 2 chips, 6 cores/chip, 2 threads/core
CPU(s) orderable:	1 or 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core

Continued on next page

Software

Operating System:	Oracle Solaris 10 10/09
Compiler:	Oracle Solaris Studio Express 6/10
Auto Parallel:	Yes
File System:	zfs
System State:	Default
Base Pointers:	64-bit
Peak Pointers:	32/64-bit
Other Software:	Apache C++ Standard Library V4.2.1

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X6270 M2 (Intel Xeon X5680 3.33GHz)

SPECfp2006 = 60.5

SPECfp_base2006 = 56.5

CPU2006 license: 6
Test sponsor: Oracle Corporation
Tested by: Oracle Corporation

Test date: May-2010
Hardware Availability: Jun-2010
Software Availability: Jun-2010

L3 Cache: 12 MB I+D on chip per chip
Other Cache: None
Memory: 48 GB (12 x 4 GB DDR3-1333 CL9, 2 Rank, ECC)
Disk Subsystem: 1 x 300 GB, SAS, 10000 RPM
Other Hardware: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	76.0	179	**75.2**	**181**	75.1	181	76.0	179	**75.2**	**181**	75.1	181
416.gamess	785	24.9	**785**	**24.9**	785	24.9	**742**	**26.4**	742	26.4	742	26.4
433.milc	**172**	**53.3**	172	53.3	200	45.9	**172**	**53.3**	172	53.3	200	45.9
434.zeusmp	119	76.5	118	77.3	**118**	**76.9**	112	81.3	112	81.2	**112**	**81.3**
435.gromacs	**173**	**41.2**	173	41.2	173	41.2	162	44.1	**162**	**44.1**	162	44.1
436.cactusADM	70.3	170	70.6	169	**70.4**	**170**	47.2	253	**47.3**	**253**	48.1	248
437.leslie3d	86.6	109	**86.4**	**109**	85.7	110	86.2	109	**86.2**	**109**	86.1	109
444.namd	432	18.6	**432**	**18.6**	432	18.6	432	18.6	**432**	**18.6**	432	18.6
447.dealII	**253**	**45.2**	249	45.9	253	45.2	**253**	**45.2**	249	45.9	253	45.2
450.soplex	246	33.9	243	34.4	**246**	**33.9**	228	36.5	**228**	**36.5**	228	36.6
453.povray	**183**	**29.1**	183	29.1	183	29.1	145	36.7	144	36.8	**145**	**36.7**
454.calculix	248	33.2	249	33.2	**249**	**33.2**	241	34.2	**241**	**34.2**	241	34.2
459.GemsFDTD	101	105	**102**	**104**	104	102	99.3	107	**99.4**	**107**	99.6	107
465.tonto	**303**	**32.5**	303	32.5	303	32.5	275	35.8	**267**	**36.8**	267	36.8
470.lbm	**112**	**123**	110	125	112	123	110	125	**109**	**126**	109	126
481.wrf	175	63.8	**178**	**62.7**	178	62.6	175	63.8	**178**	**62.7**	178	62.6
482.sphinx3	325	60.0	323	60.3	**324**	**60.1**	**301**	**64.8**	302	64.6	300	64.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
The Apache C++ Standard Library V4.2.1 was installed from
http://stdcxx.apache.org/download.html using:
    alias gmake=specmake
    gmake BUILDTYPE=8D CONFIG=sunpro.config
```

Operating System Notes

```
ulimit -s unlimited  (shell)

/etc/system parameters
   tune_t_fsflushr=10
   autoup=900
   zfs:zfs_arc_max = 0x10000000
   lpg_alloc_prefer=1
```

Platform Notes

```
Default BIOS settings used except:
  C-State                 : Disabled
  Data Reuse Optimization : Disabled
```

General Notes

```
Environment variables set by runspec before the start of the run:
OMP_NUM_THREADS = "12"
SUNW_MP_PROCBIND = "23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0"
SUNW_MP_THR_IDLE = "SPIN"

447.dealII (base): "apache_stdcxx_4_2_1" src.alt was used.
```

Base Compiler Invocation

C benchmarks:
`cc`

C++ benchmarks:
`CC`

Fortran benchmarks:
`f90`

Benchmarks using both Fortran and C:
`cc f90`

Base Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64`
436.cactusADM: `-DSPEC_CPU_LP64`
437.leslie3d: `-DSPEC_CPU_LP64`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
450.soplex: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64`
459.GemsFDTD: `-DSPEC_CPU_LP64`

Continued on next page

Base Portability Flags (Continued)

465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_WORDS_LITTLEENDIAN
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast -xipo=2 -m64 -xautopar -xreduction

C++ benchmarks:
-fast -xipo=2 -m64 -xalias_level=compatible -library=no%Cstd
-I/data1/stdcxx-4.2.1/include -I/data1/stdcxx-4.2.1/build/include
-L/data1/stdcxx-4.2.1/build/lib -R/data1/stdcxx-4.2.1/build/lib -lstd8D

Fortran benchmarks:
-fast -xipo=2 -m64 -xautopar -xreduction

Benchmarks using both Fortran and C:
-fast(cc) -xipo=2 -m64 -xautopar -xreduction -fast(f90)

Base Other Flags

C benchmarks:
-V -# -xjobs=24

C++ benchmarks:
-verbose=diags,version -xjobs=24

Fortran benchmarks:
-V -v -xjobs=24

Benchmarks using both Fortran and C:
-V -# -xjobs=24 -v

Peak Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Continued on next page

Peak Compiler Invocation (Continued)

Fortran benchmarks:
f90

Benchmarks using both Fortran and C:
cc f90

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_WORDS_LITTLEENDIAN

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xautopar -xreduction
-L/data1/SmartHeap_9/lib -R/data1/SmartHeap_9/lib -lsmartheap_mt64

482.sphinx3: -fast -xipo=2 -m64 -xpagesize=2M -xalias_level=std
-xrestrict -xprefetch=no%auto -xautopar -xreduction

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: basepeak = yes

450.soplex: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xpagesize=2M -xalias_level=compatible -library=stlport4
-m64

453.povray: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xvector=no%simd -xalias_level=compatible
-library=stlport4 -qoption iropt -Atile:skewp
-qoption iropt -Ainline:cs=700

Continued on next page

Peak Optimization Flags (Continued)

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -fast -xipo=2 -m64 -xpagesize=2M -xunroll=1
-xvector=no%simd

434.zeusmp: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xautopar -xreduction

437.leslie3d: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-Qoption ube -xprefetch_mult=2 -xautopar -xreduction

459.GemsFDTD: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xautopar -xreduction

465.tonto: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xautopar -xreduction -xprefetch=no%auto
-stackvar -xalias -lumem

Benchmarks using both Fortran and C:

435.gromacs: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
-xvector=no%simd -xipo=2 -m64 -xpagesize=2M
-Qoption ube -fsimple=3 -xautopar -xreduction

436.cactusADM: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -m64 -fast(cc) -fast(f90)
-xipo=0 -xpagesize=2M -xprefetch_level=2
-W2,-Aparallel:nthreads=24
-Qoption iropt -Aparallel:nthreads=24 -xautopar -xreduction
-lumem -lmvec

454.calculix: -fast(cc) -fast(f90) -xipo=2 -m64 -xpagesize=2M
-xunroll=3 -xprefetch_level=2
-xprefetch_auto_type=indirect_array_access

481.wrf: basepeak = yes

Peak Other Flags

C benchmarks:
-V -# -xjobs=24

Continued on next page

Peak Other Flags (Continued)

C++ benchmarks:
```
-verbose=diags,version -xjobs=24
```

Fortran benchmarks:
```
-V -v -xjobs=24
```

Benchmarks using both Fortran and C:
```
-V -# -xjobs=24 -v
```

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86_64.20100901.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86_64.20100901.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 12:21:15 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 31 August 2010.