



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

SPECfp<sup>®</sup>2006 = 48.7

Intel DH67BLB3 Motherboard (Intel Core i5-2500T)

SPECfp\_base2006 = 46.0

CPU2006 license: 13


Test date: Apr-2011

Test sponsor: Intel Corporation

Hardware Availability: Mar-2011

Tested by: Intel Corporation

Software Availability: Apr-2011



### Hardware

CPU Name: Intel Core i5-2500T  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.3 GHz  
 CPU MHz: 2300  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Windows 7 Ultimate (64-bit)  
 Compiler: Intel C++ Compiler XE for Intel64  
 Version 12.0.3.163 Build 20110217  
 Intel Visual Fortran Compiler XE for Intel64  
 Version 12.0.3.163 Build 20110217  
 Microsoft Visual Studio 2008 Professional SP1  
 (for libraries)  
 Auto Parallel: Yes  
 File System: NTFS

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

SPECfp2006 = **48.7**

Intel DH67BLB3 Motherboard (Intel Core i5-2500T)

SPECfp\_base2006 = **46.0**

CPU2006 license: 13

Test date: Apr-2011

Test sponsor: Intel Corporation

Hardware Availability: Mar-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

L3 Cache: 6 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 8 GB (2 x 4 GB 2Rx8 PC3-10600U-9)  
 Disk Subsystem: Seagate 1 TB SATA, 7200 RPM  
 Other Hardware: None

System State: Default  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<b><u>149</u></b>	<b><u>91.0</u></b>	151	90.2	149	91.1	<b><u>149</u></b>	<b><u>91.0</u></b>	151	90.2	149	91.1
416.gamess	<b><u>834</u></b>	<b><u>23.5</u></b>	832	23.5	835	23.5	<b><u>590</u></b>	<b><u>33.2</u></b>	590	33.2	590	33.2
433.milc	160	57.4	160	57.4	<b><u>160</u></b>	<b><u>57.4</u></b>	160	57.4	160	57.4	<b><u>160</u></b>	<b><u>57.4</u></b>
434.zeusmp	151	60.4	151	60.4	<b><u>151</u></b>	<b><u>60.4</u></b>	151	60.4	151	60.4	<b><u>151</u></b>	<b><u>60.4</u></b>
435.gromacs	277	25.8	<b><u>277</u></b>	<b><u>25.8</u></b>	277	25.8	277	25.8	<b><u>277</u></b>	<b><u>25.8</u></b>	277	25.8
436.cactusADM	109	110	<b><u>109</u></b>	<b><u>109</u></b>	110	109	106	113	105	114	<b><u>105</u></b>	<b><u>113</u></b>
437.leslie3d	152	61.9	<b><u>151</u></b>	<b><u>62.2</u></b>	151	62.2	152	61.9	<b><u>151</u></b>	<b><u>62.2</u></b>	151	62.2
444.namd	355	22.6	355	22.6	<b><u>355</u></b>	<b><u>22.6</u></b>	<b><u>352</u></b>	<b><u>22.8</u></b>	352	22.8	351	22.8
447.dealII	276	41.4	<b><u>277</u></b>	<b><u>41.4</u></b>	277	41.4	276	41.4	<b><u>277</u></b>	<b><u>41.4</u></b>	277	41.4
450.soplex	249	33.5	<b><u>249</u></b>	<b><u>33.5</u></b>	250	33.4	249	33.5	<b><u>249</u></b>	<b><u>33.5</u></b>	250	33.4
453.povray	<b><u>130</u></b>	<b><u>41.0</u></b>	130	41.1	130	41.0	<b><u>107</u></b>	<b><u>49.8</u></b>	107	49.8	107	49.9
454.calculix	232	35.6	232	35.6	<b><u>232</u></b>	<b><u>35.6</u></b>	232	35.6	232	35.6	<b><u>232</u></b>	<b><u>35.6</u></b>
459.GemsFDTD	<b><u>222</u></b>	<b><u>47.8</u></b>	222	47.8	223	47.6	<b><u>207</u></b>	<b><u>51.3</u></b>	207	51.2	207	51.3
465.tonto	<b><u>420</u></b>	<b><u>23.5</u></b>	420	23.4	419	23.5	308	31.9	<b><u>308</u></b>	<b><u>31.9</u></b>	308	31.9
470.lbm	<b><u>116</u></b>	<b><u>118</u></b>	116	118	116	118	<b><u>116</u></b>	<b><u>118</u></b>	116	118	116	118
481.wrf	206	54.1	205	54.4	<b><u>206</u></b>	<b><u>54.1</u></b>	206	54.1	205	54.4	<b><u>206</u></b>	<b><u>54.1</u></b>
482.sphinx3	441	44.2	<b><u>445</u></b>	<b><u>43.8</u></b>	446	43.7	441	44.2	<b><u>445</u></b>	<b><u>43.8</u></b>	446	43.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

Tested systems can be used with Shin-G ATX case,  
 PC Power and Cooling 1200W power supply  
 OMP\_NUM\_THREADS set to number of processors cores  
 KMP\_AFFINITY set to granularity=fine,scatter

## Base Compiler Invocation

C benchmarks:  
 icl -Qvc9 -Qstd=c99

C++ benchmarks:  
 icl -Qvc9

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 48.7

Intel DH67BLB3 Motherboard (Intel Core i5-2500T)

SPECfp\_base2006 = 46.0

CPU2006 license: 13

Test date: Apr-2011

Test sponsor: Intel Corporation

Hardware Availability: Mar-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

## Base Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_P64 -names:lowercase  
 416.gamess: -DSPEC\_CPU\_P64  
 433.milc: -DSPEC\_CPU\_P64  
 434.zeusmp: -DSPEC\_CPU\_P64  
 435.gromacs: -DSPEC\_CPU\_P64  
 436.cactusADM: -DSPEC\_CPU\_P64 -names:lowercase /assume:underscore  
 437.leslie3d: -DSPEC\_CPU\_P64  
 444.namd: -DSPEC\_CPU\_P64 /TP  
 447.dealII: -DSPEC\_CPU\_P64 -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
 450.soplex: -DSPEC\_CPU\_P64  
 453.povray: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WINDOWS\_ICL  
 454.calculix: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_NOZMODIFIER -names:lowercase  
 459.GemsFDTD: -DSPEC\_CPU\_P64  
 465.tonto: -DSPEC\_CPU\_P64  
 470.lbm: -DSPEC\_CPU\_P64  
 481.wrf: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WINDOWS\_ICL  
 482.sphinx3: -DSPEC\_CPU\_P64

## Base Optimization Flags

C benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch  
-Qauto-ilp32 /F1000000000

C++ benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch  
-Qcxx-features -Qauto-ilp32 /F1000000000 shlw64M.lib  
-link /FORCE:MULTIPLE

Fortran benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch  
/F1000000000

Benchmarks using both Fortran and C:

-QxAVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch  
-Qauto-ilp32 /F1000000000



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 48.7

Intel DH67BLB3 Motherboard (Intel Core i5-2500T)

SPECfp\_base2006 = 46.0

CPU2006 license: 13

Test date: Apr-2011

Test sponsor: Intel Corporation

Hardware Availability: Mar-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

## Peak Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000 sh1W64M.lib  
-link /FORCE:MULTIPLE

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qunroll4 -Qansi-alias -Qauto-ilp32  
/F1000000000 sh1W64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias -Qscalar-rep-  
/F1000000000

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 48.7

Intel DH67BLB3 Motherboard (Intel Core i5-2500T)

SPECfp\_base2006 = 46.0

CPU2006 license: 13

Test date: Apr-2011

Test sponsor: Intel Corporation

Hardware Availability: Mar-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

## Peak Optimization Flags (Continued)

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qunroll2 -Qopt-prefetch -Qparallel  
/F1000000000

465.tonto: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc  
/F1000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qunroll2  
-Qauto-ilp32 /F1000000000

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.html>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.xml>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 20:45:00 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 10 May 2011.