



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp[®]2006 = **62.0**

BladeSymphony BS320 (Intel Xeon X5690)

SPECfp_base2006 = **59.4**

CPU2006 license: 35


Test sponsor: HITACHI

Tested by: HITACHI

Test date: Apr-2011

Hardware Availability: Mar-2011

Software Availability: Apr-2011



Hardware

CPU Name: Intel Xeon X5690
 CPU Characteristics: Intel Turbo Boost Technology up to 3.73 GHz
 CPU MHz: 3466
 FPU: Integrated
 CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip
 CPU(s) orderable: 1, 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux
 Server release 5.4.3, Advanced Platform,
 Kernel 2.6.18-164.9.1.el5 on an x86_64
 Compiler: Intel C++ Compiler XE for Linux
 Version 12.0.3.174 Build 20110309
 Intel Fortran Compiler XE for Linux
 Version 12.0.3.174 Build 20110309
 Auto Parallel: Yes
 File System: ext3

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp2006 = **62.0**

BladeSymphony BS320 (Intel Xeon X5690)

SPECfp_base2006 = **59.4**

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Apr-2011

Hardware Availability: Mar-2011

Software Availability: Apr-2011

L3 Cache: 12 MB I+D on chip per chip
 Other Cache: None
 Memory: 48 GB (6 x 8 GB 2Rx4 PC3-10600R-9, ECC)
 Disk Subsystem: 2 x 146 GB 10000 rpm Fibre Channel RAID1 configuration
 Other Hardware: None

System State: Run level 3 (multi-user)
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	77.0	177	75.8	179	<u>76.9</u>	<u>177</u>	79.4	171	75.6	180	<u>75.8</u>	<u>179</u>
416.gamess	746	26.3	755	25.9	<u>752</u>	<u>26.0</u>	<u>654</u>	<u>29.9</u>	643	30.5	655	29.9
433.milc	190	48.4	189	48.7	<u>189</u>	<u>48.5</u>	190	48.4	189	48.7	<u>189</u>	<u>48.5</u>
434.zeusmp	76.5	119	77.6	117	<u>76.6</u>	<u>119</u>	76.5	119	77.6	117	<u>76.6</u>	<u>119</u>
435.gromacs	<u>294</u>	<u>24.3</u>	293	24.3	294	24.3	282	25.3	<u>283</u>	<u>25.3</u>	300	23.8
436.cactusADM	<u>39.9</u>	<u>300</u>	39.5	303	40.1	298	<u>39.9</u>	<u>300</u>	39.5	303	40.1	298
437.leslie3d	80.8	116	<u>84.2</u>	<u>112</u>	85.3	110	80.8	116	<u>84.2</u>	<u>112</u>	85.3	110
444.namd	382	21.0	<u>381</u>	<u>21.0</u>	381	21.0	374	21.5	<u>374</u>	<u>21.5</u>	374	21.5
447.dealII	<u>269</u>	<u>42.5</u>	287	39.9	260	44.0	<u>269</u>	<u>42.5</u>	287	39.9	260	44.0
450.soplex	<u>254</u>	<u>32.8</u>	256	32.6	254	32.8	<u>254</u>	<u>32.8</u>	256	32.6	254	32.8
453.povray	<u>157</u>	<u>33.9</u>	157	33.8	157	33.9	<u>125</u>	<u>42.5</u>	125	42.6	125	42.5
454.calculix	253	32.6	<u>255</u>	<u>32.4</u>	256	32.3	232	35.5	232	35.5	<u>232</u>	<u>35.5</u>
459.GemsFDTD	146	72.5	<u>146</u>	<u>72.8</u>	145	73.3	146	72.5	<u>146</u>	<u>72.8</u>	145	73.3
465.tonto	<u>322</u>	<u>30.5</u>	319	30.8	357	27.6	276	35.6	297	33.1	<u>279</u>	<u>35.3</u>
470.lbm	<u>48.3</u>	<u>284</u>	48.3	285	48.5	283	<u>48.3</u>	<u>284</u>	48.3	285	48.5	283
481.wrf	<u>214</u>	<u>52.2</u>	221	50.4	214	52.3	<u>214</u>	<u>52.2</u>	221	50.4	214	52.3
482.sphinx3	319	61.1	311	62.7	<u>315</u>	<u>62.0</u>	<u>298</u>	<u>65.5</u>	294	66.3	301	64.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
Hugepages was enabled with the following:
'nodedv /mnt/hugepages hugetlbfs defaults 0 0' added to /etc/fstab
echo 900 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

Platform Notes

BIOS Settings:
 Intel HT Technology = Disabled
 Data Reuse Optimization = Disabled



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp2006 = 62.0

BladeSymphony BS320 (Intel Xeon X5690)

SPECfp_base2006 = 59.4

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Apr-2011

Hardware Availability: Mar-2011

Software Availability: Apr-2011

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp2006 = 62.0

BladeSymphony BS320 (Intel Xeon X5690)

SPECfp_base2006 = 59.4

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Apr-2011

Hardware Availability: Mar-2011

Software Availability: Apr-2011

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias
-parallel

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -parallel
-static

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp2006 = 62.0

BladeSymphony BS320 (Intel Xeon X5690)

SPECfp_base2006 = 59.4

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Apr-2011

Hardware Availability: Mar-2011

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc
-opt-malloc-options=3 -auto -unroll4
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32
-ansi-alias

436.cactusADM: basepeak = yes

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>
<http://www.spec.org/cpu2006/flags/PlatformHitachi.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>
<http://www.spec.org/cpu2006/flags/PlatformHitachi.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 21:02:48 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 10 May 2011.