



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp®2006 = 49.0

NovaScale R480 F2 (Intel Xeon L7545, 1.87 GHz)

SPECfp\_base2006 = 44.5

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Dell Inc.

Test date: Apr-2011

Hardware Availability: Jul-2011

Software Availability: Apr-2011



### Hardware

CPU Name: Intel Xeon L7545  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.53 GHz  
 CPU MHz: 1866  
 FPU: Integrated  
 CPU(s) enabled: 24 cores, 4 chips, 6 cores/chip, 2 threads/core  
 CPU(s) orderable: 2,4 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 11 SP1 (x86\_64), Kernel 2.6.32.12-0.7-default  
 Compiler: Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0 Update 3  
 Auto Parallel: Yes  
 File System: ext3  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp2006 = **49.0**

NovaScale R480 F2 (Intel Xeon L7545, 1.87 GHz)

SPECfp\_base2006 = **44.5**

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Dell Inc.

Test date: Apr-2011

Hardware Availability: Jul-2011

Software Availability: Apr-2011

L3 Cache: 18 MB I+D on chip per chip  
Other Cache: None  
Memory: 512 GB (64 x 8 GB 4Rx8 PC3-8500R-7, ECC, running at 978 MHz)  
Disk Subsystem: 1 x 500 GB 7200 RPM SAS 6Gb  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	41.7	326	41.9	324	<b>41.9</b>	<b>324</b>	42.5	320	<b>41.7</b>	<b>326</b>	41.5	327
416.gamess	1315	14.9	1336	14.7	<b>1325</b>	<b>14.8</b>	<b>932</b>	<b>21.0</b>	935	20.9	931	21.0
433.milc	451	20.4	453	20.3	<b>452</b>	<b>20.3</b>	451	20.4	453	20.3	<b>452</b>	<b>20.3</b>
434.zeusmp	113	80.2	<b>114</b>	<b>79.8</b>	114	79.6	113	80.2	<b>114</b>	<b>79.8</b>	114	79.6
435.gromacs	<b>429</b>	<b>16.6</b>	432	16.5	426	16.8	401	17.8	404	17.7	<b>402</b>	<b>17.8</b>
436.cactusADM	<b>38.0</b>	<b>314</b>	37.4	319	39.4	303	<b>38.0</b>	<b>314</b>	37.4	319	39.4	303
437.leslie3d	<b>60.6</b>	<b>155</b>	61.2	153	58.8	160	<b>60.6</b>	<b>155</b>	61.2	153	58.8	160
444.namd	540	14.8	<b>540</b>	<b>14.9</b>	540	14.9	<b>531</b>	<b>15.1</b>	531	15.1	530	15.1
447.dealII	421	27.2	<b>421</b>	<b>27.2</b>	421	27.2	421	27.2	<b>421</b>	<b>27.2</b>	421	27.2
450.soplex	<b>488</b>	<b>17.1</b>	488	17.1	489	17.0	<b>488</b>	<b>17.1</b>	488	17.1	489	17.0
453.povray	229	23.2	<b>230</b>	<b>23.2</b>	231	23.0	182	29.3	<b>182</b>	<b>29.2</b>	183	29.1
454.calculix	<b>391</b>	<b>21.1</b>	391	21.1	386	21.4	<b>338</b>	<b>24.4</b>	338	24.4	337	24.4
459.GemsFDTD	132	80.5	<b>132</b>	<b>80.7</b>	128	82.9	105	101	103	103	<b>105</b>	<b>101</b>
465.tonto	616	16.0	<b>651</b>	<b>15.1</b>	665	14.8	<b>390</b>	<b>25.2</b>	391	25.1	390	25.3
470.lbm	30.0	458	<b>30.2</b>	<b>455</b>	31.6	434	30.0	458	<b>30.2</b>	<b>455</b>	31.6	434
481.wrf	427	26.1	<b>435</b>	<b>25.7</b>	439	25.5	427	26.1	<b>435</b>	<b>25.7</b>	439	25.5
482.sphinx3	556	35.0	<b>557</b>	<b>35.0</b>	559	34.9	522	37.4	<b>521</b>	<b>37.4</b>	519	37.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'mount -t hugetlbfs nodev /mnt/hugepages' was used to enable large pages
echo 900 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

## Platform Notes

BIOS Settings:  
Power Management = Maximum Performance (Default = Active Power Controller)  
Node Interleaving = Enabled (Default = Disabled)



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 49.0**

NovaScale R480 F2 (Intel Xeon L7545, 1.87 GHz)

**SPECfp\_base2006 = 44.5**

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** Dell Inc.

**Test date:** Apr-2011  
**Hardware Availability:** Jul-2011  
**Software Availability:** Apr-2011

## General Notes

The Dell PowerEdge R910 and the Bull NovaScale R480 F2 models are electronically equivalent. The results have been measured on a Dell PowerEdge R910 model.  
OMP\_NUM\_THREADS set to number of cores  
Binaries were compiled on RHEL5.5

## Base Compiler Invocation

C benchmarks:  
icc -m64

C++ benchmarks:  
icpc -m64

Fortran benchmarks:  
ifort -m64

Benchmarks using both Fortran and C:  
icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.deallI: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 49.0**

NovaScale R480 F2 (Intel Xeon L7545, 1.87 GHz)

**SPECfp\_base2006 = 44.5**

**CPU2006 license:** 20

**Test date:** Apr-2011

**Test sponsor:** Bull SAS

**Hardware Availability:** Jul-2011

**Tested by:** Dell Inc.

**Software Availability:** Apr-2011

## Base Optimization Flags (Continued)

C++ benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias`

Fortran benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch`

Benchmarks using both Fortran and C:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias`

## Peak Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

`433.milc: basepeak = yes`

`470.lbm: basepeak = yes`

`482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias  
-parallel`

C++ benchmarks:

`444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32`

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

**SPECfp2006 = 49.0**

NovaScale R480 F2 (Intel Xeon L7545, 1.87 GHz)

**SPECfp\_base2006 = 44.5**

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Dell Inc.

**Test date:** Apr-2011

**Hardware Availability:** Jul-2011

**Software Availability:** Apr-2011

## Peak Optimization Flags (Continued)

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

### Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -parallel  
-static

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

### Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32  
-ansi-alias

436.cactusADM: basepeak = yes

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110524.00.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110524.00.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECfp2006 = 49.0**

NovaScale R480 F2 (Intel Xeon L7545, 1.87 GHz)

**SPECfp\_base2006 = 44.5**

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Dell Inc.

**Test date:** Apr-2011

**Hardware Availability:** Jul-2011

**Software Availability:** Apr-2011

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 20:10:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 24 May 2011.