



SPEC® CFP2006 Result  
Copyright 2006-2014 Standard Performance Evaluation Corporation

Copyright 2006-2014 Standard Performance Evaluation Corporation

<b>HITACHI</b>		<b>SPECfp®2006 =</b> <b>30.8</b>																																																
Blade Symphony BS2000 (Intel Xeon E5603)		<b>SPECfp_base2006 =</b> <b>29.6</b>																																																
<b>CPU2006 license:</b> 35 <b>Test sponsor:</b> HITACHI <b>Tested by:</b> HITACHI		<b>Test date:</b> May-2011 <b>Hardware Availability:</b> Feb-2011 <b>Software Availability:</b> Jan-2011																																																
<table border="1"> <thead> <tr> <th>Benchmark</th> <th>Score</th> </tr> </thead> <tbody> <tr><td>410.bwaves</td><td>126</td></tr> <tr><td>416.gamess</td><td>13.3</td></tr> <tr><td>433.milc</td><td>29.8</td></tr> <tr><td>434.zeusmp</td><td>29.2</td></tr> <tr><td>435.gromacs</td><td>56.3</td></tr> <tr><td>436.cactusADM</td><td>11.4</td></tr> <tr><td>437.leslie3d</td><td>10.6</td></tr> <tr><td>444.namd</td><td>110</td></tr> <tr><td>447.dealII</td><td>9.50</td></tr> <tr><td>450.soplex</td><td>68.2</td></tr> <tr><td>453.povray</td><td>9.33</td></tr> <tr><td>454.calculix</td><td>19.8</td></tr> <tr><td>459.GemsFDTD</td><td>16.6</td></tr> <tr><td>465.tonto</td><td>18.9</td></tr> <tr><td>470.lbm</td><td>15.0</td></tr> <tr><td>481.wrf</td><td>16.3</td></tr> <tr><td>482.sphinx3</td><td>47.6</td></tr> <tr><td>482.sphinx3</td><td>14.8</td></tr> <tr><td>482.sphinx3</td><td>16.0</td></tr> <tr><td>482.sphinx3</td><td>14.5</td></tr> <tr><td>482.sphinx3</td><td>28.3</td></tr> <tr><td>482.sphinx3</td><td>24.4</td></tr> <tr><td>482.sphinx3</td><td>23.7</td></tr> </tbody> </table> <p style="text-align: center;"><b>SPECfp_base2006 = 29.6</b> <b>SPECfp2006 = 30.8</b></p>			Benchmark	Score	410.bwaves	126	416.gamess	13.3	433.milc	29.8	434.zeusmp	29.2	435.gromacs	56.3	436.cactusADM	11.4	437.leslie3d	10.6	444.namd	110	447.dealII	9.50	450.soplex	68.2	453.povray	9.33	454.calculix	19.8	459.GemsFDTD	16.6	465.tonto	18.9	470.lbm	15.0	481.wrf	16.3	482.sphinx3	47.6	482.sphinx3	14.8	482.sphinx3	16.0	482.sphinx3	14.5	482.sphinx3	28.3	482.sphinx3	24.4	482.sphinx3	23.7
Benchmark	Score																																																	
410.bwaves	126																																																	
416.gamess	13.3																																																	
433.milc	29.8																																																	
434.zeusmp	29.2																																																	
435.gromacs	56.3																																																	
436.cactusADM	11.4																																																	
437.leslie3d	10.6																																																	
444.namd	110																																																	
447.dealII	9.50																																																	
450.soplex	68.2																																																	
453.povray	9.33																																																	
454.calculix	19.8																																																	
459.GemsFDTD	16.6																																																	
465.tonto	18.9																																																	
470.lbm	15.0																																																	
481.wrf	16.3																																																	
482.sphinx3	47.6																																																	
482.sphinx3	14.8																																																	
482.sphinx3	16.0																																																	
482.sphinx3	14.5																																																	
482.sphinx3	28.3																																																	
482.sphinx3	24.4																																																	
482.sphinx3	23.7																																																	

<b>Hardware</b>		<b>Software</b>	
CPU Name:	Intel Xeon E5603	Operating System:	Red Hat Enterprise Linux Server release 5.4.3, Advanced Platform, Kernel 2.6.18-164.9.1.el5 on an x86_64
CPU Characteristics:		Compiler:	Intel C++ Compiler XE for Linux Version 12.0.3.174 Build 20110309
CPU MHz:	1600		Intel Fortran Compiler XE for Linux Version 12.0.3.174 Build 20110309
FPU:	Integrated	Auto Parallel:	Yes
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip	File System:	ext3
CPU(s) orderable:	1, 2 chips		Continued on next page
Primary Cache:	32 KB I + 32 KB D on chip per core		
Secondary Cache:	256 KB I+D on chip per core		

Continued on next page

Standard Performance Evaluation Corporation  
info@spec.org  
<http://www.spec.org/>

Page 1



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## HITACHI

BladeSymphony BS2000 (Intel Xeon E5603)

**SPECfp2006 = 30.8**

**SPECfp\_base2006 = 29.6**

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: May-2011

Hardware Availability: Feb-2011

Software Availability: Jan-2011

L3 Cache:	4 MB I+D on chip per chip
Other Cache:	None
Memory:	48 GB (12 x 4 GB 2Rx4 PC3-10600R-9, ECC, running at 1066 MHz)
Disk Subsystem:	2 x 146 GB 10000 rpm SAS RAID1 configuration
Other Hardware:	None

System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	32/64-bit
Other Software:	None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	112	122	<b>108</b>	<b>125</b>	108	126	108	126	108	126	<b>108</b>	<b>126</b>
416.gamess	1644	11.9	1652	11.9	<b>1648</b>	<b>11.9</b>	<b>1472</b>	<b>13.3</b>	1470	13.3	1474	13.3
433.milc	315	29.2	315	29.2	<b>315</b>	<b>29.2</b>	<b>308</b>	<b>29.8</b>	308	29.8	309	29.7
434.zeusmp	<b>162</b>	<b>56.3</b>	162	56.3	162	56.2	<b>162</b>	<b>56.3</b>	162	56.3	162	56.2
435.gromacs	675	10.6	<b>676</b>	<b>10.6</b>	677	10.5	<b>627</b>	<b>11.4</b>	629	11.4	626	11.4
436.cactusADM	108	111	<b>108</b>	<b>110</b>	109	109	108	111	<b>108</b>	<b>110</b>	109	109
437.leslie3d	135	69.4	<b>138</b>	<b>68.2</b>	138	68.1	<b>135</b>	69.4	<b>138</b>	<b>68.2</b>	138	68.1
444.namd	<b>860</b>	<b>9.33</b>	859	9.33	860	9.33	<b>844</b>	<b>9.50</b>	875	9.16	843	9.52
447.dealII	<b>577</b>	<b>19.8</b>	628	18.2	577	19.8	<b>577</b>	<b>19.8</b>	628	18.2	577	19.8
450.soplex	501	16.7	503	16.6	<b>501</b>	<b>16.6</b>	501	16.7	503	16.6	<b>501</b>	<b>16.6</b>
453.povray	355	15.0	354	15.0	<b>355</b>	<b>15.0</b>	<b>282</b>	<b>18.9</b>	284	18.8	282	18.9
454.calculix	558	14.8	560	14.7	<b>559</b>	<b>14.8</b>	505	16.3	<b>505</b>	<b>16.3</b>	505	16.3
459.GemsFDTD	226	47.0	222	47.8	<b>223</b>	<b>47.6</b>	226	47.0	222	47.8	<b>223</b>	<b>47.6</b>
465.tonto	672	14.6	<b>679</b>	<b>14.5</b>	764	12.9	<b>616</b>	<b>16.0</b>	622	15.8	615	16.0
470.lbm	81.9	168	<b>81.4</b>	<b>169</b>	81.2	169	81.9	168	<b>81.4</b>	<b>169</b>	81.2	169
481.wrf	398	28.0	<b>395</b>	<b>28.3</b>	389	28.7	<b>398</b>	28.0	<b>395</b>	<b>28.3</b>	389	28.7
482.sphinx3	824	23.7	817	23.9	<b>821</b>	<b>23.7</b>	<b>797</b>	<b>24.4</b>	798	24.4	787	24.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run Hugepages was enabled with the following:

```
'nodev /mnt/hugepages hugetlbfs defaults 0 0' added to /etc/fstab
echo 900 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

## Platform Notes

BIOS Settings:

Data Reuse Optimization = Disabled



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

BladeSymphony BS2000 (Intel Xeon E5603)

**SPECfp2006 =**

**30.8**

**SPECfp\_base2006 =**

**29.6**

**CPU2006 license:** 35

**Test sponsor:** HITACHI

**Tested by:** HITACHI

**Test date:**

May-2011

**Hardware Availability:** Feb-2011

**Software Availability:** Jan-2011

## Base Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias`

C++ benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias`

Fortran benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch`

Benchmarks using both Fortran and C:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias`



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

BladeSymphony BS2000 (Intel Xeon E5603)

**SPECfp2006 =**

**30.8**

**SPECfp\_base2006 =**

**29.6**

**CPU2006 license:** 35

**Test sponsor:** HITACHI

**Tested by:** HITACHI

**Test date:**

May-2011

**Hardware Availability:** Feb-2011

**Software Availability:** Jan-2011

## Peak Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)`  
`-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32`  
`-ansi-alias`

470.lbm: `basepeak = yes`

482.sphinx3: `-xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias`  
`-parallel`

C++ benchmarks:

444.namd: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)`  
`-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias`  
`-auto-ilp32`

447.dealII: `basepeak = yes`

450.soplex: `basepeak = yes`

453.povray: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)`  
`-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias`  
`-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT`

Fortran benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

BladeSymphony BS2000 (Intel Xeon E5603)

SPECfp2006 =

30.8

SPECfp\_base2006 =

29.6

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date:

May-2011

Hardware Availability:

Feb-2011

Software Availability:

Jan-2011

## Peak Optimization Flags (Continued)

410.bwaves: -xsse4.2 -ipo -O3 -no-prec-div -opt-prefetch -parallel  
-static

416.gamess: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4  
-B /usr/share/libhugetlbfss/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfss-link=BDT

Benchmarks using both Fortran and C:

435.gromacs: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32  
-ansi-alias

436.cactusADM: basepeak = yes

454.calculix: -xsse4.2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>  
<http://www.spec.org/cpu2006/flags/PlatformHitachi.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>  
<http://www.spec.org/cpu2006/flags/PlatformHitachi.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 17:56:43 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 7 June 2011.