



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp[®]2006 = 25.9

Asus M4A89GTD-PRO (Phenom II X2 560)

SPECfp_base2006 = 25.1

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2011

Hardware Availability: Sep-2010

Software Availability: Apr-2011



Hardware

CPU Name: AMD Phenom II X2 560
 CPU Characteristics:
 CPU MHz: 3300
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core

Continued on next page

Software

Operating System: Windows 7 Ultimate (64-bit)
 Compiler: Intel C++ Compiler XE for Intel 64
 Version 12.0.3.176 Build 20110309
 Intel Visual Fortran Compiler XE for Intel 64
 Version 12.0.3.176 Build 20110309
 Microsoft Visual Studio 2008 Professional SP1
 (for libraries)
 Auto Parallel: Yes
 File System: NTFS

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 25.9

Asus M4A89GTD-PRO (Phenom II X2 560)

SPECfp_base2006 = 25.1

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2011

Hardware Availability: Sep-2010

Software Availability: Apr-2011

L3 Cache: 6 MB I+D on chip per chip
Other Cache: None
Memory: 4 GB (2 x 2 GB 2Rx8 PC3-10600U-9)
Disk Subsystem: Seagate 1 TB SATA, 7200 RPM
Other Hardware: None

System State: Default
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	332	41.0	330	41.2	<u>331</u>	<u>41.1</u>	332	41.0	330	41.2	<u>331</u>	<u>41.1</u>
416.gamess	885	22.1	<u>882</u>	<u>22.2</u>	882	22.2	<u>777</u>	<u>25.2</u>	777	25.2	777	25.2
433.milc	<u>315</u>	<u>29.2</u>	315	29.2	315	29.2	<u>315</u>	<u>29.2</u>	315	29.2	315	29.2
434.zeusmp	<u>300</u>	<u>30.4</u>	300	30.4	299	30.4	<u>300</u>	<u>30.4</u>	300	30.4	299	30.4
435.gromacs	381	18.8	381	18.7	<u>381</u>	<u>18.8</u>	381	18.8	381	18.7	<u>381</u>	<u>18.8</u>
436.cactusADM	262	45.6	262	45.6	<u>262</u>	<u>45.6</u>	265	45.1	265	45.2	<u>265</u>	<u>45.2</u>
437.leslie3d	<u>476</u>	<u>19.8</u>	476	19.8	475	19.8	<u>476</u>	<u>19.8</u>	476	19.8	475	19.8
444.namd	<u>464</u>	<u>17.3</u>	464	17.3	463	17.3	<u>459</u>	<u>17.5</u>	459	17.5	459	17.5
447.dealII	<u>477</u>	<u>24.0</u>	477	24.0	477	24.0	<u>477</u>	<u>24.0</u>	477	24.0	477	24.0
450.soplex	<u>552</u>	<u>15.1</u>	552	15.1	552	15.1	<u>552</u>	<u>15.1</u>	552	15.1	552	15.1
453.povray	218	24.4	218	24.4	<u>218</u>	<u>24.4</u>	<u>179</u>	<u>29.7</u>	179	29.7	179	29.7
454.calculix	<u>322</u>	<u>25.6</u>	322	25.6	322	25.6	<u>322</u>	<u>25.6</u>	322	25.6	322	25.6
459.GemsFDTD	587	18.1	<u>587</u>	<u>18.1</u>	588	18.1	<u>578</u>	<u>18.3</u>	579	18.3	578	18.4
465.tonto	482	20.4	<u>481</u>	<u>20.5</u>	480	20.5	418	23.5	418	23.5	<u>418</u>	<u>23.5</u>
470.lbm	<u>363</u>	<u>37.8</u>	363	37.9	363	37.8	<u>363</u>	<u>37.8</u>	363	37.9	363	37.8
481.wrf	382	29.2	<u>383</u>	<u>29.2</u>	383	29.2	382	29.2	<u>383</u>	<u>29.2</u>	383	29.2
482.sphinx3	669	29.1	670	29.1	<u>669</u>	<u>29.1</u>	669	29.1	670	29.1	<u>669</u>	<u>29.1</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter

Base Compiler Invocation

C benchmarks:
icl -Qvc9 -Qstd=c99

C++ benchmarks:
icl -Qvc9

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 25.9

Asus M4A89GTD-PRO (Phenom II X2 560)

SPECfp_base2006 = 25.1

CPU2006 license: 13

Test date: May-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2010

Tested by: Intel Corporation

Software Availability: Apr-2011

Base Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64 -names:lowercase
 416.gamess: -DSPEC_CPU_P64
 433.milc: -DSPEC_CPU_P64
 434.zeusmp: -DSPEC_CPU_P64
 435.gromacs: -DSPEC_CPU_P64
 436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
 437.leslie3d: -DSPEC_CPU_P64
 444.namd: -DSPEC_CPU_P64 /TP
 447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
 450.soplex: -DSPEC_CPU_P64
 453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
 454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
 459.GemsFDTD: -DSPEC_CPU_P64
 465.tonto: -DSPEC_CPU_P64
 470.lbm: -DSPEC_CPU_P64
 481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
 482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:

/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000

C++ benchmarks:

/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
-Qcxx-features -Qauto-ilp32 -Qprec-div- /F1000000000 shlw64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:

/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
/F1000000000

Benchmarks using both Fortran and C:

/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 25.9

Asus M4A89GTD-PRO (Phenom II X2 560)

SPECfp_base2006 = 25.1

CPU2006 license: 13

Test date: May-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2010

Tested by: Intel Corporation

Software Availability: Apr-2011

Peak Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
sh1W64M.lib -link /FORCE:MULTIPLE

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias -Qauto-ilp32
/F1000000000 sh1W64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias
-Qscalar-rep- /F1000000000

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 25.9

Asus M4A89GTD-PRO (Phenom II X2 560)

SPECfp_base2006 = 25.1

CPU2006 license: 13

Test date: May-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2010

Tested by: Intel Corporation

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Qopt-prefetch -Qparallel
/F1000000000

465.tonto: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc
/F1000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qunroll2
-Qauto-ilp32 /F1000000000

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.html>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.xml>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 21:19:54 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 19 July 2011.