



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Huawei

**SPECint®2006 = 30.0**

## Tecal RH5885 V2 (Intel Xeon E7-4820)

**SPECint\_base2006 = 27.8**

CPU2006 license: 3175


Test sponsor: Huawei

Tested by: Huawei

Test date: Jan-2013

Hardware Availability: Oct-2012

Software Availability: Oct-2012



### Hardware

CPU Name: Intel Xeon E7-4820  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.27 GHz  
 CPU MHz: 2000  
 FPU: Integrated  
 CPU(s) enabled: 32 cores, 4 chips, 8 cores/chip  
 CPU(s) orderable: 2,4 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 18 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 1 TB (64 x 16 GB 4Rx4 PC3-10600R-9, ECC, running at 978 MHz)  
 Disk Subsystem: 1 x 500 GB SATA, 7200 RPM  
 Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 6.2 (Santiago)  
 2.6.32-220.el6.x86\_64  
 Compiler: C/C++: Version 13.0.0.079 of Intel C++ Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V9.01



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECint2006 = 30.0

Tecal RH5885 V2 (Intel Xeon E7-4820)

SPECint\_base2006 = 27.8

CPU2006 license: 3175  
Test sponsor: Huawei  
Tested by: Huawei

Test date: Jan-2013  
Hardware Availability: Oct-2012  
Software Availability: Oct-2012

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	541	18.0	540	18.1	<b>540</b>	<b>18.1</b>	<b>467</b>	<b>20.9</b>	468	20.9	467	20.9
401.bzip2	714	13.5	<b>714</b>	<b>13.5</b>	713	13.5	698	13.8	695	13.9	<b>697</b>	<b>13.8</b>
403.gcc	554	14.5	<b>553</b>	<b>14.5</b>	553	14.6	572	14.1	565	14.3	<b>572</b>	<b>14.1</b>
429.mcf	324	28.2	<b>323</b>	<b>28.2</b>	319	28.6	324	28.2	<b>323</b>	<b>28.2</b>	319	28.6
445.gobmk	671	15.6	673	15.6	<b>672</b>	<b>15.6</b>	<b>607</b>	<b>17.3</b>	606	17.3	608	17.3
456.hammer	<b>281</b>	<b>33.2</b>	282	33.1	281	33.2	274	34.0	276	33.7	<b>276</b>	<b>33.9</b>
458.sjeng	724	16.7	<b>724</b>	<b>16.7</b>	724	16.7	<b>698</b>	<b>17.3</b>	698	17.3	698	17.3
462.libquantum	<b>10.8</b>	<b>1920</b>	10.8	1920	10.8	1920	<b>10.8</b>	<b>1920</b>	10.8	1920	10.8	1920
464.h264ref	858	25.8	<b>857</b>	<b>25.8</b>	857	25.8	763	29.0	<b>763</b>	<b>29.0</b>	763	29.0
471.omnetpp	491	12.7	<b>594</b>	<b>10.5</b>	594	10.5	<b>387</b>	<b>16.1</b>	387	16.1	389	16.0
473.astar	415	16.9	409	17.2	<b>412</b>	<b>17.1</b>	415	16.9	409	17.2	<b>412</b>	<b>17.1</b>
483.xalancbmk	246	28.1	<b>246</b>	<b>28.0</b>	247	28.0	230	29.9	231	29.9	<b>230</b>	<b>29.9</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS configuration:  
Intel Hyper-Threading set to Disabled  
Power Technology set to Custom, Performance/Watt set to Traditional  
Sysinfo program /home/cpu2006/config/sysinfo.rev6818  
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ 5569a0425e2ad530534e4c79a46e4d28  
running on RH5885-24 Wed Jan 30 20:38:33 2013

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo  
model name : Intel(R) Xeon(R) CPU E7- 4820 @ 2.00GHz  
4 "physical id"s (chips)  
32 "processors"  
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)  
cpu cores : 8  
siblings : 8  
physical 0: cores 0 1 2 8 17 18 24 25  
physical 1: cores 0 1 2 8 17 18 24 25  
physical 2: cores 0 1 2 8 17 18 24 25

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECint2006 = 30.0

Tecal RH5885 V2 (Intel Xeon E7-4820)

SPECint\_base2006 = 27.8

CPU2006 license: 3175  
Test sponsor: Huawei  
Tested by: Huawei

Test date: Jan-2013  
Hardware Availability: Oct-2012  
Software Availability: Oct-2012

## Platform Notes (Continued)

physical 3: cores 0 1 2 8 17 18 24 25  
cache size : 18432 KB

From /proc/meminfo  
MemTotal: 1058809572 kB  
HugePages\_Total: 0  
Hugepagesize: 2048 kB

/usr/bin/lsb\_release -d  
Red Hat Enterprise Linux Server release 6.2 (Santiago)

From /etc/\*release\* /etc/\*version\*  
redhat-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)  
system-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)  
system-release-cpe: cpe:/o:redhat:enterprise\_linux:6server:ga:server

uname -a:  
Linux RH5885-24 2.6.32-220.el6.x86\_64 #1 SMP Wed Nov 9 08:03:13 EST 2011  
x86\_64 x86\_64 x86\_64 GNU/Linux

run-level 3 Jan 30 20:35

SPEC is set to: /home/cpu2006  
Filesystem Type Size Used Avail Use% Mounted on  
/dev/mapper/vg\_rh588524-lv\_home  
ext4 409G 135G 254G 35% /home

Additional information from dmidecode:  
BIOS American Megatrends Inc. RGPUC-BIOS-V023 12/17/2012  
Memory:  
64x 16 GB  
64x Hyundai HMT42GR7BMR4C-H9 16 GB 978 MHz 4 rank

(End of data from sysinfo program)  
Descriptions about memory generated by sysinfo are not correct,  
only 64 DIMMs are installed not 128, see descriptions below.  
Memory:  
64x Hyundai HMT42GR7BMR4C-H9 16 GB 978 MHz 4 rank

## General Notes

Environment variables set by runspec before the start of the run:  
KMP\_AFFINITY = "granularity=fine,compact,1,0"  
LD\_LIBRARY\_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64"  
OMP\_NUM\_THREADS = "32"

Binaries compiled on a system with 4x Xeon E7-8870 CPU + 1024GB  
memory using RHEL6.2  
Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled  
runspec command invoked through numactl i.e.:

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECint2006 = 30.0

Tecal RH5885 V2 (Intel Xeon E7-4820)

SPECint\_base2006 = 27.8

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Jan-2013

Hardware Availability: Oct-2012

Software Availability: Oct-2012

## General Notes (Continued)

numactl --interleave=all runspec <etc>

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
 401.bzip2: -DSPEC\_CPU\_LP64  
 403.gcc: -DSPEC\_CPU\_LP64  
 429.mcf: -DSPEC\_CPU\_LP64  
 445.gobmk: -DSPEC\_CPU\_LP64  
 456.hmmer: -DSPEC\_CPU\_LP64  
 458.sjeng: -DSPEC\_CPU\_LP64  
 462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
 464.h264ref: -DSPEC\_CPU\_LP64  
 471.omnetpp: -DSPEC\_CPU\_LP64  
 473.astar: -DSPEC\_CPU\_LP64  
 483.xalancbmk: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32

-Wl,-z,muldefs -L/home/cpu2006/smartheap -lsmartheap64

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECint2006 = 30.0

Tecal RH5885 V2 (Intel Xeon E7-4820)

SPECint\_base2006 = 27.8

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Jan-2013

Hardware Availability: Oct-2012

Software Availability: Oct-2012

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

400.perlbench: icc -m32

445.gobmk: icc -m32

464.h264ref: icc -m32

C++ benchmarks (except as noted below):

icpc -m32

473.astar: icpc -m64

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

401.bzip2: -DSPEC\_CPU\_LP64

403.gcc: -DSPEC\_CPU\_LP64

429.mcf: -DSPEC\_CPU\_LP64

456.hmmmer: -DSPEC\_CPU\_LP64

458.sjeng: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX

473.astar: -DSPEC\_CPU\_LP64

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-prefetch -ansi-alias

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div -prof-use(pass 2) -auto-ilp32  
-opt-prefetch -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -inline-calloc  
-opt-malloc-options=3 -auto-ilp32

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECint2006 = 30.0

Tecal RH5885 V2 (Intel Xeon E7-4820)

SPECint\_base2006 = 27.8

CPU2006 license: 3175

Test date: Jan-2013

Test sponsor: Huawei

Hardware Availability: Oct-2012

Tested by: Huawei

Software Availability: Oct-2012

## Peak Optimization Flags (Continued)

456.hmmcr: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32  
-ansi-alias

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll4

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-ra-region-strategy=block -ansi-alias  
-Wl,-z,muldefs -L/home/cpu2006/smartheap -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: -xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias  
-Wl,-z,muldefs -L/home/cpu2006/smartheap -lsmartheap

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-revG.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-revG.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei	SPECint2006 = 30.0
Tecal RH5885 V2 (Intel Xeon E7-4820)	SPECint_base2006 = 27.8

**CPU2006 license:** 3175  
**Test sponsor:** Huawei  
**Tested by:** Huawei

**Test date:** Jan-2013  
**Hardware Availability:** Oct-2012  
**Software Availability:** Oct-2012

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
 For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
 Report generated on Thu Jul 24 15:16:34 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
 Originally published on 26 February 2013.