



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Huawei

SPECfp®\_rate2006 = 719

### Tecal RH5885 V2 (Intel Xeon E7-4860)

SPECfp\_rate\_base2006 = 707

CPU2006 license: 3175


Test sponsor: Huawei

Tested by: Huawei

Test date: Feb-2013

Hardware Availability: Oct-2012

Software Availability: Oct-2012



#### Hardware

CPU Name: Intel Xeon E7-4860  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.67 GHz  
 CPU MHz: 2267  
 FPU: Integrated  
 CPU(s) enabled: 40 cores, 4 chips, 10 cores/chip, 2 threads/core  
 CPU(s) orderable: 2,4 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

#### Software

Operating System: Red Hat Enterprise Linux Server release 6.2 (Santiago)  
 2.6.32-220.el6.x86\_64  
 Compiler: C/C++: Version 13.0.0.079 of Intel C++ Studio XE for Linux;  
 Fortran: Version 13.0.0.079 of Intel Fortran Studio XE for Linux  
 Auto Parallel: No  
 File System: ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Huawei

SPECfp\_rate2006 = **719**

## Tecal RH5885 V2 (Intel Xeon E7-4860)

SPECfp\_rate\_base2006 = **707**

CPU2006 license: 3175

Test date: Feb-2013

Test sponsor: Huawei

Hardware Availability: Oct-2012

Tested by: Huawei

Software Availability: Oct-2012

L3 Cache: 24 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 1 TB (64 x 16 GB 4Rx4 PC3-10600R-9, ECC, running at 1066 MHz)  
 Disk Subsystem: 1 x 500 GB SATA, 7200 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	80	2005	542	<b>2031</b>	<b>535</b>	2033	535	80	2005	542	<b>2031</b>	<b>535</b>	2033	535
416.gamess	80	2005	781	2024	774	<b>2019</b>	<b>776</b>	80	1916	818	<b>1925</b>	<b>814</b>	1933	810
433.milc	80	1271	578	1271	578	<b>1271</b>	<b>578</b>	80	1271	578	1271	578	<b>1271</b>	<b>578</b>
434.zeusmp	80	930	783	<b>930</b>	<b>783</b>	931	782	80	930	783	<b>930</b>	<b>783</b>	931	782
435.gromacs	80	<b>610</b>	<b>936</b>	610	936	611	935	80	612	933	613	931	<b>612</b>	<b>933</b>
436.cactusADM	80	<b>1210</b>	<b>790</b>	1211	789	1208	791	80	<b>1210</b>	<b>790</b>	1211	789	1208	791
437.leslie3d	80	1888	398	1888	398	<b>1888</b>	<b>398</b>	80	<b>1888</b>	<b>398</b>	1889	398	1883	399
444.namd	80	<b>922</b>	<b>696</b>	923	695	921	697	80	905	709	<b>906</b>	<b>708</b>	911	704
447.dealII	80	690	1330	696	1310	<b>692</b>	<b>1320</b>	80	690	1330	696	1310	<b>692</b>	<b>1320</b>
450.soplex	80	<b>1469</b>	<b>454</b>	1470	454	1469	454	80	1454	459	1456	458	<b>1455</b>	<b>458</b>
453.povray	80	393	1080	390	1090	<b>392</b>	<b>1090</b>	80	<b>344</b>	<b>1240</b>	343	1240	345	1230
454.calculix	80	<b>749</b>	<b>881</b>	750	880	744	887	80	<b>749</b>	<b>881</b>	750	880	744	887
459.GemsFDTD	80	2122	400	2121	400	<b>2121</b>	<b>400</b>	80	2122	400	2121	400	<b>2121</b>	<b>400</b>
465.tonto	80	<b>936</b>	<b>841</b>	936	841	929	847	80	919	857	<b>917</b>	<b>858</b>	915	860
470.lbm	80	<b>1396</b>	<b>787</b>	1399	786	1396	788	80	<b>1396</b>	<b>787</b>	1399	786	1396	788
481.wrf	80	1283	697	1281	698	<b>1283</b>	<b>697</b>	80	1265	706	1271	703	<b>1266</b>	<b>706</b>
482.sphinx3	80	<b>2288</b>	<b>682</b>	2288	682	2290	681	80	2221	702	<b>2222</b>	<b>702</b>	2223	702

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = 719

Tecal RH5885 V2 (Intel Xeon E7-4860)

SPECfp\_rate\_base2006 = 707

CPU2006 license: 3175  
Test sponsor: Huawei  
Tested by: Huawei

Test date: Feb-2013  
Hardware Availability: Oct-2012  
Software Availability: Oct-2012

## Platform Notes

BIOS configuration:  
Power Technology set to Custom, Performance/Watt set to Traditional  
Sysinfo program /home/cpu2006/config/sysinfo.rev6818  
\$Rev: 6818 \$ \$Date:: 2012-07-17 # \$ 5569a0425e2ad530534e4c79a46e4d28  
running on RH5885-24 Sun Feb 3 02:53:26 2013

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name      : Intel(R) Xeon(R) CPU E7- 4860 @ 2.27GHz
 4 "physical id"s (chips)
 80 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
  cpu cores      : 10
  siblings       : 20
  physical 0:    cores 0 1 2 8 9 16 17 18 24 25
  physical 1:    cores 0 1 2 8 9 16 17 18 24 25
  physical 2:    cores 0 1 2 8 9 16 17 18 24 25
  physical 3:    cores 0 1 2 8 9 16 17 18 24 25
cache size      : 24576 KB
```

```
From /proc/meminfo
MemTotal:        1058803604 kB
HugePages_Total: 0
Hugepagesize:    2048 kB
```

```
/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.2 (Santiago)
```

```
From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

```
uname -a:
Linux RH5885-24 2.6.32-220.el6.x86_64 #1 SMP Wed Nov 9 08:03:13 EST 2011
x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Feb 2 09:14
```

```
SPEC is set to: /home/cpu2006
Filesystem      Type      Size      Used Avail Use% Mounted on
/dev/mapper/vg_rh588524-lv_home
                ext4      409G      86G   303G   22% /home
```

Additional information from dmidecode:  
BIOS American Megatrends Inc. RGPUC-BIOS-V023 12/17/2012  
Memory:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = 719

Tecal RH5885 V2 (Intel Xeon E7-4860)

SPECfp\_rate\_base2006 = 707

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Feb-2013

Hardware Availability: Oct-2012

Software Availability: Oct-2012

## Platform Notes (Continued)

64x 16 GB

64x Hyundai HMT42GR7BMR4C-H9 16 GB 1067 MHz 4 rank

(End of data from sysinfo program)

Descriptions about memory generated by sysinfo are not correct, only 64 DIMMs are installed not 128, see descriptions below.

Memory:

64x Hyundai HMT42GR7BMR4C-H9 16 GB 1067 MHz 4 rank

## General Notes

Environment variables set by runspec before the start of the run:  
LD\_LIBRARY\_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64"

Binaries compiled on a system with 4x Xeon E7-8870 CPU + 1024GB memory using RHEL6.2

Transparent Huge Pages disabled with:

echo never > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

Filesystem page cache cleared with:

echo 1> /proc/sys/vm/drop\_caches

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64

416.gamess: -DSPEC\_CPU\_LP64

433.milc: -DSPEC\_CPU\_LP64

434.zeusmp: -DSPEC\_CPU\_LP64

435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main

436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main

437.leslie3d: -DSPEC\_CPU\_LP64

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 4



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = 719

Tecal RH5885 V2 (Intel Xeon E7-4860)

SPECfp\_rate\_base2006 = 707

CPU2006 license: 3175

Test date: Feb-2013

Test sponsor: Huawei

Hardware Availability: Oct-2012

Tested by: Huawei

Software Availability: Oct-2012

## Base Portability Flags (Continued)

```

444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

## Base Optimization Flags

C benchmarks:

```

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

```

C++ benchmarks:

```

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

```

Fortran benchmarks:

```

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

```

Benchmarks using both Fortran and C:

```

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

```

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
icc -m64
```

```
482.sphinx3: icc -m32
```

C++ benchmarks (except as noted below):

```
icpc -m64
```

```
450.soplex: icpc -m32
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = 719

Tecal RH5885 V2 (Intel Xeon E7-4860)

SPECfp\_rate\_base2006 = 707

CPU2006 license: 3175

Test date: Feb-2013

Test sponsor: Huawei

Hardware Availability: Oct-2012

Tested by: Huawei

Software Availability: Oct-2012

## Peak Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

```

## Peak Optimization Flags

C benchmarks:

```

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
         -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
         -prof-use(pass 2) -static -auto-ilp32

```

```

470.lbm: basepeak = yes

```

```

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -opt-mem-layout-trans=3
            -unroll2

```

C++ benchmarks:

```

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
         -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
         -prof-use(pass 2) -fno-alias -auto-ilp32

```

```

447.dealII: basepeak = yes

```

```

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
         -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
         -prof-use(pass 2) -opt-malloc-options=3

```

```

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
         -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
         -prof-use(pass 2) -unroll4 -ansi-alias

```

Fortran benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = 719

Tecal RH5885 V2 (Intel Xeon E7-4860)

SPECfp\_rate\_base2006 = 707

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Feb-2013

Hardware Availability: Oct-2012

Software Availability: Oct-2012

## Peak Optimization Flags (Continued)

410.bwaves: basepeak = yes

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

459.GemsFDTD: basepeak = yes

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto  
-inline-alloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)  
-prof-use(pass 2) -opt-prefetch -static -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-revG.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-revG.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 15:13:58 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 26 February 2013.