



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec


SPECint®\_rate2006 = 463

Servidor Itaotec MX225 (Intel Xeon E5-2640)

SPECint\_rate\_base2006 = 445

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Mar-2013  
Hardware Availability: Jun-2012  
Software Availability: Jun-2012



**Hardware**

CPU Name: Intel Xeon E5-2640  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.00 GHz  
 CPU MHz: 2500  
 FPU: Integrated  
 CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 15 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 64 GB (16 x 4 GB 2Rx4 PC3-10600R-9, ECC)  
 Disk Subsystem: 1000 GB, SATA-3, 7200 RPM  
 Other Hardware: None

**Software**

Operating System: Red Hat Enterprise Linux Server Release 6.3, 2.6.32-279.el6.x86\_64  
 Compiler: C/C++: Version 12.1.0 of Intel Compiler XE Build 20111011  
 Auto Parallel: No  
 File System: ext4  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V8.1



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint\_rate2006 = 463

Servidor Itaotec MX225 (Intel Xeon E5-2640)

SPECint\_rate\_base2006 = 445

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Mar-2013  
Hardware Availability: Jun-2012  
Software Availability: Jun-2012

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	24	730	321	<u>731</u>	<u>321</u>	747	314	24	<u>625</u>	<u>375</u>	639	367	608	386
401.bzip2	24	<u>964</u>	<u>240</u>	960	241	981	236	24	<u>953</u>	<u>243</u>	976	237	938	247
403.gcc	24	538	359	<u>538</u>	<u>359</u>	534	362	24	535	361	<u>538</u>	<u>359</u>	540	358
429.mcf	24	312	701	316	692	<u>316</u>	<u>693</u>	24	312	701	316	692	<u>316</u>	<u>693</u>
445.gobmk	24	745	338	763	330	<u>762</u>	<u>331</u>	24	747	337	748	337	<u>747</u>	<u>337</u>
456.hammer	24	<u>404</u>	<u>555</u>	404	554	403	556	24	<u>335</u>	<u>668</u>	335	668	336	667
458.sjeng	24	<u>871</u>	<u>333</u>	871	333	890	326	24	831	349	857	339	<u>844</u>	<u>344</u>
462.libquantum	24	187	2660	<u>187</u>	<u>2650</u>	188	2650	24	187	2660	<u>187</u>	<u>2650</u>	188	2650
464.h264ref	24	965	551	<u>934</u>	<u>569</u>	932	570	24	928	572	<u>917</u>	<u>579</u>	917	579
471.omnetpp	24	<u>575</u>	<u>261</u>	577	260	575	261	24	539	278	540	278	<u>540</u>	<u>278</u>
473.astar	24	638	264	642	262	<u>640</u>	<u>263</u>	24	638	264	642	262	<u>640</u>	<u>263</u>
483.xalancbmk	24	335	494	<u>335</u>	<u>495</u>	335	495	24	335	494	<u>335</u>	<u>495</u>	335	495

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
numactl was used to bind copies to the cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run.  
Large pages were not enabled for this run

## Platform Notes

Sysinfo program /home/rcaneca/cpu2006/Docs/sysinfo  
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ 8787f7622badcf24e01c368b1db4377c  
running on mx225 Sat Mar 9 04:28:48 2013

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo  
model name : Intel(R) Xeon(R) CPU E5-2640 0 @ 2.50GHz  
2 "physical id"s (chips)  
24 "processors"  
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)  
cpu cores : 6  
siblings : 12

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECint\_rate2006 = 463

Servidor Itautec MX225 (Intel Xeon E5-2640)

SPECint\_rate\_base2006 = 445

CPU2006 license: 9001  
Test sponsor: Itautec  
Tested by: Itautec

Test date: Mar-2013  
Hardware Availability: Jun-2012  
Software Availability: Jun-2012

## Platform Notes (Continued)

```
physical 0: cores 0 1 2 3 4 5
physical 1: cores 0 1 2 3 4 5
cache size : 15360 KB
```

```
From /proc/meminfo
MemTotal:      65917564 kB
HugePages_Total: 0
Hugepagesize:  2048 kB
```

```
/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.3 (Santiago)
```

```
From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.3 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.3 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

```
uname -a:
Linux mx225 2.6.32-279.el6.x86_64 #1 SMP Wed Jun 13 18:24:36 EDT 2012 x86_64
x86_64 x86_64 GNU/Linux
```

```
run-level 3 Mar 8 15:50
```

```
SPEC is set to: /home/rcaneca/cpu2006
Filesystem      Type      Size  Used Avail Use% Mounted on
/dev/mapper/vg_mx225-lv_home
                ext4      836G  2.2G  791G   1% /home
```

(End of data from sysinfo program)

## General Notes

This result was measured on the Servidor Itautec MX225.  
The Servidor Itautec MX215 and the Servidor Itautec MX225  
are electronically equivalent.

## Base Compiler Invocation

C benchmarks:  
icc -m32

C++ benchmarks:  
icpc -m32



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECint\_rate2006 = 463

Servidor Itautec MX225 (Intel Xeon E5-2640)

SPECint\_rate\_base2006 = 445

CPU2006 license: 9001  
Test sponsor: Itautec  
Tested by: Itautec

Test date: Mar-2013  
Hardware Availability: Jun-2012  
Software Availability: Jun-2012

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3  
C++ benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3  
-Wl,-z,muldefs -L/home/rcaneca/sh/SmartHeap\_8.1/lib -lsmartheap

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc -m32  
400.perlbench: icc -m64  
401.bzip2: icc -m64  
456.hmmmer: icc -m64  
458.sjeng: icc -m64  
C++ benchmarks:  
icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint\_rate2006 = 463

Servidor Itaotec MX225 (Intel Xeon E5-2640)

SPECint\_rate\_base2006 = 445

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Mar-2013  
Hardware Availability: Jun-2012  
Software Availability: Jun-2012

## Peak Portability Flags (Continued)

462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias -opt-mem-layout-trans=3

456.hmmr: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/home/rcaneca/sh/SmartHeap\_8.1/lib -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint\_rate2006 = 463

Servidor Itaotec MX225 (Intel Xeon E5-2640)

SPECint\_rate\_base2006 = 445

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Mar-2013  
Hardware Availability: Jun-2012  
Software Availability: Jun-2012

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>  
[http://www.spec.org/cpu2006/flags/Itaotec-Servidor\\_Itaotec-Intel-Linux-Platform.html](http://www.spec.org/cpu2006/flags/Itaotec-Servidor_Itaotec-Intel-Linux-Platform.html)

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>  
[http://www.spec.org/cpu2006/flags/Itaotec-Servidor\\_Itaotec-Intel-Linux-Platform.xml](http://www.spec.org/cpu2006/flags/Itaotec-Servidor_Itaotec-Intel-Linux-Platform.xml)

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 14:13:05 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 26 March 2013.