



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Dell Inc.

**SPECfp<sup>®</sup>2006 = 105**

PowerEdge R920 (Intel Xeon E7-4890 v2, 2.80 GHz)

**SPECfp\_base2006 = 99.6**

CPU2006 license: 55


Test date: Feb-2014

Test sponsor: Dell Inc.

Hardware Availability: Mar-2014

Tested by: Dell Inc.

Software Availability: Mar-2014



### Hardware

CPU Name: Intel Xeon E7-4890 v2  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.40 GHz  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 60 cores, 4 chips, 15 cores/chip, 2 threads/core  
 CPU(s) orderable: 2,4 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64)  
 3.0.76-0.11-default  
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;  
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext2  
 System State: Run level 3 (multi-user)

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 105

PowerEdge R920 (Intel Xeon E7-4890 v2, 2.80 GHz)

SPECfp\_base2006 = 99.6

CPU2006 license: 55

Test date: Feb-2014

Test sponsor: Dell Inc.

Hardware Availability: Mar-2014

Tested by: Dell Inc.

Software Availability: Mar-2014

L3 Cache: 37.5 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 1 TB (64 x 16 GB 2Rx4 PC3L-12800R-11, ECC)  
 Disk Subsystem: 1 x 400 GB SAS6 SSD  
 Other Hardware: None

Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<b><u>15.8</u></b>	<b><u>858</u></b>	15.9	856	15.4	881	<b><u>15.8</u></b>	<b><u>858</u></b>	15.9	856	15.4	881
416.gamess	596	32.9	<b><u>596</u></b>	<b><u>32.9</u></b>	596	32.8	532	36.8	533	36.8	<b><u>533</u></b>	<b><u>36.8</u></b>
433.milc	153	59.9	<b><u>153</u></b>	<b><u>59.8</u></b>	154	59.5	<b><u>153</u></b>	<b><u>60.1</u></b>	154	59.5	152	60.5
434.zeusmp	<b><u>57.4</u></b>	<b><u>158</u></b>	57.4	158	57.4	158	<b><u>57.4</u></b>	<b><u>158</u></b>	57.4	158	57.4	158
435.gromacs	180	39.6	180	39.7	<b><u>180</u></b>	<b><u>39.7</u></b>	180	39.6	180	39.7	<b><u>180</u></b>	<b><u>39.7</u></b>
436.cactusADM	16.7	715	18.1	659	<b><u>17.9</u></b>	<b><u>667</u></b>	16.7	715	18.1	659	<b><u>17.9</u></b>	<b><u>667</u></b>
437.leslie3d	53.0	177	47.4	198	<b><u>47.4</u></b>	<b><u>198</u></b>	53.0	177	47.4	198	<b><u>47.4</u></b>	<b><u>198</u></b>
444.namd	<b><u>342</u></b>	<b><u>23.4</u></b>	342	23.4	342	23.4	335	24.0	335	24.0	<b><u>335</u></b>	<b><u>24.0</u></b>
447.dealII	216	53.0	<b><u>216</u></b>	<b><u>52.9</u></b>	217	52.7	216	53.0	<b><u>216</u></b>	<b><u>52.9</u></b>	217	52.7
450.soplex	196	42.5	195	42.8	<b><u>195</u></b>	<b><u>42.7</u></b>	196	42.5	195	42.8	<b><u>195</u></b>	<b><u>42.7</u></b>
453.povray	117	45.6	<b><u>117</u></b>	<b><u>45.5</u></b>	117	45.4	97.7	54.4	<b><u>97.6</u></b>	<b><u>54.5</u></b>	97.6	54.5
454.calculix	195	42.3	<b><u>198</u></b>	<b><u>41.7</u></b>	198	41.6	174	47.3	175	47.2	<b><u>175</u></b>	<b><u>47.3</u></b>
459.GemsFDTD	53.2	199	<b><u>53.6</u></b>	<b><u>198</u></b>	53.6	198	47.9	221	47.7	222	<b><u>47.9</u></b>	<b><u>221</u></b>
465.tonto	274	35.9	298	33.0	<b><u>279</u></b>	<b><u>35.3</u></b>	<b><u>215</u></b>	<b><u>45.7</u></b>	215	45.7	215	45.8
470.lbm	<b><u>10.2</u></b>	<b><u>1340</u></b>	10.2	1340	10.4	1310	<b><u>10.2</u></b>	<b><u>1340</u></b>	10.2	1340	10.4	1310
481.wrf	111	100	114	98.1	<b><u>112</u></b>	<b><u>99.3</u></b>	111	100	114	98.1	<b><u>112</u></b>	<b><u>99.3</u></b>
482.sphinx3	270	72.1	<b><u>275</u></b>	<b><u>71.0</u></b>	275	70.8	273	71.4	<b><u>273</u></b>	<b><u>71.3</u></b>	275	70.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS settings:  
 Virtualization Technology disabled  
 Execute Disable disabled  
 System Profile set to Custom  
 ClE enabled  
 C States enabled  
 Memory Patrol Scrub set to disabled  
 Sysinfo program  
 /root/Desktop/Performance/ic14.0\_Oct17\_2013/config/sysinfo.rev6818  
 \$Rev: 6818 \$ \$Date:: 2012-07-17 # \$ e86d102572650a6e4d596a3cee98f191

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 105

PowerEdge R920 (Intel Xeon E7-4890 v2, 2.80 GHz)

SPECfp\_base2006 = 99.6

CPU2006 license: 55

Test date: Feb-2014

Test sponsor: Dell Inc.

Hardware Availability: Mar-2014

Tested by: Dell Inc.

Software Availability: Mar-2014

## Platform Notes (Continued)

running on slesperf1 Fri Feb 7 13:07:45 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

```

model name : Intel(R) Xeon(R) CPU E7-4890 v2 @ 2.80GHz
 4 "physical id"s (chips)
 120 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 15
  siblings  : 30
  physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
  physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
  physical 2: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
  physical 3: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
cache size : 38400 KB

```

From /proc/meminfo

```

MemTotal:      1058789108 kB
HugePages_Total:    0
Hugepagesize:    2048 kB

```

/usr/bin/lsb\_release -d

SUSE Linux Enterprise Server 11 (x86\_64)

From /etc/\*release\* /etc/\*version\*

```

SuSE-release:
  SUSE Linux Enterprise Server 11 (x86_64)
  VERSION = 11
  PATCHLEVEL = 3

```

uname -a:

Linux slesperf1 3.0.76-0.11-default #1 SMP Fri Jun 14 08:21:43 UTC 2013 (ccab990) x86\_64 x86\_64 x86\_64 GNU/Linux

run-level 3 Feb 7 06:56 last=S

SPEC is set to: /root/Desktop/Performance/ic14.0\_Oct17\_2013

```

Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda2       ext2  365G   31G  333G   9% /

```

Additional information from dmidecode:

BIOS Dell Inc. 1.0.4 01/27/2014

Memory:

```

32x 00CE00B300CE M393B2G70BH0-YK0 16 GB 1333 MHz
10x 00CE00B300CE M393B2G70CB0-YK0 16 GB 1333 MHz
22x 00CE04B300CE M393B2G70CB0-YK0 16 GB 1333 MHz

```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 105

PowerEdge R920 (Intel Xeon E7-4890 v2, 2.80 GHz)

SPECfp\_base2006 = 99.6

CPU2006 license: 55

Test date: Feb-2014

Test sponsor: Dell Inc.

Hardware Availability: Mar-2014

Tested by: Dell Inc.

Software Availability: Mar-2014

## Platform Notes (Continued)

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact,1,0"

LD\_LIBRARY\_PATH = "/root/Desktop/Performance/icl4.0\_Oct17\_2013/libs/32:/root/Desktop/Performance/icl4.0\_Oct17\_2013/libs/64:/root/Desktop/Performance/icl4.0\_Oct17\_2013/sh"

OMP\_NUM\_THREADS = "60"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/transparent\_hugepage/enabled

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 450.soplex: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 105

PowerEdge R920 (Intel Xeon E7-4890 v2, 2.80 GHz)

SPECfp\_base2006 = 99.6

CPU2006 license: 55

Test date: Feb-2014

Test sponsor: Dell Inc.

Hardware Availability: Mar-2014

Tested by: Dell Inc.

Software Availability: Mar-2014

## Base Portability Flags (Continued)

470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias  
C++ benchmarks:  
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias  
Fortran benchmarks:  
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch  
Benchmarks using both Fortran and C:  
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

## Peak Compiler Invocation

C benchmarks:  
icc -m64  
C++ benchmarks:  
icpc -m64  
Fortran benchmarks:  
ifort -m64  
Benchmarks using both Fortran and C:  
icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:  
433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32  
-ansi-alias

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 105

PowerEdge R920 (Intel Xeon E7-4890 v2, 2.80 GHz)

SPECfp\_base2006 = 99.6

CPU2006 license: 55

Test date: Feb-2014

Test sponsor: Dell Inc.

Hardware Availability: Mar-2014

Tested by: Dell Inc.

Software Availability: Mar-2014

## Peak Optimization Flags (Continued)

470.lbm: basepeak = yes

482.sphinx3: -xAVX -ipo -O3 -no-prec-div -unroll2 -ansi-alias  
-parallel

### C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4

### Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 105

PowerEdge R920 (Intel Xeon E7-4890 v2, 2.80 GHz)

SPECfp\_base2006 = 99.6

CPU2006 license: 55

Test date: Feb-2014

Test sponsor: Dell Inc.

Hardware Availability: Mar-2014

Tested by: Dell Inc.

Software Availability: Mar-2014

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>

<http://www.spec.org/cpu2006/flags/Dell-Platform-Settings-V1.2-revC.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>

<http://www.spec.org/cpu2006/flags/Dell-Platform-Settings-V1.2-revC.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 20:44:53 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 25 March 2014.