



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

IBM System x3950 X6  
(Intel Xeon E7-8850 v2, 2.30 GHz)

SPECfp<sup>®</sup>\_rate2006 = 2430

SPECfp\_rate\_base2006 = 2380

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: May-2014

Hardware Availability: Jun-2014

Software Availability: Nov-2013



### Hardware

CPU Name: Intel Xeon E7-8850 v2  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz  
 CPU MHz: 2300  
 FPU: Integrated  
 CPU(s) enabled: 96 cores, 8 chips, 12 cores/chip, 2 threads/core  
 CPU(s) orderable: 4,6,8 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server release 6.5 (Santiago)  
 2.6.32-431.el6.x86\_64  
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;  
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux  
 Auto Parallel: No  
 File System: ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

IBM System x3950 X6  
(Intel Xeon E7-8850 v2, 2.30 GHz)

SPECfp\_rate2006 = 2430

SPECfp\_rate\_base2006 = 2380

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: May-2014

Hardware Availability: Jun-2014

Software Availability: Nov-2013

L3 Cache: 24 MB I+D on chip per chip  
Other Cache: None  
Memory: 2 TB (128 x 16 GB 2Rx4 PC3L-12800R-11, ECC, running at 1066 MHz)  
Disk Subsystem: 1 x 400 GB SATA, SSD  
Other Hardware: None

System State: Run level 3 (multi-user)  
Base Pointers: 32/64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	192	<b>1232</b>	<b>2120</b>	1233	2120	1229	2120	192	<b>1232</b>	<b>2120</b>	1233	2120	1229	2120
416.gamess	192	<b>1395</b>	<b>2700</b>	1400	2690	1388	2710	192	1372	2740	1377	2730	<b>1373</b>	<b>2740</b>
433.milc	192	<b>859</b>	<b>2050</b>	859	2050	859	2050	192	860	2050	858	2050	<b>859</b>	<b>2050</b>
434.zeusmp	192	665	2630	<b>664</b>	<b>2630</b>	663	2640	192	665	2630	<b>664</b>	<b>2630</b>	663	2640
435.gromacs	192	427	3210	<b>430</b>	<b>3190</b>	430	3190	192	425	3220	423	3240	<b>424</b>	<b>3230</b>
436.cactusADM	192	<b>793</b>	<b>2890</b>	791	2900	796	2880	192	<b>793</b>	<b>2890</b>	791	2900	796	2880
437.leslie3d	192	1308	1380	1307	1380	<b>1308</b>	<b>1380</b>	96	593	1520	598	1510	<b>596</b>	<b>1510</b>
444.namd	192	710	2170	<b>714</b>	<b>2160</b>	726	2120	192	710	2170	<b>714</b>	<b>2160</b>	726	2120
447.dealII	192	492	4470	490	4480	<b>491</b>	<b>4470</b>	192	492	4470	490	4480	<b>491</b>	<b>4470</b>
450.soplex	192	1171	1370	<b>1172</b>	<b>1370</b>	1173	1370	96	574	1390	<b>576</b>	<b>1390</b>	577	1390
453.povray	192	<b>279</b>	<b>3660</b>	277	3690	280	3650	192	238	4290	<b>238</b>	<b>4300</b>	237	4310
454.calculix	192	571	2770	566	2800	<b>570</b>	<b>2780</b>	192	571	2770	566	2800	<b>570</b>	<b>2780</b>
459.GemsFDTD	192	1598	1280	1601	1270	<b>1599</b>	<b>1270</b>	192	1598	1280	1601	1270	<b>1599</b>	<b>1270</b>
465.tonto	192	720	2620	<b>717</b>	<b>2630</b>	717	2640	192	692	2730	<b>692</b>	<b>2730</b>	693	2730
470.lbm	192	1055	2500	<b>1055</b>	<b>2500</b>	1056	2500	192	1055	2500	<b>1055</b>	<b>2500</b>	1056	2500
481.wrf	192	<b>856</b>	<b>2510</b>	851	2520	857	2500	192	849	2520	<b>851</b>	<b>2520</b>	852	2520
482.sphinx3	192	<b>1642</b>	<b>2280</b>	1640	2280	1644	2280	192	<b>1642</b>	<b>2280</b>	1640	2280	1644	2280

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

**SPECfp\_rate2006 = 2430**

IBM System x3950 X6  
(Intel Xeon E7-8850 v2, 2.30 GHz)

**SPECfp\_rate\_base2006 = 2380**

**CPU2006 license:** 11

**Test date:** May-2014

**Test sponsor:** IBM Corporation

**Hardware Availability:** Jun-2014

**Tested by:** IBM Corporation

**Software Availability:** Nov-2013

## Platform Notes

Operating Mode set to Maximum Performance in BIOS  
Memory Data Scrambling Disabled  
Patrol Scrub Disabled  
Sysinfo program /cpu2006.1.2\_14\_aug2013/config/sysinfo.rev6818  
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191  
running on x3950x6 Wed May 21 07:25:56 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name      : Intel(R) Xeon(R) CPU E7-8850 v2 @ 2.30GHz
 8 "physical id"s (chips)
192 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
  cpu cores     : 12
  siblings      : 24
 physical 0:    cores 0 1 2 3 4 5 8 9 10 11 12 13
 physical 1:    cores 0 1 2 3 4 5 8 9 10 11 12 13
 physical 2:    cores 0 1 2 3 4 5 8 9 10 11 12 13
 physical 3:    cores 0 1 2 3 4 5 8 9 10 11 12 13
 physical 4:    cores 0 1 2 3 4 5 8 9 10 11 12 13
 physical 5:    cores 0 1 2 3 4 5 8 9 10 11 12 13
 physical 6:    cores 0 1 2 3 4 5 8 9 10 11 12 13
 physical 7:    cores 0 1 2 3 4 5 8 9 10 11 12 13
 cache size     : 24576 KB
```

From /proc/meminfo

```
MemTotal:      2117452600 kB
HugePages_Total: 0
Hugepagesize:   2048 kB
```

/usr/bin/lsb\_release -d

```
Red Hat Enterprise Linux Server release 6.5 (Santiago)
```

From /etc/\*release\* /etc/\*version\*

```
redhat-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

uname -a:

```
Linux x3950x6 2.6.32-431.el6.x86_64 #1 SMP Sun Nov 10 22:19:54 EST 2013
x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 May 20 11:52

SPEC is set to: /cpu2006.1.2\_14\_aug2013

```
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/mapper/vg_x3950x6-lv_root ext4  357G  8.3G  331G   3% /
Continued on next page
```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

IBM System x3950 X6  
(Intel Xeon E7-8850 v2, 2.30 GHz)

**SPECfp\_rate2006 = 2430**

**SPECfp\_rate\_base2006 = 2380**

**CPU2006 license:** 11  
**Test sponsor:** IBM Corporation  
**Tested by:** IBM Corporation

**Test date:** May-2014  
**Hardware Availability:** Jun-2014  
**Software Availability:** Nov-2013

## Platform Notes (Continued)

Additional information from dmidecode:  
BIOS IBM -[A8E107JUS-1.00]- 05/02/2014  
Memory:  
64x Hynix HMT42GR7AFR4A-PB 16 GB 1067 MHz 2 rank  
64x NO DIMM Unknown  
64x Samsung M393B2G70QH0-YK0 16 GB 1067 MHz 2 rank

(End of data from sysinfo program)  
Memory speed from dmidecode lists the downclocked speed of the run.

## General Notes

Environment variables set by runspec before the start of the run:  
LD\_LIBRARY\_PATH = "/cpu2006.1.2\_14\_aug2013/libs/32:/cpu2006.1.2\_14\_aug2013/libs/64:/cpu2006.1.2\_14\_aug2013/sh"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB  
memory using RedHat EL 6.4  
Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled  
Filesystem page cache cleared with:  
echo 1> /proc/sys/vm/drop\_caches  
runspec command invoked through numactl i.e.:  
numactl --interleave=all runspec <etc>

## Base Compiler Invocation

C benchmarks:  
icc -m64

C++ benchmarks:  
icpc -m64

Fortran benchmarks:  
ifort -m64

Benchmarks using both Fortran and C:  
icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

IBM System x3950 X6  
(Intel Xeon E7-8850 v2, 2.30 GHz)

**SPECfp\_rate2006 = 2430**

**SPECfp\_rate\_base2006 = 2380**

**CPU2006 license:** 11

**Test sponsor:** IBM Corporation

**Tested by:** IBM Corporation

**Test date:** May-2014

**Hardware Availability:** Jun-2014

**Software Availability:** Nov-2013

## Base Portability Flags (Continued)

```

436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

## Base Optimization Flags

C benchmarks:

```

-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

```

C++ benchmarks:

```

-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

```

Fortran benchmarks:

```

-xAVX -ipo -O3 -no-prec-div -opt-prefetch

```

Benchmarks using both Fortran and C:

```

-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

```

## Peak Compiler Invocation

C benchmarks:

```

icc -m64

```

C++ benchmarks (except as noted below):

```

icpc -m64

```

```

450.soplex: icpc -m32

```

Fortran benchmarks:

```

ifort -m64

```

Benchmarks using both Fortran and C:

```

icc -m64 ifort -m64

```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

IBM System x3950 X6  
(Intel Xeon E7-8850 v2, 2.30 GHz)

**SPECfp\_rate2006 = 2430**

**SPECfp\_rate\_base2006 = 2380**

**CPU2006 license:** 11

**Test sponsor:** IBM Corporation

**Tested by:** IBM Corporation

**Test date:** May-2014

**Hardware Availability:** Jun-2014

**Software Availability:** Nov-2013

## Peak Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

## Peak Optimization Flags

C benchmarks:

```

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -auto-ilp32

```

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: basepeak = yes

```

450.soplex: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -opt-malloc-options=3

```

```

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -unroll4 -ansi-alias

```

Fortran benchmarks:

410.bwaves: basepeak = yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

IBM System x3950 X6  
(Intel Xeon E7-8850 v2, 2.30 GHz)

**SPECfp\_rate2006 = 2430**

**SPECfp\_rate\_base2006 = 2380**

**CPU2006 license:** 11  
**Test sponsor:** IBM Corporation  
**Tested by:** IBM Corporation

**Test date:** May-2014  
**Hardware Availability:** Jun-2014  
**Software Availability:** Nov-2013

## Peak Optimization Flags (Continued)

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: -xAVX -ipo -O3 -no-prec-div -opt-prefetch

459.GemsFDTD: basepeak = yes

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto  
-inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)  
-prof-use(pass 2) -opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: -xAVX -ipo -O3 -no-prec-div -auto-ilp32

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>  
<http://www.spec.org/cpu2006/flags/IBM-Platform-Flags-V1.2-IVB-A.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>  
<http://www.spec.org/cpu2006/flags/IBM-Platform-Flags-V1.2-IVB-A.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Fri Jul 25 00:10:11 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 1 July 2014.