



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation


IBM System x3250 M5  
(Intel Xeon E3-1281 v3, 3.70 GHz)

SPECint®2006 = 64.5

SPECint\_base2006 = 62.5

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Jun-2014  
Hardware Availability: Jul-2014  
Software Availability: Sep-2013



### Hardware

CPU Name: Intel Xeon E3-1281 v3  
 CPU Characteristics: Intel Turbo Boost Technology up to 4.10 GHz  
 CPU MHz: 3700  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 8 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 16 GB (4 x 4 GB 2Rx8 PC3-12800E-11, ECC)  
 Disk Subsystem: 1 x 250 GB SATA, 7200 RPM  
 Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 6.4 (Santiago)  
 2.6.32-358.el6.x86\_64  
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V10.0



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

IBM System x3250 M5  
(Intel Xeon E3-1281 v3, 3.70 GHz)

SPECint2006 = **64.5**

SPECint\_base2006 = **62.5**

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Jun-2014  
Hardware Availability: Jul-2014  
Software Availability: Sep-2013

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	<b><u>213</u></b>	<b><u>45.9</u></b>	213	45.9	213	45.9	<b><u>177</u></b>	<b><u>55.3</u></b>	178	54.9	<b><u>177</u></b>	<b><u>55.2</u></b>
401.bzip2	315	30.7	314	30.7	<b><u>314</u></b>	<b><u>30.7</u></b>	<b><u>311</u></b>	<b><u>31.0</u></b>	312	31.0	311	31.1
403.gcc	<b><u>202</u></b>	<b><u>39.8</u></b>	202	39.8	203	39.7	199	40.4	200	40.3	<b><u>200</u></b>	<b><u>40.3</u></b>
429.mcf	<b><u>116</u></b>	<b><u>78.9</u></b>	117	78.3	115	79.2	116	78.8	<b><u>115</u></b>	<b><u>79.0</u></b>	115	79.0
445.gobmk	324	32.4	<b><u>324</u></b>	<b><u>32.4</u></b>	325	32.3	313	33.6	<b><u>313</u></b>	<b><u>33.5</u></b>	313	33.5
456.hammer	<b><u>114</u></b>	<b><u>82.2</u></b>	114	82.2	115	80.9	123	75.6	<b><u>123</u></b>	<b><u>75.9</u></b>	122	76.5
458.sjeng	<b><u>312</u></b>	<b><u>38.8</u></b>	313	38.7	312	38.8	<b><u>309</u></b>	<b><u>39.1</u></b>	309	39.2	310	39.1
462.libquantum	13.0	1590	<b><u>13.8</u></b>	<b><u>1500</u></b>	13.8	1500	<b><u>13.0</u></b>	<b><u>1590</u></b>	<b><u>13.8</u></b>	<b><u>1500</u></b>	13.8	1500
464.h264ref	355	62.4	<b><u>357</u></b>	<b><u>62.0</u></b>	357	61.9	355	62.4	<b><u>357</u></b>	<b><u>62.0</u></b>	357	61.9
471.omnetpp	<b><u>221</u></b>	<b><u>28.3</u></b>	221	28.2	219	28.5	182	34.3	181	34.6	<b><u>181</u></b>	<b><u>34.5</u></b>
473.astar	184	38.2	183	38.4	<b><u>183</u></b>	<b><u>38.3</u></b>	<b><u>184</u></b>	<b><u>38.2</u></b>	182	38.6	184	38.1
483.xalancbmk	<b><u>89.6</u></b>	<b><u>77.0</u></b>	89.6	77.0	90.4	76.3	<b><u>88.2</u></b>	<b><u>78.3</u></b>	88.0	78.4	88.3	78.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS setting:  
Operating Mode set to Maximum Performance  
Sysinfo program /root/SPECCpu2014jan16/config/sysinfo.rev6818  
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191  
running on localhost.localdomain Mon Jun 23 14:46:27 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo  
model name : Intel(R) Xeon(R) CPU E3-1281 v3 @ 3.70GHz  
1 "physical id"s (chips)  
8 "processors"  
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)  
cpu cores : 4  
siblings : 8

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

**SPECint2006 = 64.5**

IBM System x3250 M5  
(Intel Xeon E3-1281 v3, 3.70 GHz)

**SPECint\_base2006 = 62.5**

**CPU2006 license:** 11  
**Test sponsor:** IBM Corporation  
**Tested by:** IBM Corporation

**Test date:** Jun-2014  
**Hardware Availability:** Jul-2014  
**Software Availability:** Sep-2013

## Platform Notes (Continued)

physical 0: cores 0 1 2 3  
cache size : 8192 KB

From /proc/meminfo  
MemTotal: 16298904 kB  
HugePages\_Total: 0  
Hugepagesize: 2048 kB

/usr/bin/lsb\_release -d  
Red Hat Enterprise Linux Server release 6.4 (Santiago)

From /etc/\*release\* /etc/\*version\*  
redhat-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)  
system-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)  
system-release-cpe: cpe:/o:redhat:enterprise\_linux:6server:ga:server

uname -a:  
Linux localhost.localdomain 2.6.32-358.el6.x86\_64 #1 SMP Tue Jan 29 11:47:41  
EST 2013 x86\_64 x86\_64 x86\_64 GNU/Linux

run-level 3 Jun 23 14:44

SPEC is set to: /root/SPECCpu2014jan16  
Filesystem Type Size Used Avail Use% Mounted on  
/dev/mapper/VolGroup-lv\_root  
ext4 221G 32G 179G 15% /

Additional information from dmidecode:  
BIOS IBM -[JUE113JUS-1.03]- 06/17/2014  
Memory:  
4x Micron 18KSF51272AZ-1G6K1 4 GB 1600 MHz 2 rank

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:  
KMP\_AFFINITY = "granularity=fine,scatter"  
LD\_LIBRARY\_PATH = "/root/SPECCpu2014jan16/libs/32:/root/SPECCpu2014jan16/libs/64:/root/SPECCpu2014jan16/sh"  
OMP\_NUM\_THREADS = "4"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB  
memory using RedHat EL 6.4  
Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled  
runspec command invoked through numactl i.e.:  
numactl --interleave=all runspec <etc>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

IBM System x3250 M5  
(Intel Xeon E3-1281 v3, 3.70 GHz)

**SPECint2006 = 64.5**

**SPECint\_base2006 = 62.5**

**CPU2006 license:** 11  
**Test sponsor:** IBM Corporation  
**Tested by:** IBM Corporation

**Test date:** Jun-2014  
**Hardware Availability:** Jul-2014  
**Software Availability:** Sep-2013

## Base Compiler Invocation

C benchmarks:  
icc -m64

C++ benchmarks:  
icpc -m64

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
403.gcc: -DSPEC\_CPU\_LP64  
429.mcf: -DSPEC\_CPU\_LP64  
445.gobmk: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
471.omnetpp: -DSPEC\_CPU\_LP64  
473.astar: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32

C++ benchmarks:  
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32  
-Wl,-z,muldefs -L/sh -lsmartheap64

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc -m64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

IBM System x3250 M5  
(Intel Xeon E3-1281 v3, 3.70 GHz)

**SPECint2006 = 64.5**

**SPECint\_base2006 = 62.5**

**CPU2006 license:** 11  
**Test sponsor:** IBM Corporation  
**Tested by:** IBM Corporation

**Test date:** Jun-2014  
**Hardware Availability:** Jul-2014  
**Software Availability:** Sep-2013

## Peak Compiler Invocation (Continued)

400.perlbench: `icc -m32`

445.gobmk: `icc -m32`

C++ benchmarks (except as noted below):

`icpc -m32`

473.astar: `icpc -m64`

## Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`  
401.bzip2: `-DSPEC_CPU_LP64`  
403.gcc: `-DSPEC_CPU_LP64`  
429.mcf: `-DSPEC_CPU_LP64`  
456.hmmer: `-DSPEC_CPU_LP64`  
458.sjeng: `-DSPEC_CPU_LP64`  
462.libquantum: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX`  
464.h264ref: `-DSPEC_CPU_LP64`  
473.astar: `-DSPEC_CPU_LP64`  
483.xalancbmk: `-DSPEC_CPU_LINUX`

## Peak Optimization Flags

C benchmarks:

400.perlbench: `-xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -opt-prefetch -ansi-alias`

401.bzip2: `-xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div -prof-use(pass 2) -auto-ilp32 -opt-prefetch -ansi-alias`

403.gcc: `-xCORE-AVX2 -ipo -O3 -no-prec-div -inline-calloc -opt-malloc-options=3 -auto-ilp32`

429.mcf: `-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32`

445.gobmk: `-xCORE-AVX2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -ansi-alias`

456.hmmer: `-xCORE-AVX2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32 -ansi-alias`

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

IBM System x3250 M5  
(Intel Xeon E3-1281 v3, 3.70 GHz)

**SPECint2006 = 64.5**

**SPECint\_base2006 = 62.5**

**CPU2006 license:** 11  
**Test sponsor:** IBM Corporation  
**Tested by:** IBM Corporation

**Test date:** Jun-2014  
**Hardware Availability:** Jul-2014  
**Software Availability:** Sep-2013

## Peak Optimization Flags (Continued)

458.sjeng: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll4

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-ra-region-strategy=block -ansi-alias  
-Wl,-z,muldefs -L/sh -lsmartheap

473.astar: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch  
-auto-p32 -Wl,-z,muldefs -L/sh -lsmartheap64

483.xalancbmk: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch  
-ansi-alias -Wl,-z,muldefs -L/sh -lsmartheap

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>  
<http://www.spec.org/cpu2006/flags/IBM-Platform-Flags-V1.2-HSW-A.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>  
<http://www.spec.org/cpu2006/flags/IBM-Platform-Flags-V1.2-HSW-A.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Fri Jul 25 00:34:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 15 July 2014.