



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp[®]2006 = **48.3**

Intel DQ87PG motherboard (Intel Pentium G3420)

SPECfp_base2006 = **47.6**

CPU2006 license: 13


Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Sep-2012



Hardware

CPU Name: Intel Pentium G3420
 CPU Characteristics:
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Microsoft Windows 7 Enterprise 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 13.1.1.171 of Intel C++ Studio XE for Windows;
 Fortran: Version 13.1.1.171 of Intel Fortran Studio XE for Windows;
 Libraries: Version 15.00.30729.01 of Microsoft Visual Studio 2008 Professional SP1
 Auto Parallel: Yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = **48.3**

Intel DQ87PG motherboard (Intel Pentium G3420)

SPECfp_base2006 = **47.6**

CPU2006 license: 13

Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Sep-2012

L3 Cache: 3 MB I+D on chip per chip
 Other Cache: None
 Memory: 4 GB (2 x 2 GB 1Rx8 PC3-12800U-11)
 Disk Subsystem: 250 GB Seagate SATA HDD, 7200 RPM
 Other Hardware: None

File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 10.0 from <http://www.microquill.com/>

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>151</u>	<u>89.8</u>	151	90.0	154	88.5	<u>151</u>	<u>89.8</u>	151	90.0	154	88.5
416.gamess	622	31.5	618	31.7	<u>618</u>	<u>31.7</u>	<u>598</u>	<u>32.7</u>	596	32.8	599	32.7
433.milc	150	61.2	<u>150</u>	<u>61.2</u>	150	61.2	150	61.2	<u>150</u>	<u>61.2</u>	150	61.2
434.zeusmp	<u>135</u>	<u>67.6</u>	135	67.6	134	67.9	<u>135</u>	<u>67.6</u>	135	67.6	134	67.9
435.gromacs	216	33.0	<u>216</u>	<u>33.0</u>	217	32.9	216	33.0	<u>216</u>	<u>33.0</u>	217	32.9
436.cactusADM	158	75.6	163	73.4	<u>161</u>	<u>74.2</u>	158	75.6	163	73.4	<u>161</u>	<u>74.2</u>
437.leslie3d	179	52.5	179	52.6	<u>179</u>	<u>52.5</u>	179	52.5	179	52.6	<u>179</u>	<u>52.5</u>
444.namd	375	21.4	<u>375</u>	<u>21.4</u>	375	21.4	375	21.4	<u>375</u>	<u>21.4</u>	375	21.4
447.dealII	207	55.3	<u>207</u>	<u>55.3</u>	207	55.3	207	55.3	<u>207</u>	<u>55.3</u>	207	55.3
450.soplex	246	33.9	<u>243</u>	<u>34.3</u>	241	34.7	246	33.9	<u>243</u>	<u>34.3</u>	241	34.7
453.povray	115	46.1	<u>115</u>	<u>46.1</u>	115	46.1	<u>99.1</u>	<u>53.7</u>	101	52.9	98.4	54.1
454.calculix	<u>248</u>	<u>33.2</u>	252	32.8	248	33.3	<u>248</u>	<u>33.2</u>	252	32.8	248	33.3
459.GemsFDTD	<u>249</u>	<u>42.6</u>	249	42.7	249	42.6	<u>249</u>	<u>42.6</u>	249	42.7	249	42.6
465.tonto	308	31.9	<u>308</u>	<u>32.0</u>	308	32.0	289	34.1	287	34.3	<u>287</u>	<u>34.2</u>
470.lbm	151	91.2	150	91.7	<u>150</u>	<u>91.6</u>	151	91.2	150	91.7	<u>150</u>	<u>91.6</u>
481.wrf	<u>168</u>	<u>66.3</u>	168	66.4	169	66.1	<u>168</u>	<u>66.3</u>	168	66.4	169	66.1
482.sphinx3	<u>463</u>	<u>42.1</u>	464	42.0	463	42.1	<u>463</u>	<u>42.1</u>	464	42.0	463	42.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 13.0 was set up to generate 64-bit binaries with the command:
 "ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

Platform Notes

Sysinfo program C:\SPEC13.1\Docs\sysinfo
 \$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
 running on Clt7C05070FB2EF Mon Sep 23 06:31:52 2013

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 48.3

Intel DQ87PG motherboard (Intel Pentium G3420)

SPECfp_base2006 = 47.6

CPU2006 license: 13

Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Sep-2012

Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'

```

OS Name       : Microsoft Windows 7 Enterprise
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: INTEL_
System Model   : DQ87PG__
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 60 Stepping 3 GenuineIntel ~3200 Mhz
BIOS Version  : Intel(R) Corp. PGQ8710H.86A.0036.2013.0702.1908, 7/2/2013
Total Physical Memory: 3,749 MB

```

Trying 'wmic cpu get /value'

```

DeviceID      : CPU0
L2CacheSize   : 512
L3CacheSize   : 3072
MaxClockSpeed : 3200
Name          : Intel(R) Pentium(R) CPU G3420 @ 3.20GHz
NumberOfCores : 2
NumberOfLogicalProcessors: 2

```

(End of data from sysinfo program)

BIOS: SATA mode set to RAID

Windows Disk Driver: Intel Rapid Storage Technology 12.5.0.1066

Windows Chipset Driver: Intel Chipset Driver 9.4.0.1027

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
Micron MT8JTF25664AZ-1G6 Series Memory DIMMs

General Notes

OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 48.3

Intel DQ87PG motherboard (Intel Pentium G3420)

SPECfp_base2006 = 47.6

CPU2006 license: 13

Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Sep-2012

Base Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc10 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: /Qlowercase

436.cactusADM: -Qlowercase /assume:underscore

444.namd: /TP

447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG

-Qoption,cpp,--ms_incompat_treatment_of_commas_in_macros

453.povray: -DSPEC_CPU_NEED_INVHYP -DNEED_INVHYP

454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase

481.wrf: -DSPEC_CPU_WINDOWS_ICL

Base Optimization Flags

C benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias

-Qopt-prefetch /F1000000000

C++ benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias

-Qopt-prefetch -Qcxx-features /F1000000000 shlw32M.lib

-link /FORCE:MULTIPLE

Fortran benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias

-Qopt-prefetch /F1000000000

Benchmarks using both Fortran and C:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias

-Qopt-prefetch /F1000000000

Peak Compiler Invocation

C benchmarks:

icl -Qvc10 -Qstd=c99

C++ benchmarks:

icl -Qvc10

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 4



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 48.3

Intel DQ87PG motherboard (Intel Pentium G3420)

SPECfp_base2006 = 47.6

CPU2006 license: 13

Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Sep-2012

Peak Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc10 -Qstd=c99 ifort

Peak Portability Flags

410.bwaves: /Qlowercase

436.cactusADM: -Qlowercase /assume:underscore

444.namd: /TP

447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG

-Qoption,cpp,--ms_incompat_treatment_of_commas_in_macros

453.povray: -DSPEC_CPU_NEED_INVHYP -DNEED_INVHYP

454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase

481.wrf: -DSPEC_CPU_WINDOWS_ICL

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)

-Qipo -O3 -Qprec-div- -Oa /F1000000000 shlw32M.lib

-link /FORCE:MULTIPLE

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)

-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias /F1000000000

shlw32M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: basepeak = yes

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 5



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 48.3

Intel DQ87PG motherboard (Intel Pentium G3420)

SPECfp_base2006 = 47.6

CPU2006 license: 13

Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Sep-2012

Peak Optimization Flags (Continued)

416.gamess: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias
-Qscalar-rep- /F1000000000

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc
/F1000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Jul 25 00:53:28 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 July 2014.