



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint®2006 = 52.8

Intel DQ87PG motherboard (Intel Core i3-4340)

SPECint_base2006 = 51.1

CPU2006 license: 13


Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013



Hardware

CPU Name: Intel Core i3-4340
 CPU Characteristics: 3600
 CPU MHz: Integrated
 FPU: 2 cores, 1 chip, 2 cores/chip, 2 threads/core
 CPU(s) enabled: 1 chip
 CPU(s) orderable: 32 KB I + 32 KB D on chip per core
 Primary Cache: 256 KB I+D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: 4 GB (2 x 2 GB 1Rx8 PC3-12800U-11)
 Memory: 250 GB Seagate SATA HDD, 7200 RPM
 Disk Subsystem: None
 Other Hardware:

Software

Operating System: Microsoft Windows 7 Enterprise 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 13.1.1.171 of Intel C++ Studio XE for Windows;
 Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 10.0 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 52.8

Intel DQ87PG motherboard (Intel Core i3-4340)

SPECint_base2006 = 51.1

CPU2006 license: 13

Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	270	36.1	<u>271</u>	<u>36.1</u>	272	36.0	227	43.0	223	43.8	<u>224</u>	<u>43.7</u>
401.bzip2	388	24.9	<u>364</u>	<u>26.5</u>	364	26.5	357	27.0	<u>357</u>	<u>27.0</u>	357	27.0
403.gcc	266	30.3	266	30.3	<u>266</u>	<u>30.3</u>	250	32.2	<u>250</u>	<u>32.2</u>	250	32.2
429.mcf	130	70.3	129	70.6	<u>129</u>	<u>70.5</u>	130	70.3	129	70.6	<u>129</u>	<u>70.5</u>
445.gobmk	<u>362</u>	<u>29.0</u>	361	29.0	362	29.0	344	30.5	343	30.6	<u>344</u>	<u>30.5</u>
456.hmmer	134	69.5	<u>134</u>	<u>69.5</u>	135	69.4	134	69.5	<u>134</u>	<u>69.5</u>	135	69.4
458.sjeng	367	33.0	<u>367</u>	<u>33.0</u>	367	33.0	367	33.0	<u>367</u>	<u>33.0</u>	367	33.0
462.libquantum	23.2	893	23.7	874	<u>23.3</u>	<u>889</u>	23.2	893	23.7	874	<u>23.3</u>	<u>889</u>
464.h264ref	330	67.0	330	67.1	<u>330</u>	<u>67.0</u>	330	67.0	330	67.1	<u>330</u>	<u>67.0</u>
471.omnetpp	<u>259</u>	<u>24.2</u>	257	24.3	259	24.1	<u>236</u>	<u>26.4</u>	236	26.5	237	26.4
473.astar	<u>233</u>	<u>30.2</u>	233	30.2	231	30.4	<u>233</u>	<u>30.2</u>	233	30.2	231	30.4
483.xalancbmk	128	53.8	<u>130</u>	<u>53.2</u>	130	53.0	128	53.8	<u>130</u>	<u>53.2</u>	130	53.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 13.1 was set up to generate 64-bit binaries with the command:
 "ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

Platform Notes

Sysinfo program C:\SPEC13.1\Docs\sysinfo
 \$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
 running on Clt7C05070FB2B7 Thu Sep 19 15:33:56 2013

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name       : Microsoft Windows 7 Enterprise
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: INTEL_
System Model   : DQ87PG__
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 60 Stepping 3 GenuineIntel ~3600 Mhz
BIOS Version  : Intel(R) Corp. PGQ8710H.86A.0036.2013.0702.1908, 7/2/2013
Total Physical Memory: 3,749 MB
```

```
Trying 'wmic cpu get /value'
DeviceID      : CPU0
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 52.8

Intel DQ87PG motherboard (Intel Core i3-4340)

SPECint_base2006 = 51.1

CPU2006 license: 13

Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Platform Notes (Continued)

```

L2CacheSize      : 512
L3CacheSize      : 4096
MaxClockSpeed    : 3600
Name              : Intel(R) Core(TM) i3-4340 CPU @ 3.60GHz
NumberOfCores    : 2
NumberOfLogicalProcessors: 4

```

(End of data from sysinfo program)

BIOS: SATA mode set to RAID

Windows Disk Driver: Intel Rapid Storage Technology 12.5.0.1066

Windows Chipset Driver: Intel Chipset Driver 9.4.0.1027

Component Notes

Tested systems can be used with Shin-G ATX case,
 PC Power and Cooling 1200W power supply
 Micron MT8JTF25664AZ-1G6 Series Memory DIMMs

General Notes

OMP_NUM_THREADS set to number of processors cores
 KMP_AFFINITY set to granularity=fine,scatter
 Binaries compiled on a system with 1x Intel Core i7-860 CPU
 + 8GB memory using Windows 7 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Base Portability Flags

```

400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
               -DSPEC_CPU_NO_NEED_VA_COPY
401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
429.mcf: -DSPEC_CPU_P64
445.gobmk: -DSPEC_CPU_P64
456.hmmer: -DSPEC_CPU_P64
458.sjeng: -DSPEC_CPU_P64
462.libquantum: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES

```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 52.8

Intel DQ87PG motherboard (Intel Core i3-4340)

SPECint_base2006 = 51.1

CPU2006 license: 13

Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Base Portability Flags (Continued)

471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
473.astar: -DSPEC_CPU_P64
483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword

Base Optimization Flags

C benchmarks:
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel
-Qauto-ilp32 /F512000000
C++ benchmarks:
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
-Qauto-ilp32 /F512000000 shlw64M.lib -link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:
icl -Qvc10 -Qstd=c99
C++ benchmarks:
icl -Qvc10

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:
400.perlbench: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F512000000 shlw64M.lib
-link /FORCE:MULTIPLE

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 52.8

Intel DQ87PG motherboard (Intel Core i3-4340)

SPECint_base2006 = 51.1

CPU2006 license: 13

Test date: Sep-2013

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Peak Optimization Flags (Continued)

401.bzip2: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias
-Qauto-ilp32 /F512000000

403.gcc: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F512000000

429.mcf: basepeak = yes

445.gobmk: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32
/F512000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000
shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.xml>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 52.8

Intel DQ87PG motherboard (Intel Core i3-4340)

SPECint_base2006 = 51.1

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2013

Hardware Availability: Sep-2013

Software Availability: Apr-2013

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Jul 25 00:56:47 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 July 2014.