



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

SPECfp<sup>®</sup>2006 = **53.5**

### Express5800/GT110g (Intel Pentium G3240)

SPECfp\_base2006 = **52.8**

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Aug-2014

Hardware Availability: Jul-2014

Software Availability: Jan-2014



#### Hardware

CPU Name: Intel Pentium G3240  
 CPU Characteristics:  
 CPU MHz: 3100  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

#### Software

Operating System: Red Hat Enterprise Linux Server release 6.5 (Santiago)  
 Kernel 2.6.32-431.el6.x86\_64  
 Compiler: C/C++: Version 14.0.2.144 of Intel C++ Studio XE for Linux;  
 Fortran: Version 14.0.2.144 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

SPECfp2006 = **53.5**

### Express5800/GT110g (Intel Pentium G3240)

SPECfp\_base2006 = **52.8**

CPU2006 license: 9006

Test date: Aug-2014

Test sponsor: NEC Corporation

Hardware Availability: Jul-2014

Tested by: NEC Corporation

Software Availability: Jan-2014

L3 Cache: 3 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 16 GB (2 x 8 GB 2Rx8 PC3-12800E-11, ECC, running at 1333 MHz and CL9)  
 Disk Subsystem: 1 x 500 GB SATA, 7200 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	153	88.9	<b>153</b>	<b>89.0</b>	152	89.4	153	88.9	<b>153</b>	<b>89.0</b>	152	89.4
416.gamess	<b>538</b>	<b>36.4</b>	539	36.3	537	36.4	<b>515</b>	<b>38.0</b>	515	38.0	514	38.1
433.milc	<b>129</b>	<b>71.4</b>	129	71.4	128	71.4	<b>129</b>	<b>71.4</b>	129	71.4	128	71.4
434.zeusmp	<b>124</b>	<b>73.2</b>	124	73.2	124	73.4	<b>124</b>	<b>73.2</b>	124	73.2	124	73.4
435.gromacs	195	36.6	197	36.2	<b>195</b>	<b>36.6</b>	195	36.6	197	36.2	<b>195</b>	<b>36.6</b>
436.cactusADM	149	80.0	157	76.2	<b>155</b>	<b>77.1</b>	149	80.0	157	76.2	<b>155</b>	<b>77.1</b>
437.leslie3d	<b>161</b>	<b>58.3</b>	161	58.3	161	58.4	<b>161</b>	<b>58.3</b>	161	58.3	161	58.4
444.namd	<b>357</b>	<b>22.5</b>	357	22.5	357	22.5	347	23.1	346	23.1	<b>347</b>	<b>23.1</b>
447.dealII	<b>197</b>	<b>58.1</b>	196	58.4	197	58.1	<b>197</b>	<b>58.1</b>	196	58.4	197	58.1
450.soplex	233	35.8	229	36.4	<b>232</b>	<b>35.9</b>	233	35.8	229	36.4	<b>232</b>	<b>35.9</b>
453.povray	105	50.8	105	50.9	<b>105</b>	<b>50.9</b>	94.8	56.1	96.5	55.1	<b>96.1</b>	<b>55.4</b>
454.calculix	<b>177</b>	<b>46.7</b>	177	46.7	177	46.6	<b>177</b>	<b>46.7</b>	177	46.7	177	46.6
459.GemsFDTD	219	48.4	220	48.2	<b>220</b>	<b>48.2</b>	219	48.4	220	48.2	<b>220</b>	<b>48.2</b>
465.tonto	<b>249</b>	<b>39.6</b>	249	39.6	249	39.6	240	41.0	<b>240</b>	<b>41.0</b>	240	40.9
470.lbm	134	103	134	102	<b>134</b>	<b>103</b>	134	103	134	102	<b>134</b>	<b>103</b>
481.wrf	159	70.2	159	70.2	<b>159</b>	<b>70.2</b>	159	70.2	159	70.2	<b>159</b>	<b>70.2</b>
482.sphinx3	429	45.5	422	46.2	<b>423</b>	<b>46.0</b>	410	47.5	419	46.5	<b>412</b>	<b>47.3</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS Settings:  
Energy Performance: Performance

## General Notes

Environment variables set by runspec before the start of the run:  
 KMP\_AFFINITY = "granularity=fine,compact,1,0"  
 LD\_LIBRARY\_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"  
 OMP\_NUM\_THREADS = "2"

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 53.5

Express5800/GT110g (Intel Pentium G3240)

SPECfp\_base2006 = 52.8

CPU2006 license: 9006

Test date: Aug-2014

Test sponsor: NEC Corporation

Hardware Availability: Jul-2014

Tested by: NEC Corporation

Software Availability: Jan-2014

## General Notes (Continued)

Added glibc-static-2.12-1.132.el6.x86\_64  
to enable static linking  
Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.deallI: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 53.5

Express5800/GT110g (Intel Pentium G3240)

SPECfp\_base2006 = 52.8

CPU2006 license: 9006

Test date: Aug-2014

Test sponsor: NEC Corporation

Hardware Availability: Jul-2014

Tested by: NEC Corporation

Software Availability: Jan-2014

## Base Optimization Flags (Continued)

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias  
-parallel

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

**SPECfp2006 = 53.5**

**Express5800/GT110g (Intel Pentium G3240)**

**SPECfp\_base2006 = 52.8**

**CPU2006 license:** 9006

**Test date:** Aug-2014

**Test sponsor:** NEC Corporation

**Hardware Availability:** Jul-2014

**Tested by:** NEC Corporation

**Software Availability:** Jan-2014

## Peak Optimization Flags (Continued)

447.dealll: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4

### Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>  
<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-R120-RevB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>  
<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-R120-RevB.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 53.5

Express5800/GT110g (Intel Pentium G3240)

SPECfp\_base2006 = 52.8

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Aug-2014

Hardware Availability: Jul-2014

Software Availability: Jan-2014

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Wed Oct 8 19:40:04 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 8 October 2014.