



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R920 (Intel Xeon E7-4809 v2, 1.90 GHz)

**SPECfp®\_rate2006 = 600**

**SPECfp\_rate\_base2006 = 588**

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Aug-2014

Hardware Availability: Mar-2014

Software Availability: May-2014



**SPECfp\_rate\_base2006 = 588**

**SPECfp\_rate2006 = 600**

## Hardware

CPU Name: Intel Xeon E7-4809 v2  
CPU Characteristics:  
CPU MHz:  
FPU:  
CPU(s) enabled: 24 cores, 4 chips, 6 cores/chip, 2 threads/core  
CPU(s) orderable: 2,4 chip  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

## Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64) 3.0.76-0.11-default  
Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;  
Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux  
Auto Parallel: No  
File System: ext2  
System State: Run level 3 (multi-user)

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R920 (Intel Xeon E7-4809  
v2, 1.90 GHz)

**SPECfp\_rate2006 = 600**

**SPECfp\_rate\_base2006 = 588**

CPU2006 license: 55

Test date: Aug-2014

Test sponsor: Dell Inc.

Hardware Availability: Mar-2014

Tested by: Dell Inc.

Software Availability: May-2014

L3 Cache:	12 MB I+D on chip per chip
Other Cache:	None
Memory:	1 TB (64 x 16 GB 2Rx4 PC3-12800R-11, ECC, running at 1066 MHz)
Disk Subsystem:	1 x 400 GB SAS SSD SSD
Other Hardware:	None

Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	48	<b>1002</b>	<b>651</b>	1002	651	1003	650	48	<b>1002</b>	<b>651</b>	1002	651	1003	650
416.gamess	48	<b>1857</b>	<b>506</b>	1856	506	1859	505	48	<b>1850</b>	<b>508</b>	1899	495	1828	514
433.milc	48	651	677	654	673	<b>653</b>	<b>675</b>	48	652	676	653	675	<b>652</b>	<b>675</b>
434.zeusmp	48	684	638	<b>688</b>	<b>635</b>	689	634	48	684	638	<b>688</b>	<b>635</b>	689	634
435.gromacs	48	<b>571</b>	<b>600</b>	567	604	573	598	48	566	605	<b>562</b>	<b>610</b>	559	613
436.cactusADM	48	877	654	<b>882</b>	<b>650</b>	900	638	48	877	654	<b>882</b>	<b>650</b>	900	638
437.leslie3d	48	<b>1060</b>	<b>426</b>	1057	427	1062	425	24	464	486	464	486	<b>464</b>	<b>486</b>
444.namd	48	<b>972</b>	<b>396</b>	971	396	991	388	48	958	402	982	392	<b>959</b>	<b>402</b>
447.dealII	48	<b>619</b>	<b>886</b>	623	881	617	890	48	<b>619</b>	<b>886</b>	623	881	617	890
450.soplex	48	<b>953</b>	<b>420</b>	958	418	953	420	48	<b>953</b>	<b>420</b>	958	418	953	420
453.povray	48	368	693	<b>366</b>	<b>697</b>	366	698	48	322	793	320	798	<b>320</b>	<b>797</b>
454.calculix	48	<b>537</b>	<b>737</b>	537	738	538	737	48	<b>537</b>	<b>737</b>	537	738	538	737
459.GemsFDTD	48	<b>1293</b>	<b>394</b>	1294	393	1293	394	48	<b>1293</b>	<b>394</b>	1294	393	1293	394
465.tonto	48	808	585	<b>807</b>	<b>585</b>	803	588	48	<b>768</b>	<b>615</b>	766	617	768	615
470.lbm	48	1020	647	<b>1020</b>	<b>647</b>	1017	649	48	1020	647	<b>1020</b>	<b>647</b>	1017	649
481.wrf	48	727	737	701	765	<b>702</b>	<b>764</b>	48	693	774	694	773	<b>693</b>	<b>774</b>
482.sphinx3	48	1586	590	1592	588	<b>1589</b>	<b>589</b>	48	1586	590	1592	588	<b>1589</b>	<b>589</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS settings:

Virtualization Technology disabled

Execute Disable disabled

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R920 (Intel Xeon E7-4809 v2, 1.90 GHz)

**SPECfp\_rate2006 = 600**

**SPECfp\_rate\_base2006 = 588**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Aug-2014

**Hardware Availability:** Mar-2014

**Software Availability:** May-2014

## Platform Notes (Continued)

System Profile set to Custom

CPU Power Management set to Maximum Performance

C1E set to disabled

C States set to disabled

Memory Patrol Scrub set to disabled

Sysinfo program

/root/Desktop/Performance/ic14.0\_Oct17\_2013/config/sysinfo.rev6818

\$Rev: 6818 \$ \$Date::: 2012-07-17 #\\$ e86d102572650a6e4d596a3cee98f191

running on slesperf3 Sat Aug 30 14:39:50 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E7-4809 v2 @ 1.90GHz  
 4 "physical id"s (chips)  
 48 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 6  
 siblings : 12  
 physical 0: cores 0 1 2 3 4 5  
 physical 1: cores 0 1 2 3 4 5  
 physical 2: cores 0 1 2 3 4 5  
 physical 3: cores 0 1 2 3 4 5

cache size : 12288 KB

From /proc/meminfo

MemTotal: 1058789108 kB  
HugePages\_Total: 0  
Hugepagesize: 2048 kB

/usr/bin/lsb\_release -d

SUSE Linux Enterprise Server 11 (x86\_64)

From /etc/\*release\* /etc/\*version\*

SuSE-release:  
 SUSE Linux Enterprise Server 11 (x86\_64)  
VERSION = 11  
PATCHLEVEL = 3

uname -a:

Linux slesperf3 3.0.76-0.11-default #1 SMP Fri Jun 14 08:21:43 UTC 2013  
(ccab990) x86\_64 x86\_64 x86\_64 GNU/Linux

run-level 3 Aug 30 07:32 last=S

SPEC is set to: /root/Desktop/Performance/ic14.0\_Oct17\_2013

Filesystem Type Size Used Avail Use% Mounted on  
/dev/sda2 ext2 365G 247G 117G 68% /

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R920 (Intel Xeon E7-4809  
v2, 1.90 GHz)

**SPECfp\_rate2006 = 600**

**SPECfp\_rate\_base2006 = 588**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Aug-2014

**Hardware Availability:** Mar-2014

**Software Availability:** May-2014

## Platform Notes (Continued)

Additional information from dmidecode:

BIOS Dell Inc. 1.2.2 05/05/2014

Memory:

64x 00CE00B300CE M393B2G70BH0-YK0 16 GB 1066 MHz

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:

```
LD_LIBRARY_PATH = "/root/Desktop/Performance/icl4.0_Oct17_2013/libs/32:/root/Desktop/Performance/icl4.0_Oct17_2013/libs/64:/root/Desktop/Performance/icl4.0_Oct17_2013/sh"
```

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

```
echo always > /sys/kernel/mm/transparent_hugepage/enabled
```

Filesystem page cache cleared with:

```
echo 1> /proc/sys/vm/drop_caches
```

runspec command invoked through numactl i.e.:

```
numactl --interleave=all runspec <etc>
```

## Base Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R920 (Intel Xeon E7-4809  
v2, 1.90 GHz)

**SPECfp\_rate2006 = 600**

**SPECfp\_rate\_base2006 = 588**

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Aug-2014

Hardware Availability: Mar-2014

Software Availability: May-2014

## Base Portability Flags (Continued)

```
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3
```

C++ benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3
```

Fortran benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -opt-prefetch
```

Benchmarks using both Fortran and C:

```
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3
```

## Peak Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R920 (Intel Xeon E7-4809  
v2, 1.90 GHz)

**SPECfp\_rate2006 = 600**

**SPECfp\_rate\_base2006 = 588**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Aug-2014

**Hardware Availability:** Mar-2014

**Software Availability:** May-2014

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
           -prof-use(pass 2) -auto-ilp32
```

```
470.lbm: basepeak = yes
```

```
482.sphinx3: basepeak = yes
```

C++ benchmarks:

```
444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
           -prof-use(pass 2) -fno-alias -auto-ilp32
```

```
447.dealII: basepeak = yes
```

```
450.soplex: basepeak = yes
```

```
453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
            -prof-use(pass 2) -unroll14 -ansi-alias
```

Fortran benchmarks:

```
410.bwaves: basepeak = yes
```

```
416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
             -no-prec-div(pass 2) -prof-use(pass 2) -unroll12
             -inline-level=0 -scalar-rep-
```

```
434.zeusmp: basepeak = yes
```

```
437.leslie3d: -xAVX -ipo -O3 -no-prec-div -opt-prefetch
```

```
459.GemsFDTD: basepeak = yes
```

```
465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -auto
            -inline-calloc -opt-malloc-options=3
```

Benchmarks using both Fortran and C:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R920 (Intel Xeon E7-4809  
v2, 1.90 GHz)

**SPECfp\_rate2006 = 600**

**SPECfp\_rate\_base2006 = 588**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Aug-2014

**Hardware Availability:** Mar-2014

**Software Availability:** May-2014

## Peak Optimization Flags (Continued)

435.gromacs: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)  
-prof-use(pass 2) -opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: -xAVX -ipo -O3 -no-prec-div -auto-ilp32

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.html>

<http://www.spec.org/cpu2006/flags/Dell-Platform-Settings-V1.2-revD.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.xml>

<http://www.spec.org/cpu2006/flags/Dell-Platform-Settings-V1.2-revD.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Wed Oct 8 19:40:41 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 8 October 2014.