



# SPEC® CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9  
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECint®2006 =

SPECint\_base2006

Test date: Nov-2014  
Hardware Availability: Sep-2014  
Software Availability: Sep-2014

CPU2006 license: 3  
Test sponsor: Hewlett-Packard Company  
Tested by: Hewlett-Packard Company

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

- 400.perlbench
- 401.bzip2
- 403.gcc
- 429.mcf
- 445.gobmk
- 456.hmmer
- 458.sjeng
- 462.libquantum
- 464.h264ref
- 471.omnettp
- 473.astar
- 483

**Non-Compliant**

### Hardware

CPU Name: Intel Xeon E5-2643 v3  
CPU Characteristics: Intel Turbo Boost Technology up to 3.70 GHz  
CPU MHz: 3400  
FPU: Integrated  
CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server release 7.0 (Maipo)  
Kernel 3.10.0-123.el7.x86\_64  
Compiler: C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux  
Auto Parallel: Yes  
File System: ext4  
System State: Run level 3 (multi-user)

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9  
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECint2006 =

SPECint\_base2006

CPU2006 license: 3  
Test sponsor: Hewlett-Packard Company  
Tested by: Hewlett-Packard Company

Test date: Nov-2014  
Hardware Availability: Sep-2014  
Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

Secondary Cache: 256 KB I+D on chip per core  
L3 Cache: 20 MB I+D on chip per chip  
Other Cache: None  
Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2133P-R)  
Disk Subsystem: 1 x 400 GB SAS SSD, RAID 0  
Other Hardware: None

Base Processors: 32/64-bit  
Link Pointers: 32/64-bit  
Other Software: Microquill SmartHeap V10.0

## Result Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
401.bzip2	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
403.gcc	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
429.mcf	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
445.gobmk	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
456.hammer	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
458.sjeng	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
462.libquantum	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
464.h264ref	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
471.omnetpp	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
473.astar	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
483.xs	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"  
Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/transparent\_hugepage/enabled



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint2006 = **NC**

ProLiant BL460c Gen9  
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECint\_base2006 = **NC**

CPU2006 license: 3

Test date: Nov-2014

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2014

Tested by: Hewlett-Packard Company

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

## Platform Notes

### BIOS Configuration:

```

HP Power Profile set to Custom
HP Power Regulator to HP Static High Performance Mode
Minimum Processor Idle Power Core State set to C6 State
Minimum Processor Idle Power Package State set to No Package State
QPI Snoop Configuration set to Early Snoop
Thermal Configuration set to Maximum Cooling
Collaborative Power Control set to Disabled
Processor Power and Utilization Monitoring set to Disabled
Memory Double Refresh Rate set to 1x Refresh
Intel Hyperthreading Optimiz set to Disabled
Sysinfo program /cpu2006/config/sysinfo.rev6914
$Rev: 6914 $ $Date:: 2014-06-25 #$ e3fbb8667b5a285932ceab81e28219e1
running on A-BL460cGen9-VP Thu Nov 6 09:12:08 2014

```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```

From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E5-2643 v3 @ 3.40GHz
 2 "physical id"s (chips)
 2 "processor"s
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution)
cpu cores : 6
siblings : 6
physical 0: cores 0 1 2 3 4 5
physical 1: cores 0 1 2 3 4 5
cache size : 20480 KB

```

```

From /proc/meminfo
MemTotal:      263846716 kB
HugePages_Total:      0
Hugepagesize:    2048 kB

```

```

From /etc/*release* /etc/*version*
os-release:

```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9  
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECint2006 =

SPECint\_base2006

Test date: Nov-2014  
Hardware Availability: Sep-2014  
Software Availability: Sep-2014

CPU2006 license: 3  
Test sponsor: Hewlett-Packard Company  
Tested by: Hewlett-Packard Company

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

## Platform Notes (Continued)

```

NAME="Red Hat Enterprise Linux Server"
VERSION="7.0 (Maipo)"
ID="rhel"
ID_LIKE="fedora"
VERSION_ID="7.0"
PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
ANSI_COLOR="0;31"
CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server

uname -a:
Linux A-BL460cGen9-VP2 7.0.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57 EDT
2014 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Nov 6 08:23

SPEC is set to: /cpu2006
Filesystem            Type      Size  Used Avail Use% Mounted on
/dev/mapper/rhel-root  ext4     310G  116G  179G   40% /

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program
reads system data which is "intended to allow hardware to be accurately
determined", but the intent may not be met, as there are frequent changes to
hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS HP I36 08/26/2014
Memory:
16x 17 752369-081 16 GB 2 rank 2133 MHz

(End of data from sysinfo program)

```



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint2006 = **NC**

ProLiant BL460c Gen9  
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECint\_base2006 = **NC**

CPU2006 license: 3

Test date: Nov-2014

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2014

Tested by: Hewlett-Packard Company

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

## General Notes

Environment variables set by runspec before the start of the run:  
KMP\_AFFINITY = "granularity=fine,scatter" **NON-COMPLIANT**  
LD\_LIBRARY\_PATH = "/cpu2006/libs/32:/cpu2006/lib/64:/cpu2006/sh"  
OMP\_NUM\_THREADS = "12"

Binaries compiled on a system with 1x Intel Xeon E5-4670K CPU + 16GB memory using RedHat EL 7.0

## Base Compiler Invocation

C benchmarks:  
icc -m64

C++ benchmarks:  
icpc -m64

## Base Portability Flags

400.perlbenc: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
403.gcc: -DSPEC\_CPU\_LP64  
429.tcf: -DSPEC\_CPU\_LP64  
445.gobmk: -DSPEC\_CPU\_LP64  
450.mimicr: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
471.o.netpp: -DSPEC\_CPU\_LP64  
473.astar: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint2006 = **NC**

ProLiant BL460c Gen9  
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECint\_base2006 = **NC**

CPU2006 license: 3

Test date: Nov-2014

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2014

Tested by: Hewlett-Packard Company

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

## Base Optimization Flags

C benchmarks:

`-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32`

C++ benchmarks:

`-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32  
-Wl,-z,muldefs -L/sh -lmartheap64`

## Base Other Flags

C benchmarks:

`403.gcc: -Dalloca=_alloca`

## Peak Compiler Invocation

C benchmarks (except as noted below):

`icc -m64`

`400.perlbench: icc -m32 -L/opt/intel/composer_xe_2015/lib/ia32`

`445.gobmk: icc -m32 -L/opt/intel/composer_xe_2015/lib/ia32`

C++ benchmarks (except as noted below):

`icpc -m64`

`471.cnetpp: icpc -m32 -L/opt/intel/composer_xe_2015/lib/ia32`

## Peak Portability Flags

`400.perlbench: -DSPEC_CPU_LINUX_IA32`

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9  
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECint2006 =

SPECint\_base2006

Test date: Nov-2014  
Hardware Availability: Sep-2014  
Software Availability: Sep-2014

CPU2006 license: 3  
Test sponsor: Hewlett-Packard Company  
Tested by: Hewlett-Packard Company

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

## Peak Portability Flags (Continued)

401.bzip2: -DSPEC\_CPU\_LP64  
403.gcc: -DSPEC\_CPU\_LP64  
429.mcf: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
473.astar: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-prefetch -ansi-alias  
401.bzip2: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div -prof-use(pass 2) -auto-ilp32  
-opt-prefetch -ansi-alias  
403.gcc: -xCORE-AVX2 -ipo -O3 -no-prec-div -inline-calloc  
-opt-malloc-options=3 -auto-ilp32  
429.mcf: -xCORE-AVX2 -ipo -O3 -no-prec-div -parallel  
-opt-prefetch -auto-p32  
445.gobmk: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias  
456.hmmer: basepeak = yes  
458.sjeng: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll4

Continued on next page





# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9  
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECint2006 =

SPECint\_base2006

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

## Peak Optimization Flags (Continued)

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-ra-region-iterations=block -ansi-alias  
-WL,-z,muldefs -L/sh -lsmarheap

473.astar: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch  
-auto- -WL,-z,muldefs -L/sh -lsmarheap64

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.xml>





# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9  
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECint2006 =

SPECint\_base2006

Test date: Nov-2014  
Hardware Availability: Sep-2014  
Software Availability: Sep-2014

CPU2006 license: 3  
Test sponsor: Hewlett-Packard Company  
Tested by: Hewlett-Packard Company

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

**Non-Compliant**

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue Nov 3 17:12:02 2015 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 2 December 2014.