



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Huawei

**SPECfp<sup>®</sup>2006 = 81.8**

Huawei XH622 V3 (Intel Xeon E5-2650L v3)

**SPECfp\_base2006 = 77.7**

CPU2006 license: 3175


Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2015

Hardware Availability: Sep-2014

Software Availability: Sep-2014



### Hardware

CPU Name: Intel Xeon E5-2650L v3  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.50 GHz  
 CPU MHz: 1800  
 FPU: Integrated  
 CPU(s) enabled: 24 cores, 2 chips, 12 cores/chip  
 CPU(s) orderable: 1,2 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server release 7.0 (Maipo)  
 3.10.0-123.el7.x86\_64  
 Compiler: C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux;  
 Fortran: Version 15.0.0.090 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Huawei

SPECfp2006 = **81.8**

Huawei XH622 V3 (Intel Xeon E5-2650L v3)

SPECfp\_base2006 = **77.7**

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2015

Hardware Availability: Sep-2014

Software Availability: Sep-2014

L3 Cache: 30 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2133P-R)  
 Disk Subsystem: 1 x 500 GB SATA, 7200 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

| Benchmark     | Base               |                    |                    |                    |                    |                    | Peak               |                    |                    |                    |                    |                    |
|---------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
|               | Seconds            | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              |
| 410.bwaves    | 36.0               | 377                | <b><u>35.5</u></b> | <b><u>382</u></b>  | 35.3               | 385                | 36.0               | 377                | <b><u>35.5</u></b> | <b><u>382</u></b>  | 35.3               | 385                |
| 416.gamess    | 740                | 26.5               | <b><u>740</u></b>  | <b><u>26.5</u></b> | 740                | 26.5               | <b><u>655</u></b>  | <b><u>29.9</u></b> | 652                | 30.0               | 657                | 29.8               |
| 433.milc      | <b><u>167</u></b>  | <b><u>55.0</u></b> | 167                | 55.1               | 167                | 55.0               | 165                | 55.6               | 165                | 55.5               | <b><u>165</u></b>  | <b><u>55.6</u></b> |
| 434.zeusmp    | <b><u>61.9</u></b> | <b><u>147</u></b>  | 61.8               | 147                | 62.1               | 147                | <b><u>61.9</u></b> | <b><u>147</u></b>  | 61.8               | 147                | 62.1               | 147                |
| 435.gromacs   | 252                | 28.3               | <b><u>252</u></b>  | <b><u>28.3</u></b> | 253                | 28.2               | 252                | 28.3               | <b><u>252</u></b>  | <b><u>28.3</u></b> | 253                | 28.2               |
| 436.cactusADM | 21.4               | 557                | 21.3               | 562                | <b><u>21.4</u></b> | <b><u>558</u></b>  | 21.4               | 557                | 21.3               | 562                | <b><u>21.4</u></b> | <b><u>558</u></b>  |
| 437.leslie3d  | <b><u>35.1</u></b> | <b><u>267</u></b>  | 35.1               | 268                | 35.2               | 267                | <b><u>35.1</u></b> | <b><u>267</u></b>  | 35.1               | 268                | 35.2               | 267                |
| 444.namd      | <b><u>380</u></b>  | <b><u>21.1</u></b> | 380                | 21.1               | 380                | 21.1               | 370                | 21.7               | 369                | 21.7               | <b><u>370</u></b>  | <b><u>21.7</u></b> |
| 447.dealII    | <b><u>279</u></b>  | <b><u>41.0</u></b> | 279                | 41.0               | 279                | 41.0               | <b><u>279</u></b>  | <b><u>41.0</u></b> | 279                | 41.0               | 279                | 41.0               |
| 450.soplex    | <b><u>238</u></b>  | <b><u>35.1</u></b> | 241                | 34.6               | 238                | 35.1               | <b><u>238</u></b>  | <b><u>35.1</u></b> | 241                | 34.6               | 238                | 35.1               |
| 453.povray    | 136                | 39.1               | 139                | 38.2               | <b><u>136</u></b>  | <b><u>39.0</u></b> | <b><u>122</u></b>  | <b><u>43.7</u></b> | 123                | 43.3               | 122                | 43.8               |
| 454.calculix  | <b><u>211</u></b>  | <b><u>39.1</u></b> | 211                | 39.1               | 211                | 39.1               | 195                | 42.3               | <b><u>195</u></b>  | <b><u>42.2</u></b> | 195                | 42.2               |
| 459.GemsFDTD  | <b><u>63.9</u></b> | <b><u>166</u></b>  | 63.4               | 167                | 64.8               | 164                | 53.7               | 198                | <b><u>53.6</u></b> | <b><u>198</u></b>  | 53.5               | 198                |
| 465.tonto     | 375                | 26.2               | <b><u>375</u></b>  | <b><u>26.2</u></b> | 373                | 26.4               | <b><u>267</u></b>  | <b><u>36.8</u></b> | 267                | 36.8               | 267                | 36.8               |
| 470.lbm       | 24.9               | 551                | 24.2               | 567                | <b><u>24.3</u></b> | <b><u>566</u></b>  | 24.9               | 551                | 24.2               | 567                | <b><u>24.3</u></b> | <b><u>566</u></b>  |
| 481.wrf       | 152                | 73.3               | <b><u>152</u></b>  | <b><u>73.5</u></b> | 152                | 73.6               | 152                | 73.3               | <b><u>152</u></b>  | <b><u>73.5</u></b> | 152                | 73.6               |
| 482.sphinx3   | 408                | 47.8               | 411                | 47.4               | <b><u>409</u></b>  | <b><u>47.7</u></b> | 408                | 47.8               | 411                | 47.4               | <b><u>409</u></b>  | <b><u>47.7</u></b> |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS configuration:  
 Set Power Efficiency Mode to Custom  
 Set Snoop Mode to HS mode  
 Set Intel Hyper-threading Technology to Disable  
 Sysinfo program /spec15/config/sysinfo.rev6914  
 \$Rev: 6914 \$ \$Date:: 2014-06-25 #\$ e3fbb8667b5a285932ceab81e28219e1  
 running on localhost.localdomain Wed Mar 18 14:59:27 2015

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = 81.8

Huawei XH622 V3 (Intel Xeon E5-2650L v3)

SPECfp\_base2006 = 77.7

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2015

Hardware Availability: Sep-2014

Software Availability: Sep-2014

## Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E5-2650L v3 @ 1.80GHz

2 "physical id"s (chips)

24 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 12

siblings : 12

physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13

physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13

cache size : 30720 KB

From /proc/meminfo

MemTotal: 263720560 kB

HugePages\_Total: 0

Hugepagesize: 2048 kB

From /etc/\*release\* /etc/\*version\*

os-release:

NAME="Red Hat Enterprise Linux Server"

VERSION="7.0 (Maipo)"

ID="rhel"

ID\_LIKE="fedora"

VERSION\_ID="7.0"

PRETTY\_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"

ANSI\_COLOR="0;31"

CPE\_NAME="cpe:/o:redhat:enterprise\_linux:7.0:GA:server"

redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)

system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)

system-release-cpe: cpe:/o:redhat:enterprise\_linux:7.0:ga:server

uname -a:

Linux localhost.localdomain 3.10.0-123.el7.x86\_64 #1 SMP Mon May 5 11:16:57

EDT 2014 x86\_64 x86\_64 x86\_64 GNU/Linux

run-level 3 Mar 18 14:58

SPEC is set to: /spec15

Filesystem Type Size Used Avail Use% Mounted on

/dev/sdal ext4 443G 165G 256G 40% /

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Insyde Corp. 1.17 09/03/2014

Memory:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = 81.8

Huawei XH622 V3 (Intel Xeon E5-2650L v3)

SPECfp\_base2006 = 77.7

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2015

Hardware Availability: Sep-2014

Software Availability: Sep-2014

## Platform Notes (Continued)

8x Micron 36ASF2G72PZ-2G1A2 16 GB 1 rank 2133 MHz  
8x Micron 36ASF2G72PZ-2G1A2 16 GB 2 rank 2133 MHz

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact,1,0"  
LD\_LIBRARY\_PATH = "/spec15/libs/32:/spec15/libs/64:/spec15/sh"  
OMP\_NUM\_THREADS = "24"

Binaries compiled on a system with 1x Core i5-4670K CPU + 16GB memory using RedHat EL 7.0

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/transparent\_hugepage/enabled  
runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>  
The Huawei XH622 V3 and Huawei XH628 V3

are electronically equivalent.

The results have been measured on a Huawei XH628 V3 model.

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = 81.8

Huawei XH622 V3 (Intel Xeon E5-2650L v3)

SPECfp\_base2006 = 77.7

CPU2006 license: 3175

Test date: Mar-2015

Test sponsor: Huawei

Hardware Availability: Sep-2014

Tested by: Huawei

Software Availability: Sep-2014

## Base Portability Flags (Continued)

```

447.deallI: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

## Base Optimization Flags

```

C benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

C++ benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

```

## Peak Compiler Invocation

```

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

```

## Peak Portability Flags

Same as Base Portability Flags



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = 81.8

Huawei XH622 V3 (Intel Xeon E5-2650L v3)

SPECfp\_base2006 = 77.7

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2015

Hardware Availability: Sep-2014

Software Availability: Sep-2014

## Peak Optimization Flags

### C benchmarks:

433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32 -ansi-alias

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

### C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-inline-calloc -opt-malloc-options=3 -auto -unroll4

### Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = 81.8

Huawei XH622 V3 (Intel Xeon E5-2650L v3)

SPECfp\_base2006 = 77.7

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2015

Hardware Availability: Sep-2014

Software Availability: Sep-2014

## Peak Optimization Flags (Continued)

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-HASWELL-V1.4.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-HASWELL-V1.4.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Tue Apr 21 18:20:12 2015 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 21 April 2015.