



SPEC® CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp®2006 = 95.1

Express5800/R120f-1E (Intel Xeon E5-2630L v3)

SPECfp_base2006 = 89.2

CPU2006 license: 9006


Test date: Apr-2015

Test sponsor: NEC Corporation

Hardware Availability: Jan-2015

Tested by: NEC Corporation

Software Availability: Jul-2014



Hardware

CPU Name: Intel Xeon E5-2630L v3
CPU Characteristics: Intel Turbo Boost Technology up to 2.90 GHz
CPU MHz: 1800
FPU: Integrated
CPU(s) enabled: 16 cores, 2 chips, 8 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: Red Hat Enterprise Linux Server release 6.5 (Santiago)
Compiler: Kernel 2.6.32-431.20.3.el6.x86_64
Auto Parallel: C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux;
File System: Fortran: Version 15.0.0.090 of Intel Fortran Studio XE for Linux
Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R120f-1E (Intel Xeon E5-2630L v3)

SPECfp2006 = 95.1

CPU2006 license: 9006

Test date: Apr-2015

Hardware Availability: Jan-2015

Software Availability: Jul-2014

Test sponsor: NEC Corporation

Tested by: NEC Corporation

L3 Cache: 20 MB I+D on chip per chip
 Other Cache: None
 Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2133P-R,
 running at 1866 MHz)
 Disk Subsystem: 1 x 250 GB SATA, 7200 RPM
 Other Hardware: None

System State: Run level 3 (multi-user)
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	34.5	394	34.3	396	<u>34.4</u>	<u>395</u>	34.5	394	34.3	396	<u>34.4</u>	<u>395</u>
416.gamess	708	27.6	<u>708</u>	<u>27.7</u>	706	27.7	<u>527</u>	<u>37.1</u>	<u>526</u>	<u>37.2</u>	<u>526</u>	<u>37.2</u>
433.milc	146	62.8	141	65.3	<u>141</u>	<u>65.2</u>	146	62.8	141	65.3	<u>141</u>	<u>65.2</u>
434.zeusmp	52.7	173	<u>52.9</u>	<u>172</u>	53.1	171	<u>52.7</u>	<u>173</u>	<u>52.9</u>	<u>172</u>	53.1	171
435.gromacs	223	32.0	<u>217</u>	<u>32.9</u>	217	32.9	<u>223</u>	<u>32.0</u>	<u>217</u>	<u>32.9</u>	217	32.9
436.cactusADM	21.8	548	<u>20.5</u>	<u>582</u>	20.3	588	21.8	548	<u>20.5</u>	<u>582</u>	20.3	588
437.leslie3d	<u>36.4</u>	<u>258</u>	36.7	256	35.6	264	<u>36.4</u>	<u>258</u>	36.7	256	35.6	264
444.namd	329	24.4	328	24.4	<u>328</u>	<u>24.4</u>	<u>319</u>	<u>25.1</u>	320	25.1	319	25.1
447.dealII	241	47.6	237	48.2	<u>238</u>	<u>48.1</u>	241	47.6	237	48.2	<u>238</u>	<u>48.1</u>
450.soplex	220	37.8	211	39.6	<u>214</u>	<u>38.9</u>	220	37.8	211	39.6	<u>214</u>	<u>38.9</u>
453.povray	107	49.5	<u>107</u>	<u>49.7</u>	107	49.8	<u>95.9</u>	<u>55.5</u>	94.1	56.6	96.3	55.2
454.calculix	179	46.1	179	46.0	<u>179</u>	<u>46.0</u>	157	52.4	157	52.5	<u>157</u>	<u>52.5</u>
459.GemsFDTD	<u>51.4</u>	<u>207</u>	50.8	209	51.5	206	<u>45.3</u>	234	45.5	233	<u>45.3</u>	<u>234</u>
465.tonto	<u>316</u>	<u>31.1</u>	317	31.1	313	31.4	<u>210</u>	47.0	209	47.1	<u>209</u>	<u>47.0</u>
470.lbm	22.2	618	<u>22.5</u>	<u>610</u>	22.6	609	<u>22.2</u>	618	<u>22.5</u>	<u>610</u>	22.6	609
481.wrf	116	96.4	118	94.8	<u>116</u>	<u>96.1</u>	<u>116</u>	<u>96.4</u>	118	94.8	<u>116</u>	<u>96.1</u>
482.sphinx3	328	59.4	330	59.1	<u>328</u>	<u>59.4</u>	<u>328</u>	<u>59.4</u>	330	59.1	<u>328</u>	<u>59.4</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

BIOS Settings:

Power Management Policy: Custom
 Energy Performance: Performance
 Patrol Scrub: Disabled
 Early Snoop: Disabled
 Hyper-Threading: Disabled



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R120f-1E (Intel Xeon E5-2630L v3)

SPECfp2006 = 95.1

CPU2006 license: 9006

Test date: Apr-2015

Test sponsor: NEC Corporation

Hardware Availability: Jan-2015

Tested by: NEC Corporation

Software Availability: Jul-2014

General Notes

Environment variables set by runspec before the start of the run:

KMP_AFFINITY = "granularity=fine,compact"

LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"

OMP_NUM_THREADS = "16"

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled

Base Compiler Invocation

C benchmarks:

 icc -m64

C++ benchmarks:

 icpc -m64

Fortran benchmarks:

 ifort -m64

Benchmarks using both Fortran and C:

 icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

 -xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
 -ansi-alias

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R120f-1E (Intel Xeon E5-2630L v3)

SPECfp2006 = 95.1

CPU2006 license: 9006

Test date: Apr-2015

Test sponsor: NEC Corporation

Hardware Availability: Jan-2015

Tested by: NEC Corporation

Software Availability: Jul-2014

Base Optimization Flags (Continued)

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-fno-alias -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R120f-1E (Intel Xeon E5-2630L v3)

SPECfp2006 = 95.1

CPU2006 license: 9006

Test date: Apr-2015

Test sponsor: NEC Corporation

Hardware Availability: Jan-2015

Tested by: NEC Corporation

Software Availability: Jul-2014

Peak Optimization Flags (Continued)

447.deallII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll14
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll12
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll12
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-inline-calloc -opt-malloc-options=3 -auto -unroll14

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml>



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R120f-1E (Intel Xeon E5-2630L v3)

SPECfp2006 = 95.1

SPECfp_base2006 = 89.2

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Apr-2015

Hardware Availability: Jan-2015

Software Availability: Jul-2014

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Tue May 19 18:12:35 2015 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 May 2015.