



# SPEC® CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp®2006 = **108**

PRIMERGY RX2530 M1, Intel Xeon E5-2637 v3, 3.5 GHz

SPECfp\_base2006 = **105**

CPU2006 license: 19


Test date: Mar-2015

Test sponsor: Fujitsu

Hardware Availability: Feb-2015

Tested by: Fujitsu

Software Availability: Sep-2014



### Hardware

CPU Name: Intel Xeon E5-2637 v3  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.70 GHz  
 CPU MHz: 3500  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server release 7.0 (Maipo)  
 Kernel 3.10.0-123.8.1.el7.x86\_64  
 Compiler: C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux;  
 Fortran: Version 15.0.0.090 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: xfs

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp2006 = **108**

PRIMERGY RX2530 M1, Intel Xeon E5-2637 v3, 3.5 GHz

SPECfp\_base2006 = **105**

CPU2006 license: 19

Test date: Mar-2015

Test sponsor: Fujitsu

Hardware Availability: Feb-2015

Tested by: Fujitsu

Software Availability: Sep-2014

L3 Cache: 15 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2133P-R)  
 Disk Subsystem: 1 x SATA, 500 GB, 7200 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	29.6	459	<u>29.7</u>	<u>458</u>	29.7	457	29.6	459	<u>29.7</u>	<u>458</u>	29.7	457
416.gamess	<u>465</u>	<u>42.1</u>	467	41.9	464	42.2	424	46.2	<u>423</u>	<u>46.3</u>	423	46.3
433.milc	118	77.7	<u>118</u>	<u>77.6</u>	119	77.4	117	78.2	<u>117</u>	<u>78.2</u>	117	78.4
434.zeusmp	<u>50.1</u>	<u>182</u>	50.0	182	50.4	180	<u>50.1</u>	<u>182</u>	50.0	182	50.4	180
435.gromacs	<u>139</u>	<u>51.5</u>	139	51.4	139	51.5	<u>139</u>	<u>51.5</u>	139	51.4	139	51.5
436.cactusADM	<u>22.3</u>	<u>535</u>	22.2	538	22.3	535	<u>22.3</u>	<u>535</u>	22.2	538	22.3	535
437.leslie3d	<u>36.0</u>	<u>261</u>	35.9	262	36.1	260	<u>36.0</u>	<u>261</u>	35.9	262	36.1	260
444.namd	<u>257</u>	<u>31.2</u>	257	31.2	257	31.2	<u>250</u>	<u>32.1</u>	250	32.0	250	32.1
447.dealII	188	60.9	191	59.9	<u>188</u>	<u>60.7</u>	188	60.9	191	59.9	<u>188</u>	<u>60.7</u>
450.soplex	191	43.8	192	43.4	<u>192</u>	<u>43.5</u>	191	43.8	192	43.4	<u>192</u>	<u>43.5</u>
453.povray	<u>87.3</u>	<u>60.9</u>	87.5	60.8	87.1	61.0	<u>77.3</u>	<u>68.8</u>	77.3	68.8	77.2	68.9
454.calculix	<u>139</u>	<u>59.2</u>	140	59.1	139	59.3	<u>133</u>	<u>62.2</u>	133	62.1	132	62.4
459.GemsFDTD	57.6	184	59.0	180	<u>58.5</u>	<u>182</u>	<u>51.6</u>	<u>206</u>	51.5	206	52.1	204
465.tonto	<u>208</u>	<u>47.3</u>	208	47.3	208	47.4	174	56.5	174	56.6	<u>174</u>	<u>56.6</u>
470.lbm	<u>28.5</u>	<u>481</u>	29.7	463	28.4	483	<u>28.5</u>	<u>481</u>	29.7	463	28.4	483
481.wrf	109	102	<u>108</u>	<u>103</u>	107	104	109	102	<u>108</u>	<u>103</u>	107	104
482.sphinx3	227	85.9	<u>226</u>	<u>86.2</u>	226	86.4	223	87.4	226	86.3	<u>225</u>	<u>86.7</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS configuration:  
 Energy Performance = Performance  
 Utilization Profile = Unbalanced  
 QPI snoop mode: Home Snoop  
 COD Enable = Disabled, Early Snoop = Disabled  
 CPU ClE Support = Disabled



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 108**

PRIMERGY RX2530 M1, Intel Xeon E5-2637 v3, 3.5 GHz

**SPECfp\_base2006 = 105**

**CPU2006 license:** 19

**Test date:** Mar-2015

**Test sponsor:** Fujitsu

**Hardware Availability:** Feb-2015

**Tested by:** Fujitsu

**Software Availability:** Sep-2014

## General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact,1,0"

LD\_LIBRARY\_PATH = "/home/SPECcpu2006/libs/32:/home/SPECcpu2006/libs/64:/home/SPECcpu2006/sh"

OMP\_NUM\_THREADS = "8"

Binaries compiled on a system with 1x Core i5-4670K CPU + 16GB memory using RedHat EL 7.0

For information about Fujitsu please visit: <http://www.fujitsu.com>

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 450.soplex: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
 482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 108**

PRIMERGY RX2530 M1, Intel Xeon E5-2637 v3, 3.5 GHz

**SPECfp\_base2006 = 105**

**CPU2006 license:** 19

**Test date:** Mar-2015

**Test sponsor:** Fujitsu

**Hardware Availability:** Feb-2015

**Tested by:** Fujitsu

**Software Availability:** Sep-2014

## Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch  
-ansi-alias

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch  
-ansi-alias

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32 -ansi-alias

470.lbm: basepeak = yes

482.sphinx3: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias  
-parallel

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 108**

PRIMERGY RX2530 M1, Intel Xeon E5-2637 v3, 3.5 GHz

**SPECfp\_base2006 = 105**

**CPU2006 license:** 19

**Test sponsor:** Fujitsu

**Tested by:** Fujitsu

**Test date:** Mar-2015

**Hardware Availability:** Feb-2015

**Software Availability:** Sep-2014

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4  
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-inline-calloc -opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform-Settings-V1.2-HSW-RevA.html>



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Fujitsu

**SPECfp2006 = 108**

PRIMERGY RX2530 M1, Intel Xeon E5-2637 v3, 3.5 GHz

**SPECfp\_base2006 = 105**

**CPU2006 license:** 19

**Test sponsor:** Fujitsu

**Tested by:** Fujitsu

**Test date:** Mar-2015

**Hardware Availability:** Feb-2015

**Software Availability:** Sep-2014

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform-Settings-V1.2-HSW-RevA.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue May 19 18:13:27 2015 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 19 May 2015.