



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Lenovo Group Limited

SPECfp<sup>®</sup>2006 = **99.8**

Lenovo ThinkServer TS150  
(3.50 GHz, Intel Xeon E3-1240 v5)

SPECfp\_base2006 = **97.7**

CPU2006 license: 9017


Test date: Jan-2016

Test sponsor: Lenovo Group Limited

Hardware Availability: Oct-2015

Tested by: Lenovo Group Limited

Software Availability: Aug-2015



### Hardware

CPU Name: Intel Xeon E3-1240 v5  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.90 GHz  
 CPU MHz: 3500  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 12 (x86\_64)  
 Kernel 3.12.28-4-default  
 Compiler: C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux;  
 Fortran: Version 16.0.0.101 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: xfs  
 System State: Run level 3 (multi-user)

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Lenovo Group Limited

SPECfp2006 = **99.8**

Lenovo ThinkServer TS150  
(3.50 GHz, Intel Xeon E3-1240 v5)

SPECfp\_base2006 = **97.7**

CPU2006 license: 9017

Test date: Jan-2016

Test sponsor: Lenovo Group Limited

Hardware Availability: Oct-2015

Tested by: Lenovo Group Limited

Software Availability: Aug-2015

L3 Cache: 8 MB I+D on chip per chip  
Other Cache: None  
Memory: 32 GB (4 x 8 GB 2Rx8 PC4-2133P-U)  
Disk Subsystem: 1 x 800 GB SATA SSD  
Other Hardware: None

Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	95.8	142	<u>95.7</u>	<u>142</u>	95.5	142	95.8	142	<u>95.7</u>	<u>142</u>	95.5	142
416.gamess	389	50.3	389	50.4	<u>389</u>	<u>50.4</u>	352	55.6	352	55.6	<u>352</u>	<u>55.6</u>
433.milc	81.0	113	80.6	114	<u>80.9</u>	<u>113</u>	81.0	113	80.6	114	<u>80.9</u>	<u>113</u>
434.zeusmp	43.2	211	<u>43.2</u>	<u>210</u>	43.4	210	43.2	211	<u>43.2</u>	<u>210</u>	43.4	210
435.gromacs	105	68.3	<u>104</u>	<u>68.5</u>	104	68.7	105	68.3	<u>104</u>	<u>68.5</u>	104	68.7
436.cactusADM	33.5	356	<u>32.6</u>	<u>366</u>	32.3	369	33.5	356	<u>32.6</u>	<u>366</u>	32.3	369
437.leslie3d	86.4	109	86.6	109	<u>86.5</u>	<u>109</u>	86.4	109	86.6	109	<u>86.5</u>	<u>109</u>
444.namd	214	37.5	<u>214</u>	<u>37.5</u>	214	37.5	<u>210</u>	<u>38.2</u>	210	38.2	210	38.2
447.dealII	139	82.1	140	81.8	<u>140</u>	<u>82.0</u>	139	82.1	140	81.8	<u>140</u>	<u>82.0</u>
450.soplex	145	57.4	146	57.0	<u>146</u>	<u>57.2</u>	145	57.4	146	57.0	<u>146</u>	<u>57.2</u>
453.povray	73.8	72.1	<u>73.4</u>	<u>72.5</u>	71.6	74.3	67.2	79.2	<u>65.0</u>	<u>81.9</u>	62.9	84.6
454.calculix	<u>105</u>	<u>78.5</u>	105	78.4	105	78.6	103	79.8	<u>104</u>	<u>79.3</u>	104	79.2
459.GemsFDTD	127	83.8	<u>127</u>	<u>83.8</u>	127	83.8	<u>125</u>	<u>84.8</u>	125	84.8	125	84.8
465.tonto	<u>147</u>	<u>67.1</u>	147	67.0	147	67.1	133	73.7	<u>133</u>	<u>73.9</u>	133	73.9
470.lbm	72.8	189	<u>72.8</u>	<u>189</u>	72.9	188	72.8	189	<u>72.8</u>	<u>189</u>	72.9	188
481.wrf	85.9	130	<u>86.0</u>	<u>130</u>	86.1	130	85.9	130	<u>86.0</u>	<u>130</u>	86.1	130
482.sphinx3	<u>187</u>	<u>104</u>	188	104	186	105	<u>187</u>	<u>104</u>	188	104	186	105

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

### BIOS Configuration:

EIST Support set to Enabled  
Intel (R) Hyper-Threading set to Disabled  
C1E Support set to Enabled  
C State Support set to Enabled  
Turbo Mode set to Enable  
Sysinfo program /home/cpu2006-1.2-ic16.0/config/sysinfo.rev6914  
\$Rev: 6914 \$ \$Date:: 2014-06-25 #\$ e3fbb8667b5a285932ceab81e28219e1  
running on TS150 Mon Jan 11 09:07:45 2016

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Lenovo Group Limited

SPECfp2006 = 99.8

Lenovo ThinkServer TS150  
(3.50 GHz, Intel Xeon E3-1240 v5)

SPECfp\_base2006 = 97.7

CPU2006 license: 9017

Test date: Jan-2016

Test sponsor: Lenovo Group Limited

Hardware Availability: Oct-2015

Tested by: Lenovo Group Limited

Software Availability: Aug-2015

### Platform Notes (Continued)

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```

From /proc/cpuinfo
model name      : Intel(R) Xeon(R) CPU E3-1240 v5 @ 3.50GHz
 1 "physical id"s (chips)
 4 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores    : 4
  siblings     : 4
  physical 0   : cores 0 1 2 3
cache size    : 8192 KB

```

```

From /proc/meminfo
MemTotal:      32933324 kB
HugePages_Total: 0
Hugepagesize:  2048 kB

```

```

From /etc/*release* /etc/*version*
SuSE-release:
SUSE Linux Enterprise Server 12 (x86_64)
VERSION = 12
PATCHLEVEL = 0
# This file is deprecated and will be removed in a future service pack or
release.
# Please check /etc/os-release for details about this release.
os-release:
NAME="SLES"
VERSION="12"
VERSION_ID="12"
PRETTY_NAME="SUSE Linux Enterprise Server 12"
ID="sles"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:12"

```

```

uname -a:
Linux TS150 3.12.28-4-default #1 SMP Thu Sep 25 17:02:34 UTC 2014 (9879bd4)
x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Jan 11 03:55

```

SPEC is set to: /home/cpu2006-1.2-ic16.0
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda3       xfs   693G  27G  667G   4% /home

```

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Lenovo Group Limited

**SPECfp2006 = 99.8**

Lenovo ThinkServer TS150  
(3.50 GHz, Intel Xeon E3-1240 v5)

**SPECfp\_base2006 = 97.7**

**CPU2006 license:** 9017

**Test date:** Jan-2016

**Test sponsor:** Lenovo Group Limited

**Hardware Availability:** Oct-2015

**Tested by:** Lenovo Group Limited

**Software Availability:** Aug-2015

## Platform Notes (Continued)

hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS LENOVO FWKT32A 12/25/2015

Memory:

4x Samsung M378A1G43DB0-CPB 8 GB 2 rank 2133 MHz

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact,1,0"

LD\_LIBRARY\_PATH = "/home/cpu2006-1.2-ic16.0/libs/32:/home/cpu2006-1.2-ic16.0/libs/64:/home/cpu2006-1.2-ic16.0/sh"

OMP\_NUM\_THREADS = "4"

Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB memory using RedHat EL 7.1

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/transparent\_hugepage/enabled

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64

416.gamess: -DSPEC\_CPU\_LP64

433.milc: -DSPEC\_CPU\_LP64

434.zeusmp: -DSPEC\_CPU\_LP64

435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main

436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main

437.leslie3d: -DSPEC\_CPU\_LP64

444.namd: -DSPEC\_CPU\_LP64

447.dealII: -DSPEC\_CPU\_LP64

450.soplex: -DSPEC\_CPU\_LP64

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 4



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

**Lenovo Group Limited**

**SPECfp2006 = 99.8**

Lenovo ThinkServer TS150  
(3.50 GHz, Intel Xeon E3-1240 v5)

**SPECfp\_base2006 = 97.7**

**CPU2006 license:** 9017

**Test date:** Jan-2016

**Test sponsor:** Lenovo Group Limited

**Hardware Availability:** Oct-2015

**Tested by:** Lenovo Group Limited

**Software Availability:** Aug-2015

## Base Portability Flags (Continued)

```

453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

## Base Optimization Flags

```

C benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

C++ benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

```

## Peak Compiler Invocation

```

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

```

## Peak Portability Flags

Same as Base Portability Flags



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Lenovo Group Limited

**SPECfp2006 = 99.8**

Lenovo ThinkServer TS150  
(3.50 GHz, Intel Xeon E3-1240 v5)

**SPECfp\_base2006 = 97.7**

**CPU2006 license:** 9017

**Test date:** Jan-2016

**Test sponsor:** Lenovo Group Limited

**Hardware Availability:** Oct-2015

**Tested by:** Lenovo Group Limited

**Software Availability:** Aug-2015

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll4  
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

**Lenovo Group Limited**

**SPECfp2006 = 99.8**

Lenovo ThinkServer TS150  
(3.50 GHz, Intel Xeon E3-1240 v5)

**SPECfp\_base2006 = 97.7**

**CPU2006 license:** 9017

**Test date:** Jan-2016

**Test sponsor:** Lenovo Group Limited

**Hardware Availability:** Oct-2015

**Tested by:** Lenovo Group Limited

**Software Availability:** Aug-2015

## Peak Optimization Flags (Continued)

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Default-Platform-Flags.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Default-Platform-Flags.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Tue Feb 9 17:21:49 2016 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 9 February 2016.

Standard Performance Evaluation Corporation

[info@spec.org](mailto:info@spec.org)

<http://www.spec.org/>