



SPEC® CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp®2006 = 109

HPC S2600WF (Intel Xeon Silver 4114, 2.20 GHz)

SPECfp_base2006 = 105

CPU2006 license: 4204


Test date: Sep-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017



Hardware

CPU Name: Intel Xeon Silver 4114
 CPU Characteristics: Intel Turbo Boost Technology up to 3.00 GHz
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip
 CPU(s) orderable: 1,2 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 12 SP2 4.4.21-69-default
 Compiler: C/C++: Version 17.0.4.196 of Intel C/C++ Compiler for Linux;
 Fortran: Version 17.0.4.196 of Intel Fortran Compiler for Linux
 Auto Parallel: Yes
 File System: xfs
 System State: Run level 3

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp2006 = 109

HPC S2600WF (Intel Xeon Silver 4114, 2.20 GHz)

SPECfp_base2006 = 105

CPU2006 license: 4204

Test date: Sep-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017

L3 Cache: 13.75 MB I+D on chip per chip
Other Cache: None
Memory: 768 GB (24 x 32 GB 2Rx8 PC4-2666V-R, running at 2400 MT/s)
Disk Subsystem: 1 x 1600 GB SATA SSD
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	25.2	539	24.6	553	<u>25.1</u>	<u>541</u>	25.2	539	24.6	553	<u>25.1</u>	<u>541</u>
416.gamess	<u>496</u>	<u>39.5</u>	496	39.5	497	39.4	<u>456</u>	<u>43.0</u>	456	43.0	456	43.0
433.milc	<u>137</u>	<u>66.8</u>	135	68.1	138	66.5	<u>137</u>	<u>66.8</u>	135	68.1	138	66.5
434.zeusmp	43.0	212	<u>43.1</u>	<u>211</u>	43.3	210	43.0	212	<u>43.1</u>	<u>211</u>	43.3	210
435.gromacs	<u>167</u>	<u>42.8</u>	166	42.9	170	41.9	<u>167</u>	<u>42.8</u>	166	42.9	170	41.9
436.cactusADM	15.9	752	<u>16.0</u>	<u>747</u>	16.0	746	15.9	752	<u>16.0</u>	<u>747</u>	16.0	746
437.leslie3d	<u>27.3</u>	<u>345</u>	27.3	345	26.6	354	<u>27.3</u>	<u>345</u>	27.3	345	26.6	354
444.namd	<u>278</u>	<u>28.9</u>	278	28.9	278	28.9	271	29.5	<u>272</u>	<u>29.5</u>	272	29.5
447.dealII	195	58.8	<u>195</u>	<u>58.8</u>	195	58.6	195	58.8	<u>195</u>	<u>58.8</u>	195	58.6
450.soplex	209	39.9	<u>208</u>	<u>40.0</u>	208	40.1	209	39.9	<u>208</u>	<u>40.0</u>	208	40.1
453.povray	<u>94.4</u>	<u>56.3</u>	94.7	56.2	94.3	56.4	83.2	63.9	83.5	63.7	<u>83.4</u>	<u>63.8</u>
454.calculix	<u>139</u>	<u>59.3</u>	139	59.3	140	59.0	133	62.0	134	61.8	<u>133</u>	<u>62.0</u>
459.GemsFDTD	48.7	218	50.0	212	<u>50.0</u>	<u>212</u>	<u>43.8</u>	<u>242</u>	43.5	244	44.7	237
465.tonto	<u>237</u>	<u>41.5</u>	238	41.3	237	41.5	183	53.9	<u>183</u>	<u>53.8</u>	183	53.8
470.lbm	18.3	753	<u>18.5</u>	<u>742</u>	18.6	740	18.3	753	<u>18.5</u>	<u>742</u>	18.6	740
481.wrf	149	75.1	<u>149</u>	<u>75.2</u>	148	75.3	149	75.1	<u>149</u>	<u>75.2</u>	148	75.3
482.sphinx3	319	61.2	315	61.9	<u>317</u>	<u>61.4</u>	319	61.2	315	61.9	<u>317</u>	<u>61.4</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

BIOS settings:
Intel(R) Hyper-Threading Tech=Disabled
Patrol Scrub=Disabled
CPU and Power Performance Policy=Performance
Set Fan Profile=Performance
Sysinfo program /spec/config/sysinfo.rev6993
Revision 6993 of 2015-11-06 (300de342723409e6453f54e8c50448c3)
running on kvasir Sat Sep 2 20:48:31 2017

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp2006 = 109

HPC S2600WF (Intel Xeon Silver 4114, 2.20 GHz)

SPECfp_base2006 = 105

CPU2006 license: 4204

Test date: Sep-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017

Platform Notes (Continued)

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```

From /proc/cpuinfo
model name : Intel(R) Xeon(R) Silver 4114 CPU @ 2.20GHz
 2 "physical id"s (chips)
 20 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 10
  siblings  : 10
  physical 0: cores 0 1 2 3 4 8 9 10 11 12
  physical 1: cores 0 1 2 3 4 8 9 10 11 12
cache size : 14080 KB

```

```

From /proc/meminfo
MemTotal:      791028784 kB
HugePages_Total:    0
Hugepagesize:   2048 kB

```

```

/usr/bin/lsb_release -d
SUSE Linux Enterprise Server 12 SP2

```

```

From /etc/*release* /etc/*version*
SuSE-release:
SUSE Linux Enterprise Server 12 (x86_64)
VERSION = 12
PATCHLEVEL = 2
# This file is deprecated and will be removed in a future service pack or
release.
# Please check /etc/os-release for details about this release.
os-release:
NAME="SLES"
VERSION="12-SP2"
VERSION_ID="12.2"
PRETTY_NAME="SUSE Linux Enterprise Server 12 SP2"
ID="sles"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:12:sp2"

```

```

uname -a:
Linux kvasir 4.4.21-69-default #1 SMP Tue Oct 25 10:58:20 UTC 2016 (9464f67)
x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Sep 2 09:18

```

SPEC is set to: /spec
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sdal       xfs   650G  82G  569G  13% /

```

Additional information from dmidecode:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp2006 = 109

HPC S2600WF (Intel Xeon Silver 4114, 2.20 GHz)

SPECfp_base2006 = 105

CPU2006 license: 4204

Test date: Sep-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017

Platform Notes (Continued)

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Intel Corporation SE5C620.86B.0X.01.0007.060920171037 06/09/2017

Memory:

24x Kinston 9965640-006.A01G 32 GB 2 rank 2400 MHz

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

KMP_AFFINITY = "granularity=fine,compact,1,0"

LD_LIBRARY_PATH = "/spec/lib/ia32:/spec/lib/intel64:/spec/sh11.2"

OMP_NUM_THREADS = "20"

Binaries compiled on a system with 2x Intel Xeon-SP 4112 CPU + 192GB RAM memory using Redhat Enterprise Linux 7.3

Transparent Huge Pages enabled by default.

Filesystem page cache cleared with:

echo 1 > /proc/sys/vm/drop_caches

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64

416.gamess: -DSPEC_CPU_LP64

433.milc: -DSPEC_CPU_LP64

434.zeusmp: -DSPEC_CPU_LP64

435.gromacs: -DSPEC_CPU_LP64 -nofor_main

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 4



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp2006 = 109

HPC S2600WF (Intel Xeon Silver 4114, 2.20 GHz)

SPECfp_base2006 = 105

CPU2006 license: 4204

Test date: Sep-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017

Base Portability Flags (Continued)

```

436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -qopt-prefetch
```

C++ benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch
```

Fortran benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -qopt-prefetch
```

Benchmarks using both Fortran and C:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -qopt-prefetch
```

Peak Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp2006 = 109

HPC S2600WF (Intel Xeon Silver 4114, 2.20 GHz)

SPECfp_base2006 = 105

CPU2006 license: 4204

Test date: Sep-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xCORE-AVX2(pass 2)
-par-num-threads=1(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xCORE-AVX2(pass 2)
-par-num-threads=1(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xCORE-AVX2(pass 2)
-par-num-threads=1(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -unroll2 -inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xCORE-AVX2(pass 2)
-par-num-threads=1(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -unroll2 -inline-level=0
-qopt-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xCORE-AVX2(pass 2)
-par-num-threads=1(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -inline-calloc -qopt-malloc-options=3
-auto -unroll4

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

M Computers s.r.o.

SPECfp2006 = 109

HPC S2600WF (Intel Xeon Silver 4114, 2.20 GHz)

SPECfp_base2006 = 105

CPU2006 license: 4204

Test date: Sep-2017

Test sponsor: M Computers s.r.o.

Hardware Availability: Jul-2017

Tested by: M Computers s.r.o.

Software Availability: Apr-2017

Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic17.0-official-linux64-revF.html>

<http://www.spec.org/cpu2006/flags/MComputers-Platform-Settings-V1.2-revB.20170920.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic17.0-official-linux64-revF.xml>

<http://www.spec.org/cpu2006/flags/MComputers-Platform-Settings-V1.2-revB.20170920.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Wed Sep 20 11:01:38 2017 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 19 September 2017.