



SPEC CPU®2017 Integer Rate Results

Copyright 2017-2022 Standard Performance Evaluation Corporation

Alibaba Cloud

Alibaba Cloud Server Panjiu-M Series
(2.75GHz, T-Head Yitian 710)

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

CPU2017 License: 9070

Test Sponsor: Alibaba Cloud

Tested by: Alibaba Cloud

Test Date: Jun-2022

Hardware Availability: Sep-2022

Software Availability: May-2022

EC has determined that this result does not comply with the SPEC OSG Guidelines for General Availability and the SPEC CPU 2017 run and reporting rules. Specific details of the non-compliance and the submitter has notified SPEC that General Availability requirements were not met.

Copies

500.perlbench_r

502.gcc_r

505.mcf_r

520.omnetpp_r

523.xalancbmk_r

525.x264_r

531.deepsjeng_r

541.leela_r

548.exchange2_r

557.xz_r

Hardware

CPU Name: T-Head Yitian 710
Max MHz: 2750
Nominal: 2750
Enabled: 128 cores, 1 chip
Orderable: 1 chips
Cache L1: 64 KB I+D on chip per core
L2: 512 MB I+D on chip per core
L3: 64 MB I+D on chip per die (128 MB per chip)
Memory: 512 GB (8 x 64 GB 2Rx4 PC5-4800B-R)
Storage: 1 x 240 GB SATA SSD
Other: None

Software

OS: Anolis OS release 8.6
5.10.84-10.64k.al8.aarch64
Compiler: C/C++/Fortran: Version 10.2.1 of Red Hat GCC
Parallel: No
Firmware: Version 1.2.M1.AL.E.128.91 released Jun-2022
File System: xfs
System State: Run level 3 (multi-user)
Base Pointers: 64-bit
Peak Pointers: Not Applicable
Other: Jemalloc memory allocator library v5.2.1
Power Management: OS set to prefer performance at the cost of additional power usage



SPEC CPU®2017 Integer Rate Results

Copyright 2017-2022 Standard Performance Evaluation Corporation

Alibaba Cloud

Alibaba Cloud Server Panjiu-M Series
(2.75GHz, T-Head Yitian 710)

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

CPU2017 License: 9070

Test Sponsor: Alibaba Cloud

Tested by: Alibaba Cloud

Test Date: Jun-2022

Hardware Availability: Sep-2022

Software Availability: May-2022

SPEC has determined that this result does not comply with the SPEC OSG Guidelines for General Availability and the SPEC CPU 2017 run and reporting rules. Specific details of the non-compliance and the actions the submitter has notified SPEC that General Availability requirements were not met.

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
500.perlbench_r	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
502.gcc_r	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
505.mcf_r	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
520.omnetpp_r	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
523.xalancbmk_r	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
525.x264_r	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
531.deepsjeng_r	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
541.leela_r	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
548.exchange2_r	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
557.xz_r	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Notes

Binaries compiled on a Panjiu-M system with 1 x T-Head YiTian710 chip + 512 GB memory using Anolis 8.6

Submit Notes

The config file option 'submit' was used.
The option 'bind' was used to bind copies to the cores.

Operating System Notes

'ulimit -s unlimited' was used to set environment stack size
Set dirty_ratio=8 to limit dirty cache to 8% of memory
i.e. echo 8 | sudo tee /proc/sys/vm/dirty_ratio
Set swappiness=1 to swap only if necessary
i.e. echo 1 | sudo tee /proc/sys/vm/swappiness
Set zone_reclaim_mode=1 to free local node memory and avoid remote memory
i.e. echo 1 | sudo tee /proc/sys/vm/zone_reclaim_mode
Set drop_caches=3 to reset caches before invoking runcpu
i.e. echo 3 | sudo tee /proc/sys/vm/drop_caches
Set numa_balancing=0 to disable automatic numa balancing

(Continued on next page)



SPEC CPU®2017 Integer Rate Results

Copyright 2017-2022 Standard Performance Evaluation Corporation

Alibaba Cloud

Alibaba Cloud Server Panjiu-M Series
(2.75GHz, T-Head Yitian 710)

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

CPU2017 License: 9070

Test Sponsor: Alibaba Cloud

Tested by: Alibaba Cloud

Test Date: Jun-2022

Hardware Availability: Sep-2022

Software Availability: May-2022

SPEC has determined that this result does not comply with the SPEC OSG Guidelines for General Availability and the SPEC CPU 2017 run and reporting rules. Specific details of the non-compliance have been provided to the submitter. The submitter has notified SPEC that General Availability requirements were not met.

Operating System Notes (Continued)

```
i.e. echo 0 | sudo tee /proc/sys/kernel/numa_balancing
Switch off all ktune and tuned settings
i.e. sudo tuned-adm off
Transparent huge pages set to 'never' to prevent applications from allocating more memory resources than necessary.
i.e. sudo bash -c "echo never > /sys/kernel/mm/transparent_hugepage/enabled"
```

Environment Variables Notes

Environment variables set by runcpu before the start of the run:

```
LD_LIBRARY_PATH =
"/home/jemalloc-5.2.1/bin:/opt/rh/devtoolset-10/root/usr/bin//lib64:/opt/rh/devtoolset-10/root/usr/lib64:/opt/rh/devtoolset-10/root/usr/lib64:/opt/rh/devtoolset-10/root/usr/lib64/dyninst:/opt/rh/devtoolset-10/root/usr/lib/dyninst:/opt/rh/devtoolset-10/root/usr/lib64:/opt/rh/devtoolset-10/root/usr/lib"
```

General Notes

Jemalloc v. 5.2.1 is available via <https://github.com/jemalloc/jemalloc/releases/download/5.2.1/jemalloc-5.2.1.tar.bz2>
It was built on 5.10.84-10.64k.al8.aarch64 GCC10.2.1 with configure options
--prefix /root/jemalloc/install --with-lg-quantum=3

- NA: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.
- Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.
- NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Platform Notes

BIOS settings:
platform configure > memory configure > Enable NUMA Mode > Set to SubNuma mode
Yitian710 NUMA Control specifies the number of desired NUMA nodes per chip (default: 2-NUMA nodes).
SubNuma enable Setting: Dividing the chip into separate nodes may improve latency to the last

(Continued on next page)



SPEC CPU®2017 Integer Rate Results

Copyright 2017-2022 Standard Performance Evaluation Corporation

Alibaba Cloud

Alibaba Cloud Server Panjiu-M Series
(2.75GHz, T-Head Yitian 710)

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

CPU2017 License: 9070

Test Sponsor: Alibaba Cloud

Tested by: Alibaba Cloud

Test Date: Jun-2022

Hardware Availability: Sep-2022

Software Availability: May-2022

SPEC has determined that this result does not comply with the SPEC OSG Guidelines for General Availability and the SPEC CPU 2017 run and reporting rules. Specific details of the non-compliance and the submitter has notified SPEC that General Availability requirements were not met.

Platform Notes (Continued)

level cache and main memory which may benefit overall performance for NUMA-aware operating systems and workloads. Setting to 4-Numa nodes Per chip.
DDR MPAM setting : (Default: Enabled)
MPAM is a family of QoS/SLA services implemented through monitoring and partitioning of all the memory system components. It is beneficial for systems hosting VMs, and servers with a mix of background and demand processes requiring fair-share scheduling.
Set to "disable" to provide best memory bandwidth.

```
Sysinfo program /home/cpu2017/bin/sysinfo
Rev: r6622 of 2021-04-07 (82a61ec0915b55891ef0e16acafc64d)
running on localhost.localdomain Fri Jun 10 17:50:12 2022
```

SUT (System Under Test) info is seen by some common utilities.
For more information on this section, see
<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

```
From /proc/cpuinfo:
*
* Did not identify cpu model. If you would
* like to write your own sysinfo program, see
* www.spec.org/cpu2017/config.html#sysinfo
*
* 0 "physical id" tags found. Perhaps this is an older system,
* or a virtualized system. Not attempting to guess how to
* count chips/cores for this system.
```

128 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following
excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

```
From lscpu from util-linux 2.32.1:
Architecture: aarch64
Byte Order: Little Endian
CPU(s): 128
On-line CPU(s) list: 0-127
Thread(s) per core: 1
Core(s) per socket: 128
Socket(s): 1
NUMA node(s): 4
```

(Continued on next page)



SPEC CPU®2017 Integer Rate Results

Copyright 2017-2022 Standard Performance Evaluation Corporation

Alibaba Cloud

Alibaba Cloud Server Panjiu-M Series
(2.75GHz, T-Head Yitian 710)

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

CPU2017 License: 9070

Test Sponsor: Alibaba Cloud

Tested by: Alibaba Cloud

Test Date: Jun-2022

Hardware Availability: Sep-2022

Software Availability: May-2022

SPEC has determined that this result does not comply with the SPEC OSG Guidelines for General Availability and the SPEC CPU 2017 run and reporting rules. Specific details of the non-compliance and the submitter has notified SPEC that General Availability requirements were not met.

Platform Notes (Continued)

```

Vendor ID: ARM
BIOS Vendor ID: Alibaba
Model: 0
BIOS Model name: To.Be.Filled.By.P
Stepping: r0p0
BogoMIPS: 100.00
L1d cache: 64K
L1i cache: 64K
L2 cache: 1024K
L3 cache: 65536K
NUMA node0 CPU(s): 0-31
NUMA node1 CPU(s): 32-63
NUMA node2 CPU(s): 64-95
NUMA node3 CPU(s): 96-127
Flags: f asimd evtstrm aes pmull sha1 sha2 crc32 atomics fphp asimdhp
cpuid asimdrdm jscvt fcma lrcpc dcpop sha3 sm3 sm4 asimddp sha512 sve asimdfhm dit
uscat ilrcpc l1m ssbs sb dcpodp sve2 sveaes svepmull svebitperm svesha3 svesm4
flagm2 frint sve1m svebf16 i8mm bf16 dgh

```

```

From numactl --hardware
WARNING: a numa node 'node' might or might not correspond to a physical chip.
available: 4 nodes (0-3)
node 0 cpus: 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27
28 29 30
node 0 size: 130807 MB
node 0 free: 121857 MB
node 1 cpus: 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56
57 58 59 60 61 62 63
node 1 size: 130923 MB
node 1 free: 121267 MB
node 2 cpus: 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88
89 90 91 92 93 94 95
node 2 size: 130923 MB
node 2 free: 111448 MB
node 3 cpus: 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114
115 116 117 118 119 120 121 122 123 124 125 126 127
node 3 size: 130859 MB
node 3 free: 120581 MB
node distances:
node 0 1 2 3

```

(Continued on next page)



SPEC CPU®2017 Integer Rate Results

Copyright 2017-2022 Standard Performance Evaluation Corporation

Alibaba Cloud

Alibaba Cloud Server Panjiu-M Series
(2.75GHz, T-Head Yitian 710)

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

CPU2017 License: 9070

Test Sponsor: Alibaba Cloud

Tested by: Alibaba Cloud

Test Date: Jun-2022

Hardware Availability: Sep-2022

Software Availability: May-2022

SPEC has determined that this result does not comply with the SPEC OSG Guidelines for General Availability and the SPEC CPU 2017 run and reporting rules. Specific details of the non-compliance and the submitter has notified SPEC that General Availability requirements were not met.

Platform Notes (Continued)

```

0: 10 15 40 40
1: 15 10 40 40
2: 40 40 10 15
3: 40 40 15 10

```

From /proc/meminfo

MemTotal: 536078144 kB

HugePages_Total: 0

Hugepagesize: 524288 kB

/sbin/tuned-adm active

Current active profile: virtual-guest

From /etc/*release* /etc/*version*

anolis-release: Anolis OS release 8.6

os-release:

NAME="Anolis OS"

VERSION="8.6"

ID="anolis"

ID_LIKE="rhel fedora centos"

VERSION_ID="8.6"

PLATFORM_ID="platform:an8"

PRETTY_NAME="Anolis OS 8.6"

ANSI_COLOR="0;31"

redhat-release: Anolis OS release 8.6

system-release: Anolis OS release 8.6

uname -a:

Linux localhost.localdomain 5.10.84-10.64k.al8.aarch64 #1 SMP Wed Jan 26 10:20:10 CST 2022 aarch64 aarch64 aarch64 GNU/Linux

Kernel self-reported vulnerability status:

CVE-2018-12207 (iTLB Multihit):	Not affected
CVE-2018-3620 (L1 Terminal Fault):	Not affected
Microarchitectural Data Sampling:	Not affected
CVE-2017-5754 (Meltdown):	Not affected
CVE-2018-3639 (Speculative Store Bypass):	Mitigation: Speculative Store Bypass disabled via prctl
CVE-2017-5753 (Spectre variant 1):	Mitigation: __user pointer

(Continued on next page)



SPEC CPU®2017 Integer Rate Results

Copyright 2017-2022 Standard Performance Evaluation Corporation

Alibaba Cloud

Alibaba Cloud Server Panjiu-M Series
(2.75GHz, T-Head Yitian 710)

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

CPU2017 License: 9070

Test Sponsor: Alibaba Cloud

Tested by: Alibaba Cloud

Test Date: Jun-2022

Hardware Availability: Sep-2022

Software Availability: May-2022

SPEC has determined that this result does not comply with the SPEC OSG Guidelines for General Availability and the SPEC CPU 2017 run and reporting rules. Specific details of the non-compliance and the submitter has notified SPEC that General Availability requirements were not met.

Platform Notes (Continued)

CVE-2017-5715 (Spectre variant 2):	sanitization
CVE-2020-0543 (Special Register Buffer Data Sampling):	Not affected
CVE-2019-11135 (TSX Asynchronous Abort):	Not affected

run-level 3 Sep 29 19:51

SPEC is set to: /home/cpu2017

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/mapper/ao-home	xfs	148G	41G	108G	28%	/home

```

From /sys/devices/virtual/dmi/id
Vendor:      Alibaba Cloud
Product:     AliServer-Kuandwu2.0AM-02-1UC1P-5B
Product Family: TO.Be.Filled.By.PTG

```

Additional information from dmidecode 3.3 follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

```

Memory:
 7x Hynix HMC94MEBRA109N 64 GB 2 rank 4800
 7x Hynix HMC94MEBRA123N 64 GB 2 rank 4800

```

```

BIOS:
  BIOS Vendor:      Alibaba
  BIOS Version:     1.2.M1.AL.E.128.91
  BIOS Date:        06/02/2022

```

(End of data from sysinfo program)

Compiler Version Notes

```

-----
C          | 500.perlbench_r(base) 502.gcc_r(base) 505.mcf_r(base)
          | 525.x264_r(base) 557.xz_r(base)
-----

```

```

gcc (GCC) 10.2.1 20210130 (Red Hat 10.2.1-11)
Copyright (C) 2020 Free Software Foundation, Inc.

```

(Continued on next page)



SPEC CPU®2017 Integer Rate Results

Copyright 2017-2022 Standard Performance Evaluation Corporation

Alibaba Cloud

Alibaba Cloud Server Panjiu-M Series
(2.75GHz, T-Head Yitian 710)

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

CPU2017 License: 9070

Test Sponsor: Alibaba Cloud

Tested by: Alibaba Cloud

Test Date: Jun-2022

Hardware Availability: Sep-2022

Software Availability: May-2022

SPEC has determined that this result does not comply with the SPEC OSG Guidelines for General Availability and the SPEC CPU 2017 run and reporting rules. Specific details of the non-compliance and the submitter has notified SPEC that General Availability requirements were not met.

Compiler Version Notes (Continued)

This is free software; see the source for copying conditions. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

```
=====  
C++      | 520.omnetpp_r(base) 523.xalanlib_r(base) 531.deepsjeng_r(base)  
         | 541.leela_r(base)  
=====
```

```
g++ (GCC) 10.2.1 20210130 (Red Hat 10.2.1-11)  
Copyright (C) 2020 Free Software Foundation, Inc.  
This is free software; see the source for copying conditions. There is NO  
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  
=====
```

```
=====  
Fortran  | 548.exchange2_r(base)  
=====
```

```
GNU Fortran (GCC) 10.2.1 20210130 (Red Hat 10.2.1-11)  
Copyright (C) 2020 Free Software Foundation, Inc.  
This is free software; see the source for copying conditions. There is NO  
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  
=====
```

Base Compiler Invocation

benchmarks:

gcc

C++ benchmarks:

g++

Fortran benchmarks:

gfortran



SPEC CPU®2017 Integer Rate Results

Copyright 2017-2022 Standard Performance Evaluation Corporation

Alibaba Cloud

Alibaba Cloud Server Panjiu-M Series
(2.75GHz, T-Head Yitian 710)

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

CPU2017 License: 9070

Test Sponsor: Alibaba Cloud

Tested by: Alibaba Cloud

Test Date: Jun-2022

Hardware Availability: Sep-2022

Software Availability: May-2022

SPEC has determined that this result does not comply with the SPEC OSG Guidelines for General Availability and the SPEC CPU 2017 run and reporting rules. Specific details of the non-compliance have been provided to the submitter. The submitter has notified SPEC that General Availability requirements were not met.

Base Portability Flags

```

500.perlbench_r: -DSPEC_LINUX_AARCH64 -DSPEC_LP64
502.gcc_r: -DSPEC_LP64
505.mcf_r: -DSPEC_LP64
520.omnetpp_r: -DSPEC_LP64
523.xalancbmk_r: -DSPEC_LINUX -DSPEC_LP64
525.x264_r: -DSPEC_LP64
531.deepsjeng_r: -DSPEC_LP64
541.leela_r: -DSPEC_LP64
548.exchange2_r: -DSPEC_LP64
557.xz_r: -DSPEC_LP64

```

Base Optimization Flags

C benchmarks:

```

-mabi=lp64 -std=c99 -L/opt/rh/devtoolset-10/root/usr/bin//lib64
-L/opt/rh/devtoolset-10/root/usr/bin//lib -L/home/jemalloc-5.2.1/lib -g
-O3 -mcpu=neoverse-n1 -funroll-loops -flto=32
--param early-inlining-insns=96 --param max-inline-insns-auto=64
--param inline-unit-growth=96 -fgnu89-inline -ljemalloc

```

C++ benchmarks:

```

-mabi=lp64 -std=c++03 -L/opt/rh/devtoolset-10/root/usr/bin//lib64
-L/opt/rh/devtoolset-10/root/usr/bin//lib -L/home/jemalloc-5.2.1/lib -g
-O3 -mcpu=neoverse-n1 -funroll-loops -flto=32
--param early-inlining-insns=256 --param max-inline-insns-auto=128
--param inline-unit-growth=256 -ffinite-loops -ljemalloc

```

Fortran benchmarks:

```

-mabi=lp64 -L/opt/rh/devtoolset-10/root/usr/bin//lib64
-L/opt/rh/devtoolset-10/root/usr/bin//lib -L/home/jemalloc-5.2.1/lib -g
-O3 -mcpu=neoverse-n1 -funroll-loops -flto=32
--param ipa-cp-eval-threshold=1 --param ipa-cp-unit-growth=80
--param ipa-cp-max-recursive-depth=8 -fno-inline-functions-called-once
-fstack-arrays -flto-partition=one -ljemalloc

```



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Alibaba Cloud

Alibaba Cloud Server Panjiu-M Series
(2.75GHz, T-Head Yitian 710)

SPECrate®2017_int_base =

SPECrate®2017_int_peak =

CPU2017 License: 9070

Test Sponsor: Alibaba Cloud

Tested by: Alibaba Cloud

Test Date: Jun-2022

Hardware Availability: Sep-2022

Software Availability: May-2022

EC has determined that this result does not comply with the SPEC OSG Guidelines for General Availability and the SPEC CPU 2017 run and reporting rules. Specific details of the non-compliance have been provided to the submitter. The submitter has notified SPEC that General Availability requirements were not met.

Base Other Flags

C benchmarks:

-fcommon -Wl, -Map, mapfile

C++ benchmarks:

-Wl, -Map, mapfile

Fortran benchmarks:

-Wl, -Map, mapfile

The flag file that was used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/gcc.2021-07-21.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2017/flags/gcc.2021-07-21.xml>

Non-Compliant

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2017 v1.1.8 on 2022-06-10 17:50:11-0400.

Report generated on 2022-11-04 18:44:04 by CPU2017 PDF formatter v6442.

Originally published on 2022-07-05.