



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_med_base = 0.3115

ThinkSystem SR665 V3 (AMD EPYC 9654)

SPEChpc 2021_med_peak = 0.3115

hpc2021 License: 28


Test Date: Jan-2023

Test Sponsor: Lenovo Global Technology

Hardware Availability: Nov-2022

Tested by: Lenovo Global Technology

Software Availability: Nov-2022



Results Table

Benchmark	Base								Peak									
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
705.lbm_m	OMP	96	8	1987	0.617	1904	0.643	1976	0.620	OMP	96	8	1987	0.617	1904	0.643	1976	0.620
718.tealeaf_m	OMP	96	8	6190	0.218	6312	0.214	6309	0.214	OMP	96	8	6190	0.218	6312	0.214	6309	0.214
719.clvleaf_m	OMP	96	8	6867	0.269	6898	0.268	6824	0.271	OMP	96	8	6867	0.269	6898	0.268	6824	0.271
728.pot3d_m	OMP	96	8	8452	0.219	8444	0.219	8477	0.218	OMP	96	8	8452	0.219	8444	0.219	8477	0.218
734.hpgmgfv_m	OMP	96	8	3779	0.265	3738	0.268	3735	0.268	OMP	96	8	3779	0.265	3738	0.268	3735	0.268
735.weather_m	OMP	96	8	5544	0.433	5503	0.436	5415	0.443	OMP	96	8	5544	0.433	5503	0.436	5415	0.443

SPEChpc 2021_med_base = 0.3115

SPEChpc 2021_med_peak = 0.3115

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_med_base = 0.3115

ThinkSystem SR665 V3 (AMD EPYC 9654)

SPEChpc 2021_med_peak = 0.3115

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Jan-2023
Hardware Availability: Nov-2022
Software Availability: Nov-2022

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: ThinkSystem SR665 V3
Interconnect: Nvidia Mellanox ConnectX-6 HDR
Compute Nodes Used: 4
Total Chips: 8
Total Cores: 768
Total Threads: 1536
Total Memory: 6 TB
Max. Peak Threads: 8

Software Summary

Compiler: Intel oneAPI Compiler 2022.1.0
MPI Library: Intel MPI Library for Linux OS, Build 20220227
Other MPI Info: --
Other Software: --
Base Parallel Model: OMP
Base Ranks Run: 96
Base Threads Run: 8
Peak Parallel Models: OMP
Minimum Peak Ranks: 96
Maximum Peak Ranks: 96
Max. Peak Threads: 8
Min. Peak Threads: 8

Node Description: ThinkSystem SR665 V3

Hardware

Number of nodes: 4
Uses of the node: Compute
Vendor: Lenovo Global Technology
Model: ThinkSystem SR665 V3
CPU Name: AMD EPYC 9654
CPU(s) orderable: 1,2 chips
Chips enabled: 2
Cores enabled: 192
Cores per chip: 96
Threads per core: 2
CPU Characteristics: Max Boost Clock up to 3.7 GHz
CPU MHz: 2400
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: 384 MB I+D on chip per chip
32 MB shared / 8 cores
Other Cache: None
Memory: 1536 GB (24 x 64 GB 2Rx4 PC5-4800B-R)
Disk Subsystem: 1x ThinkSystem 2.5" 5300 480GB SSD
Other Hardware: None
Accel Count: --
Accel Model: --
Accel Vendor: --
Accel Type: --
Accel Connection: --
Accel ECC enabled: --
Accel Description: --
Adapter: Nvidia Mellanox ConnectX-6 HDR
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 200 Gb/s
Ports Used: 1

Software

Accelerator Driver: --
Adapter: Nvidia Mellanox ConnectX-6 HDR
Adapter Driver: 5.7-1.0.2
Adapter Firmware: 20.28.1002
Operating System: Red Hat Enterprise Linux Server release 8.6,
Kernel 4.18.0-372.9.1.el8.x86_64
Local File System: xfs
Shared File System: None
System State: Multi-user, run level 3
Other Software: None

(Continued on next page)



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_med_base = 0.3115

ThinkSystem SR665 V3 (AMD EPYC 9654)

SPEChpc 2021_med_peak = 0.3115

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Jan-2023
Hardware Availability: Nov-2022
Software Availability: Nov-2022

Node Description: ThinkSystem SR665 V3

Hardware (Continued)

Interconnect Type: ConnectX-6 HDR

Interconnect Description: Nvidia Mellanox ConnectX-6 HDR

Hardware

Vendor: Nvidia
Model: Nvidia Mellanox ConnectX-6 HDR
Switch Model: QM8700
Number of Switches: 1
Number of Ports: 40
Data Rate: 200 Gb/s
Firmware: 3.9.0606
Topology: Mesh
Primary Use: MPI Traffic, NFS Access

Software

: --

Submit Notes

The config file option 'submit' was used.

```
submit = mpiexec -hostfile ${top}/4nodes -np ranks -genv OMP_NUM_THREADS=$threads -ppn % {NRNK} $command
```

Compiler Version Notes

```
=====
FC 719.clvleaf_m(base, peak) 728.pot3d_m(base, peak) 735.weather_m(base,
peak)
-----
```

```
Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version
2022.1.0 Build 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
ifx: command line error: no files specified; for help type "ifx -help"
-----
```

```
=====
CC 705.lbm_m(base, peak) 718.tealeaf_m(base, peak) 734.hpgmgfv_m(base,
peak)
-----
```

```
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
Version 2022.1.0 Build 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
clang: warning: -Z-reserved-lib-stdc++: 'linker' input unused
[-Wunused-command-line-argument]
-----
```



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_med_base = 0.3115

ThinkSystem SR665 V3 (AMD EPYC 9654)

SPEChpc 2021_med_peak = 0.3115

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Jan-2023
Hardware Availability: Nov-2022
Software Availability: Nov-2022

Base Compiler Invocation

C benchmarks:

mpiicc -cc=icx

Fortran benchmarks:

mpiifort -fc=ifx

Base Portability Flags

705.lbm_m: -lstdc++
718.tealeaf_m: -lstdc++
719.clvleaf_m: -lstdc++
728.pot3d_m: -lstdc++
734.hpgmgfv_m: -lstdc++
735.weather_m: -lstdc++

Base Optimization Flags

C benchmarks:

-Ofast -mprefer-vector-width=512 -march=core-avx2 -ipo -fiopenmp
-ansi-alias

Fortran benchmarks:

-Ofast -mprefer-vector-width=512 -march=core-avx2 -ipo -fiopenmp
-nostandard-realloc-lhs -align array64byte

Base Other Flags

C benchmarks (except as noted below):

-Ispecmpitime

734.hpgmgfv_m: -Ispecmpitime

Fortran benchmarks:

719.clvleaf_m: -Ispecmpitime



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_med_base = 0.3115

ThinkSystem SR665 V3 (AMD EPYC 9654)

SPEChpc 2021_med_peak = 0.3115

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Jan-2023
Hardware Availability: Nov-2022
Software Availability: Nov-2022

Peak Compiler Invocation

C benchmarks:

mpiicc -cc=icx

Fortran benchmarks:

mpiifort -fc=ifx

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

705.lbm_m: basepeak = yes

718.tealeaf_m: basepeak = yes

734.hpgmgfv_m: basepeak = yes

Fortran benchmarks:

719.clvleaf_m: basepeak = yes

728.pot3d_m: basepeak = yes

735.weather_m: basepeak = yes

Peak Other Flags

C benchmarks (except as noted below):

-Ispecmpitime

734.hpgmgfv_m: -Ispecmpitime

Fortran benchmarks:

719.clvleaf_m: -Ispecmpitime



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_med_base = 0.3115

ThinkSystem SR665 V3 (AMD EPYC 9654)

SPEChpc 2021_med_peak = 0.3115

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Jan-2023
Hardware Availability: Nov-2022
Software Availability: Nov-2022

The flags file that was used to format this result can be browsed at
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2022-11-10.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2022-11-10.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2018-06-25 12:55:08-0400.
Report generated on 2023-02-22 12:26:51 by hpc2021 PDF formatter v1.0.3.
Originally published on 2023-02-22.